



QUOTATION

Demo

North Eastern Rescue Vehicles, Inc
 Bob Reilly
 10 Dwight Park Drive
 Syracuse, NY 13209
 (315) 414-9999
 Robert.Reilly@nervinc.com

Job/Order No: 710174

WO#: 710174

Page 1

| DESCRIPTION | QTY |
|--|-----|
| WC Transit | |
| WARRANTY | |
| WC, Warranty, Conversion, 12 Month | 1 |
| WC, Warranty, Limited Electrical | 1 |
| WC, Warranty, Cabinet Construction | 1 |
| CERTIFICATIONS REQUIRED | |
| VN, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10. | 1 |
| All cabinets shall be labeled as to their capacity Rating. | |
| VAN CHASSIS | |
| WC, 2024 Ford, AWD Transit 350, Gas3.5L EcoBoost V6, 148" WB High Roof Estimated (2) OEM Alternator Includes dual batteries 12V OEM outlet in dash Engine Hour meter in OEM Gauge Cluster includes OEM Back up camera option All wheel drive with steel wheels | 1 |
| HIGH IDLE | |
| -- VN, High Idle Controls, 2023+ Transit, Relay Plex | 1 |
| -- VN, Tire Pressure Monitoring System, OEM. Light in Dash | 1 |
| BASE CONVERSION | |
| -- VN, Conversion Transit High Roof, Gas 23-1 CONVERSION | 1 |

| DESCRIPTION | QTY | | |
|---|-----|--|--|
| <ul style="list-style-type: none"> - Install anti-slip decal on curbside and rear stainless steel thresholds, STD | | | |
| <p>INCLUDES THE FOLLOWING</p> | | | |
| <ul style="list-style-type: none"> - (1) Antenna pre-wire located behind Driver's Seat, | | | |
| <ul style="list-style-type: none"> -12V protection Blade style breakers with Manual reset | | | |
| <ul style="list-style-type: none"> - Static air intake and Power exhaust | | | |
| <ul style="list-style-type: none"> - R-11 Reflective insulation Insulation | | | |
| <ul style="list-style-type: none"> - Street side and Curbside Perco I. V. Hooks with Velcro straps | | | |
| <ul style="list-style-type: none"> - 60 square inches of Red/White reflective material on each door. | | | |
| <p>SHIP LOOSE (1) 5 lb ABC Fire Extinguisher</p> | | | |
| <p style="text-align: center;">VAN TOPS</p> | | | |
| <ul style="list-style-type: none"> -- VN, Top, High Roof Transit OEM -700 Series | 1 | | |
| <ul style="list-style-type: none"> -- VN, Housings, Cast, Rear Door LH/RH Warning Lts, High Roof Transit | 1 | | |
| <ul style="list-style-type: none"> To Be Installed On Upper Rear Doors- 9x7 lights | | | |
| <ul style="list-style-type: none"> -- VN, Light Valance, Rear, Interior, for 500 Series lights, Transit | 1 | | |
| <ul style="list-style-type: none"> - will contain (2) red, (1) amber, (2) load lights R-C-A-C-R | | | |
| <ul style="list-style-type: none"> -- VN, Whelen, Light, TIR6, LED, Red, w/flg, Valance Only | 2 | | |
| <ul style="list-style-type: none"> - Mounted outboard on ABS Housing inside rear doors | | | |
| <ul style="list-style-type: none"> - Primary/Secondary, when rear doors are opened, flash pattern | | | |
| <ul style="list-style-type: none"> -- VN, Whelen, Light, TIR6, LED, Amber, w/flg, Valance Only | 1 | | |
| <ul style="list-style-type: none"> - Mounted on center of ABS Housing inside rear doors | | | |
| <ul style="list-style-type: none"> - Primary/Secondary, when rear doors are opened, flash pattern, per Engineering | | | |
| <ul style="list-style-type: none"> -- VN, Scene Lighting, 5L w/Flange, Valance Only | 2 | | |
| <ul style="list-style-type: none"> - (2) mounted on ABS housing inside rear doors | | | |
| <ul style="list-style-type: none"> -- VN, Driver's side Light on Rear | 1 | | |
| <ul style="list-style-type: none"> -- VN, Light, Whelen 900 LED, Red, Clear Lens, | 1 | | |
| <ul style="list-style-type: none"> -- VN, Scene Lighting, LED, Whelen, Clear, | 1 | | |
| <ul style="list-style-type: none"> -- VN, Passengers's side Light on Rear | 1 | | |
| <ul style="list-style-type: none"> -- VN, Light, Whelen 900 LED, Red, Clear Lens, | 1 | | |
| <ul style="list-style-type: none"> -- VN, Scene Lighting, LED, Whelen, Clear, | 1 | | |

| DESCRIPTION | QTY | | |
|---|-----|--|--|
| -- VN, Whelen, Lights, Pair, Wide Angle ION Amber LED, Chrome Housing -On rear doors These lights are to be on with drive and if emergency lights are on in park. | 2 | | |
| (1) INLINE FROM THE TOP OF THE Rear Driver side Red 7L light. Left side of the light (1) INLINE FROM THE TOP OF THE Rear Passenger side Red 7L light . Right side of the light | | | |
| -- VN, Housings, Cast, (4) Side Warning/Scene Lights, High Roof Transit (1) 9L Warning Light & (1) 7 Series Scene Light will fit in each housing. | 1 | | |
| -- VN, Front Light on Driver's side | 1 | | |
| -- VN, Light, Whelen 900 LED, Red, Clear Lens, External Flash | 1 | | |
| -- VN, Scene Lighting, 7L, #7SC0ENZR, LED | 1 | | |
| -- VN, Rear Light on Driver's side | 1 | | |
| -- VN, Light, Whelen 900 LED, Red, Clear Lens, External Flash | 1 | | |
| -- VN, Scene Lighting, 7L, #7SC0ENZR, LED | 1 | | |
| -- VN, Front Light on Passenger's side | 1 | | |
| -- VN, Light, Whelen 900 LED, Red, Clear Lens, External Flash | 1 | | |
| -- VN, Scene Lighting, 7L, #7SC0ENZR, LED | 1 | | |
| -- VN, Rear Light on Passenger's side | 1 | | |
| -- VN, Light, Whelen 900 LED, Red, Clear Lens, External Flash | 1 | | |
| -- VN, Scene Lighting, 7L, #7SC0ENZR, LED | 1 | | |
| -- VN, Front Housing, HR, Whelen for (6) 700 size Warning lights- Transit ABS cowl to hold lighting. | 1 | | |
| -- VN, Front Upper, Driver outboard position #1 | 1 | | |
| -- VN, Light, Whelen 700 LED, Red, Clear Lens, | 1 | | |
| -- VN, Front Upper, Driver inboard position #2 | 1 | | |
| -- VN, Light, Whelen 700 LED, Red, Clear Lens, | 1 | | |
| -- VN, Front Upper, Driver Center position #3 | 1 | | |
| -- VN, Light, Whelen 700 LED, Clear, 70C02SCR | 1 | | |
| -- VN, Front Upper, Passenger Center position #4 | 1 | | |
| -- VN, Light, Whelen 700 LED, Clear, 70C02SCR | 1 | | |
| -- VN, Front Upper, Passenger inboard position #5 | 1 | | |
| -- VN, Light, Whelen 700 LED, Red, Clear Lens, | 1 | | |
| -- VN, Front Upper, Passenger outboard position #6 | 1 | | |
| -- VN, Light, Whelen 700 LED, Red, Clear Lens, | 1 | | |
| INTERIOR CABINETS | | | |
| -- VN, Cabinet Package, Transit, High Roof, Aluminum, O2 at CS Rear | 1 | | |

| DESCRIPTION | QTY | | |
|--|-----|--|--|
| White Painted Aluminum Cabinets | | | |
| -- VN ,Painted Aluminum Cabinets, MultiSpec White/White Aluminum cabinets painted inside and out | 1 | | |
| -- VN, Cabinet, HR Transit, Alum Bulk Head Wall, Pass-thru Only - Front bulk head will be a solid wall with a window (pass through) approximately 17"H x 10.5" wide off center toward driver's side. | 1 | | |
| -- VN, RF Cabinet, Aluminum, HR Transit, CS Rear O2 Cabinet, No BB, Version "B" L1- Open with one adjustable shelf L2 - Enclosed cabinet- 15.25" H x 23.75" W x 14.50" D With Drop down door facing rear. L3 - to accommodate (2) Portable O2 bottles L4 - 11"H x 38.5" W x 22.25" D Open slot for Stair chair storage- Open to CS Door | 1 | | |
| -- VN, O2 Cylinder Holder, Single, Cast, Strapless Duramount "D", CN 10 Certified | 2 | | |
| -- VN, Squad Bench Cabinet, Transit, Aluminum, Drop in Bio waste at head - Sharps and trash under separate lid at head of Bench with access holes - Single squad bench Lid, - with 60# Gas Strut Style Hold Open | 1 | | |
| -- VN, Lids, Hinged, Red Engraved Sharps and Trash 5.25" x 8.375"- Waste 4.5" x 4.5" -Sharps | 1 | | |
| -- VN, Squad bench Latches, Transit, Trimark handles (2) | 1 | | |
| -- VN, Cabinet, Transit, Curbside Upper Cabinet (3) Glove storage boxes at front with lift up Lexan door (1) Cabinet 7.5" H x 34.25" W x 5.25" D with top hinged Lexan door, tension hinges, | 1 | | |
| -- VN, Cabinet, Vertical O2, Foot of Squad Bench, HR Transit, Zico Rack , M Cyl. Vertical storage & Zico QRMV O2 cylinder rack at foot of squad bench Hinged solid door with latch. | 1 | | |
| -- VN, Cabinet, Aluminum Base wall, Transit, High Roof - Three Glove storage at rear, Rear hinged Lexan access -Backboard storage slot accessed from rear access doors under "D1" and "D2" - Cabinet "A" - 24.25" H x 28.5" W x 9" D. Sliding Poly carbonate Doors. With one (1) adjustable shelf | 1 | | |

| DESCRIPTION | QTY | ID | REF. NO |
|--|-----|----|---------|
| - Cabinet "B" - 24.25" H x 28.5" W x 9" D. Sliding Poly carbonate Doors. With one (1) adjustable shelf | | | |
| - Cabinet "C" - 24.25" H x 28.5" W x 9" D. Sliding Poly carbonate Doors. With one (1) adjustable shelf | | | |
| - Cabinet "D1" - 24.25" H x 28.5" W x 11.5" D. Sliding Poly carbonate Doors. With one (1) adjustable shelf | | | |
| - Cabinet "D2" - 24.25" H x 28.5" W x 11.5" D. Sliding Poly carbonate Doors. With one (1) adjustable shelf | | | |
| - Cabinet "M" Drug box -10.75" H x 11.5" W x 8" D with hinged Solid Door | | | |
| Must label weight limit on doors and drawers for CN 10 certification | | | |
| -- VN, Poly carbonate, Gray ,HR 1/4" poly carbonate | 1 | | |
| -- VN, Sliding doors with latching handles 1/4" poly carbonate sliding doors with Spring loaded latching handles | 5 | | |
| -- VN, Latch, Southco, Lever, Non Locking, Black, CN 10 Certified 5 Lb. | 2 | | |
| -- VN, Latch, Southco, Lever, Locking, Black, CN 10 Certified 5 Lb. | 1 | | |
| VAN HVAC SYSTEMS | | | |
| -- VN, Heat/AC System, Transit Gas, Webasto (Alum Cabinets) with thermostat on CS Wall Located above cab area/Attendant seat | 1 | | |
| FRONT END ALIGNMENT | | | |
| Front End Alignment, None- QC Check -Standard | 1 | | |
| VN, Third (3rd) Brake light, Transit OEM on roof | 1 | | |
| CAB INTERIOR OPTIONS | | | |
| VN, Door Panels, Transit Entry Doors, Vacuum Formed- Std | 1 | | |
| U Reflective tape to Cover Rear and Side Entry Doors-All holes | 1 | | |
| Install reflective tape to cover Rear door panel holes and install Ford OEM Decal for door opening knob | | | |
| - Reflective tape to cover ALL OEM holes in the interior panels of the rear entry doors ILOS | | | |
| - 24/7 to install (2) "SLIDE TO OPEN" decals to right rear inside | | | |

| DESCRIPTION | QTY | | |
|--|-----|--|--|
| release door. | | | |
| DOOR REFLECTORS & FLASHERS | | | |
| VN, Reflective Material, rear patient Doors, Sprinter/Transit - Rear doors to have 60 sq inches of 3M reflective material, 6" red | 1 | | |
| REAR BUMPER AND REAR STEP CONSTRUCTION | | | |
| VN, Rear Bumper, Step, OEM, Transit | 1 | | |
| -- VN, Rear Bumper, Diamond Plate with Grip strut insert | 1 | | |
| INSULATION | | | |
| VN, Insulation, Walls and Ceiling, Reflectix Foil Lined Bubble Wrap | 1 | | |
| SPLASH GUARDS AND RUNNING BOARDS | | | |
| VN, Mud Flaps, Front & Rear, Transit, Molded, No Logo | 1 | | |
| FLOORING | | | |
| VN, Flooring, Lonplate II, Midnight #443TX | 1 | | |
| Ceiling Grab Rail - Center | | | |
| VN, Ceiling Grab Rail, 72", Handicap Style, Anti-Microbial Yellow, Footless - Yellow Powder Coat Finish | 1 | | |
| GRAB HANDLES | | | |
| U Grabhandles, (1) 12" Yellow Wall Mounted | 3 | | |
| (1) Curbside Rear wall by rear doors (1) Streetside Rear wall by rear doors (1) CS wall at head of squad bench | | | |
| IV FLUID HANGERS | | | |
| VN, IV Hook, Perco, W/Straps Each SS wall centered CS wall centered | 2 | | |
| SEAT BELTS/ SAFETY NETS | | | |
| VN, Squad Bench, Seatbelt, Assy, (4 Point), Per4Max, Yellow, (2) Each - Two above the squad bench lid mounted seat belts | 1 | | |
| VN, Head of Squad Bench, Safety Net, Yellow, Transit | 1 | | |
| ATTENDANT SEAT | | | |
| VN, Attendant's Seat, EVS 1860 Fold up w/child seat on CBPED (R) Base, Black Yellow 3 Point seat belt Seat base CBPED (offset Right) | 1 | | |
| UPHOLSTERY | | | |
| VN, Upholstery, Black Seamless Squad bench backrests 2" thick and 18" wide. Squad bench full length seat cushion 2.5" thick. | 1 | | |

| DESCRIPTION | QTY | | |
|--|-----|--|--|
| VN, Strap, Two Inch Seatbelt style (1) across Backboard slot opening (1) across Stair chair storage opening | 2 | | |
| Camera, Patient Compartment | 1 | | |
| Mount monitor to the left of the steering wheel. | | | |
| In the patient compartment mount the camera on the rear headliner next to the StreetSide cabinets facing the cot. | | | |
| Trigger camera display on with Master Switch. | | | |
| 07 - ELECTRICAL 12 VOLT DC | | | |
| VN, 12 Volt Electrical System, Van, RelayPlex System Transit - Circuit board located in lower section of the base wall toward the front. | 1 | | |
| Flash Pattern- Quad Flash 75 - Per KKK | | | |
| POWER SOURCES | | | |
| VN, Power Source, 12VDC, 20A, Battery Switch/Ignition Hot Radio Power #1- | 1 | | |
| -- Power Source Location, Behind Driver's seat | 1 | | |
| VN, Power Source, 12VDC, 20A, Battery Switch/Ignition Hot Radio Power #2- | 1 | | |
| -- Power Source Location, Behind Driver's seat | 1 | | |
| VOLTMETER | | | |
| VN, Voltmeter, Smart with Low Voltage Alarm, Audio/Visual Light and Buzzer in cab console. | 1 | | |
| BATTERY SYSTEM | | | |
| VN, Battery Switch, RelayPlex Electronic w/5 min Timer - Activated thru OEM ignition switch, timer function upon ignition "off". - Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer. - (2) OEM batteries - ONLY conversion power is turned on/off. - Chassis power is NOT turned off. | 1 | | |
| VN, Power Outlet, Power Point Style, (2), in A/A - (2) in Action Area - Ignition Hot | 1 | | |
| VN, Power Outlet, Power Point Style, Each Mounted above head of squad bench - Ignition Hot | 1 | | |
| VN, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel Style Location in the Engine cover console switch panel. - Ignition Hot | 1 | | |

| DESCRIPTION | QTY | | |
|--|-----|--|--|
| FRONT CONSOLE | | | |
| VN, Console, Drivers Switch & Radio, Cab, Transit, Aluminum, 2020, CN 11 - With Map Box - Black Rubber coated Aluminum. - Angled Area: Switches - Flat Area: Siren and Radio area | 1 | | |
| | | | |
| -- VN, Drivers Control Panel, Transit, Switches in OEM Console | 1 | | |
| -- VN, Action Area Switch Panel, Eaton Esport switches, Relocate CS Wall | 1 | | |
| SIREN ELECTRONIC - CONTROL HEADS / AMPS | | | |
| VN, Siren Electronic, Whelen, WS-295-SLSA1 | 1 | | |
| SIREN SPEAKERS | | | |
| VN, Speakers, Cast, Black Powder coat, SAP3825-20Transit-6BW, SAP3826-20Transit-6B | 1 | | |
| BACK-UP ALARMS | | | |
| VN, Back-up Alarm, Auto Reset, 97 dBA, No Cutoff Switch | 1 | | |
| VN, Switch, Emergency Master, Non Sequenced | 1 | | |
| WARNING LIGHTS -WHELEN MICRON | | | |
| VN, Whelen, Micron, Red w/chrome Flange, Internal Flasher (2) in grille; Mounted in upper section of Grille wired thru external flasher, . (2) in grille; Internal Flasher -Mounted in lower section of Grille install in Chrome flange. | 4 | | |
| VN, Whelen, Light, LIN3, LED-Red, RSRO2ZCR (2) as Front intersection lights on front fenders (2) Whelen LIN3 Red LEDs with clear lenses one each side of chassis forward of OEM rear Brake lights. These lights are to be located at the same height as FRONT INTERSECTIONS and 12" from front edge of taillights to center of Whelen LIN3 LED. Wired on w/Emergency lights primary only. (2) Whelen LIN3 Red LEDs with clear lenses rear of unit mounted one each side just above rear Brake lights. Wired on w/Emergency lights primary only. | 6 | | |
| VN, Scene Lighting, CS, Activate on Opening of CS Entry Door | 1 | | |
| 11 - INTERIOR LIGHTING | | | |
| VN, Dome Lights, LED, Whelen, White Flange, (6), STD, Sprinter/Transit NOTE: NO VISABLE FASTENERS OR HOLES. | 1 | | |
| (3) Street side (3) Curbside - Transit | | | |
| VN, Timer, Momentary Switch, 15 Minute, Constant Hot Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to street side dome lights in liner on high. | 1 | | |
| ATTENDANT LIGHT | | | |
| VN, Attendant Light, Action Area, Grote LED Strip | 1 | | |
| SHORELINE INLET | | | |
| VN, Shoreline, Twistlock, 20 A - driver's side, standard location - (2) outlets std, (1) in A/A, (1) upper RF cabinet | 1 | | |

| DESCRIPTION | QTY | | |
|---|-----|--|--|
| VN, Inverter/Charger, Vanner LifeSine, LSC12-1100 LifeSine inverter will be ignition switch activated, No Inverter switch. | 1 | | |
| AUXILIARY ENVIRONMENTAL SYSTEMS | | | |
| VN, Exhaust Fan, Single 12V Blower with Vent on exterior. | 1 | | |
| VN, Thermostat, Manual, Wabasto Cot Mounts | 1 | | |
| VN, Cot Mount, Stryker, 6392 Performance load w/Floor Plate, No Inductive Charge | 1 | | |
| -- Side Mount | 1 | | |
| OXYGEN AND AIR SYSTEMS | | | |
| VN, O2 Wrench, Tether in Oxygen Cabinet | 1 | | |
| VN, O2 Regulator, Preset 50PSI | 1 | | |
| VN, O2 System, Storage Rear Vertical Cabinet, Ohio Style, (2) A/A, (1) Liner - Ohio Style | 1 | | |
| - (2) O2 Outlet in A/A | | | |
| - (1) O2 Outlet in C/S Liner @ Head of S/B | | | |
| SUCTION SYSTEM | | | |
| VN, Suction Pump, Electric, SSCOR 90206 | 1 | | |
| VN, Suction System, SSCOR Disposable with Canister Clip deletes the Ohio style vacuum outlet - plumb hose from SSCOR canister through hole in AA wall panel Meets SAE J3043 Requirements | 1 | | |
| VN, Fire Extinguisher, 5# ABC with Surface Mount Bracket, Each HD Amerex Bracket #861H with Amerex 5LB fire extinguisher. | 1 | | |
| PAINT AND FINISH | | | |
| Van, Paint, Single Color, OEM White Ford white | 1 | | |
| | 1 | | |