



North Eastern Rescue Vehicles, Inc  
 10 Dwight Park Drive  
 Syracuse, NY 13209

DESCRIPTION	QTY	ID
<b>WARRANTY</b>		
WC, Warranty, Conversion, 12 Month	1	
WC, Warranty, Paint, 60 month Prorated, Standard	1	
WC, Warranty, Structural, 20 Years, Std., Mods	1	
WC, Warranty, Limited Electrical	1	
WC, Warranty, Cabinet Construction	1	
<b>== WC- Type 3 CitiMedic Gen2 148" - 1.023 01/31/22 ==</b>		
<b>CERTIFICATIONS REQUIRED</b>		
This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.	1	
MD, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	1	
All cabinets shall be labeled as to their capacity Rating.		
<b>01- CHASSIS REQUIREMENTS</b>		
<b>FORD CHASSIS</b>		
S CM, 2025 Ford E350, 7.3L, Gasoline,Cutaway, 138"WB	1	
Auto throttle OEM Ford (1) OEM Alternator Includes 2nd battery Cab Headliner Vinyl W/ Ford CO-Pilot 360		
Domestic Chassis	1	
<b>SUSPENSION</b>		
Rear Suspension, OEM Springs	1	
<b>HIGH IDLE</b>		
High Idle Controls, OEM	1	
<b>FRONT END ALIGNMENT</b>		
Front End Alignment, None- QC Check -Standard	1	
<b>OUTSIDE REAR VIEW MIRRORS</b>		
Mirrors, Sail Mount, OEM Mirrors	1	
<b>WHEEL COVERS</b>		

DESCRIPTION	QTY		
CM, Wheel Covers, Phoenix #NF12, Installed,E-Series with Air Max Valve Extenders	1		
<b>BASE CONVERSION</b>			
CM, Conversion, Type 3, 148 Module, Ford - 23-1	1		
<b>CAB EXTENSION</b>			
CM, 8" Cab Extension, Ford, CitiMedic E350	1		
<b>MODULE BODIES:</b>			
CM, Interior Headroom, 68 Inches	1		
CM, Module, Type 3, 148" Body Length, 90" wide, Duraseam Doors, Cutaway 148" L x 90" W	1		
CM, Aisle Space, 49", CityMedic Plus (48-49" actual)	1		
<b>EXTERIOR MODULE CONSTRUCTION</b>			
CM, Stone Guard, Front, Diamond Plate, Type 3, Standard Height	1		
<b>FUEL FILLS &amp; SPLASH PLATE</b>			
CM, Housing Fuel Fill, Cast, Type III	1		
<b>REAR KICKPLATE</b>			
CM, Rear Kick plate,Under-Ride Bumper, w/ Tag recess, No lights, CM+	1		
<b>SUB-FLOOR SYSTEM</b>			
CM, Flooring, 3/4" Marine Grade Plywood, Type 3/7/9	1		
<b>MODULE DOORS, HANDLES &amp; HOLD OPENS</b>			
CM, Duraseam Hinged Doors with Hidden Jamb - Magnetic door switches, Standard	1		
CM, Hold Open Rear Entry Doors, (2) 5.5" Cast Grabber - Installed so doors will open as wide as possible - Mount at Bottom of doors.	1		
CM, Hold Open, Gas Strut, Curb Side Entry Door, 35#	1		
CM, Patient Entry Door Handles, Trimark Black/Chrome Pull Handle w/"Push Button"	1		
With Round Push button Emergency release top and bottom of interior door panels.			
CM, Rear Entry Door Trailing Latch, Side release Paddle	1		
CM, Electrical Feed to Required Doors, Spring Protector (Per Door)	8		
<b>POWER DOOR LOCKS</b>			
CM, Power Door Lock, Trimark, Each Entry Door <b>Module entry doors.</b>	2		
CM, Power Door Lock, Trimark, Each Compartment Door <b>All module compartments(except battery comp)</b>	5		
CM, Power Door Locks, All Module doors (except Batt) <b>Access Doors and Module Compartment doors (except Battery) for electric locks, wiring to CS wall for Switch.</b>	1		
<b>Includes the Tie in to the Cab door lock switches.</b>			

DESCRIPTION	QTY		
CM, Switch, Stealth, for Power Door Locks In grille on passenger's side.	1		
CM, Relay Control Circuit, Power Door Locks	1		
CM, Circuit, OEM Door Lock to activate Mod Doors (Not Dodge)	1		
<b>ENTRY DOOR INNER PANELS</b>			
CM, Entry Door Panels, Durasafe, S/S, w/ Chevrons & Blue Reflective Logo	1		
- Durasafe Design			
- Aluminum Center Panels covered: white/blue reflective tape			
- Logo to be cut in the lower entry door panel with a Blue reflective 3M material (to match the chevron on the lock box) attached to an aluminum panel behind the logo.			
<b>SIDE DOOR STEP</b>			
CM, Side Entry Step Well, Type III, Aluminum Diamond Plate	1		
CM, Light, Side Entry Step well, LED, 2", Whelen	1		
<b>WINDOWS</b>			
CM, Window, Upper, CS/Slider ,Rr/Fixed, Privacy Tint, PAN Curbside window with lower slider section	1		
Rear windows fixed			
Privacy Tint			
<b>REAR BUMPER AND REAR STEP CONSTRUCTION</b>			
CM, Rear Bumper, Ford Cutaway, w/LED Lights with Gator Grip on flip up step. Lights in side of bumper pod Steady burn with lights on	1		
CM, BLACK Polyurethane Coating, Rear Bumper Supports	1		
<b>INSULATION</b>			
CM, Insulation, Fiberglass, Un faced	1		
<b>RUB RAIL AND FENDER RINGS</b>			
CM, Rub Rails, Skirt Line, Extruded "C" channel (E-one Style), 148"	1		
CM, Tape, Reflective, White, For Extruded Skirt rails	1		
CM, Fender Flare, Black Rubber	1		
<b>SPLASH GUARDS AND RUNNING BOARDS</b>			
CM, Mud Flaps, Rear, w/ Wheeled Coach Logo	1		
CM, Running Boards, Ford Cutaway, w/Gator Grip,	1		
<b>CAB TO MODULE ACCESS</b>			
CM, Bulkhead Cabinet, Type 3, walk-thru w/8" Cab extension - with 8" extended cab area - With walk thru door	1		
CM, Bulkhead, Door, Sliding w/Sliding Window with sliding Lexan window	1		
<b>LICENSE PLATE HOLDER</b>			
CM, License Plate Holder, Cast LP0002, for Under ride Bumper in rear kick plate, centered License holder comes with (2) LED lights.	1		
<b>EXTERIOR COMPARTMENT CONSTRUCTION</b>			
CM, Compartments, Std, Floor Drop Down Compartment #2 - 2.5" drop Compartment #4 - 4" drop Compartment #6 (5.5" for spare tire)	3		

DESCRIPTION	QTY		
CM, Compartments, Sweep out Compartments #1 & #8 are standard sweep out	2		
CM, Door Sill Protector, Stainless, All Comps CM, Compartments, Diamond Plate Finish Per Comp Machine stamped louvers located above the floor line for venting.	1 4		
Comp #2,4,6			
Comp #1 to have Baffle vent			
CM, Exterior Battery Compartment, Diamond Plate Finish <b>EXTERIOR COMPARTMENT DOORS</b>	1		
CM, Compartment Comp Handle, Trimark, Oval Pull Handle, Black/Chrome <b>COMPARTMENT DOOR HOLD OPEN</b>	6		
CM, Hold Open, Gas Strut, Ext Comp, 30lb. Compartments "#6", "#1", & "#2"	3		
CM, Hold Open, Gas Strut, Comp Door Only, 110 Degree, 30lb, Comp #4 to allow easier access to the Stair chair.	1		
CM, Hold Open, Gas Strut, RF Comp, 30lb <b>COMPARTMENT LIGHTING</b>	1		
CM, Oxygen Light, 3" Surface mount Whelen LED, Clear Mounted in Oxygen Compartment on ceiling.	1		
CM, Compartment Light, 4" Optronic,#BUL43-CBK, LED, Each Compartment	5		
1 - Access Panel Wall 1 2 - Wall #1 4 - Ceiling 6 - Wall #3 8- Wall #3 in access panel			
<b>COMPARTMENT #1 - STREETSIDE FWD</b>			
CM, Compartment #1, 3/4 High, CitiMedic. <b>COMPARTMENT #2 - STREETSIDE FWD WHEELWELL</b>	1		
CM, Compartment #2, Citimedic , Type 3 Mount the inverter on the ceiling of compartment.	1		
CM, Compartment #2, Shelf, ADP, Fixed for Electrical storage Screw in shelf that extends from wall 1 to the recessed suction and wall 2 to flush with the face of the suction dogleg Round Edges Of Shelves	1		
Add Dogleg in Comp #2 for Recessed Suction in Face of A/A <b>COMPARTMENT #4 - STREETSIDE AFT</b>	1		
CM, Compartment #4, Full Height, Dual Depth, Citimedic - Full height backboard storage on the #4 compartment door. - The upper section is 8" D due to dogleg for interior cabinetry. Bottom section is 15" deep.	1		
Floor drop of 4" for the entire compartment			

DESCRIPTION	QTY		
CM, Compartment #4, Strap, Seat Belt Style, Each (1) on comp #4 door for Backboards	2		
(1) from wall #1 to Wall #3 about 6" from wall 2 for the Stair chair.			
CM, Compartment #4, Bracket, Backboard Mount on Door Diamond plate "C-style boxes mounted to the door of Comp #4  one at top and bottom to allow backboards or scoop stretcher to be slid in from the outboard side	1		
<b>COMPARTMENT #6 - CURBSIDE AFT</b>			
CM, Compartment #6, Spare Tire, With special Drop pan for spare tire.	1		
CM, Compartment #6, Shelf, Custom, Adjustable, First Shelf Shelves, All Ext. Compartment, Delete Stanpro, Round Edges of Shelves	1		
No sharp edges on shelves			
<b>COMPARTMENT #8 - CURBSIDE UPPER FORWARD</b>			
CM, Compartment #8/8.5, Split Doors, 8" Cab Extension, Upper compartment, with inside /outside access  Lower compartment for battery	1		
CM, Compartment #8, Shelf, Adjustable, First Shelf RF Comp "8"/cabinet "U8" area - centered top to bottom. Round Edges Of Shelves	1		
CM, Compartment #8, Shelf, Additional, Adjustable, Each RF Comp "8"/cabinet "L8" area centered top to bottom. Round Edges Of Shelves	1		
<b>INTERIOR TRIM AND FEATURES</b>			
CM, Interior Cabinets, Duralite Construction, Wood CM, Cabinet Shelf, Interior, Wood, Adjustable, First shelf Cabinet U4, Cabinet C6, U6	1		
CM, Cabinet Shelf, Interior, Wood, Additional, Adjustable U4	1		
CM, Cabinet Shelf Track, #HA24663, Upgrade, CN 10 ("C" channel/exterior shelf style track)  Cabinet U4 U6, C6	3		
<b>HEADLINER</b>			
CM, Headliner, Flat, PVC, Hinged trough cover	1		

DESCRIPTION	QTY		
<b>FLOORING</b>			
CM, Flooring, Lonplate II, Gunpowder Gray #424TX	1		
CM, Flooring, Roll up, 3-4" Approx....., No Toe Kick	1		
The roll up is not recessed it is installed on the cabinet wall and Squad bench.			
CM, Floor, Thresholds, .063 Aluminum, Painted w/Black Poly-urea coating	1		
<b>GRAB RAILS</b>			
<b>Rear Entry Door Grab Handles</b>			
CM, Entry Door Grab Handles (3), "L" Shape, 1", Yellow	1		
Yellow Powder Coat Finish Grab Handles			
<b>Ceiling Grab Rail - Center</b>			
CM, Ceiling Grab Rail, Overhead, 84", 1" Diameter Handicap Style, Yellow	1		
Yellow Powder Coat Finish			
<b>IV FLUID HANGERS</b>			
CM, IV Hangers, Perco (1), W/Straps Each	2		
Location: (1) CS wall centered between seats			
<b>BASEWALL CABINET:</b>			
CM, Cabinet, Base wall, 8" ext, CPR Seat, w/Telemetry Area, Recessed suction	1		
Telemetry area to have Poured black surface			
Cabinet L3.5			
CM, Cabinet, Street side Upper, 148 Module, w/CPR Seat , 68" HR	1		
Cabinet U2, U1 wood door			
CM, Street side rear, with side seat, 68" HR	1		
Cabinet U4 with (2) adjustable shelves			
Cabinet U3.5			
CM, Tray, A/A, Std Aisle No Bio waste, Poured, Black	1		
CM, Door, U1 Hinged Wood	1		
U1 cabinet will be used as a locking drug cabinet.			
CM, Door, U2 Gray Poly carbonate Slider, CN 10 Compliant	1		
<b>Interior Street side #3 - CPR Seat</b>			
CM, CPR side seat, Fixed Backrest	1		
CM, CPR, Lid, Hinged Flip Up	1		
With Trimark Latch			
CM, Door, U3.5, OHO Top Hinged Gray Poly carbonate (CWTG) CN 10 Complia	1		
CM, Door, L3.5, OHO Bottom Hinged Gray Poly carbonate, (CWBD) CN 10 Comp	1		
CM, Door, U4, OHO Dual Hinged Gray Poly carbonate (CWDX) CN 10 Compliant	1		
CM, CPR Seat, "U" Barrier Bar, Padded, 1.5" SS, Gunmetal	1		
Mounted at the front of the CPR side seat vertically in line with the Padded head cushion on the "U2" cabinets.			
CM, Telemetry Tray, Poured, Black	1		

DESCRIPTION	QTY		
<b>SQUAD BENCH AREA</b>			
CM, Cabinet, Squad Bench, CM+, w/ Bio waste	1		
With Bio waste at the head of the squad bench cabinet.			
CM, Lid, Squad Bench, Single W/Bio-Waste Must use M1 latch for CN 10 on bio waste door Lift up lid ONLY over storage area	1		
CM, Squad Bench, Handle, Trimark, STD	1		
CM, Strut, Gas, 60 LB, Installed	1		
CM, CPR, Handle, Trimark, STD	1		
CM, Bio-waste Cover, Etched Red Plastic	1		
<b>SEAT BELTS/ SAFETY NETS</b>			
CM, CPR Seat, Seatbelt, Assy, (4 Point), Per4Max, Yellow, (1) Each, CN-8 Above the lid	1		
CM, Squad Bench, Seatbelt, Assy, (4 Point) Per4Max, Yellow, (2) Each Above the lid On squad bench	1		
CM, Patient Restraint Belts, Squad Bench (3)	1		
CM, Safety Net, Head of Squad Bench, 2" Straps, Yellow attached to floor at head of squad bench, CS wall and overhead liner with removable latches.	1		
<b>CURBSIDE REAR</b>			
CM, Cabinet, Curbside Rear, In Rear wall, U6,C6 Gray OHO doors (1) adjustable shelf in cabinet U6 (1) adjustable shelf in cabinet C6	1		
<b>BIOHAZARD-</b>			
CM, Glove Butler-Cabinet, (3),Above C/S door Must use M1 latches for KKK Change notice 10 certification	1		
<b>CURBSIDE RIGHT STACK STORAGE #8</b>			
Hasp, Installed on U1 Cabinet IATS	1		
CM, RF ALS, Split Upper/Lower, HVAC at Top <b>Option A</b> <b>U8 L8 ISOS Access</b>	1		
CM, Doors, RF, U8, Dual Gen III OHO, Poly carbonate Doors, Gray	1		
CM, Doors, RF, L8, Dual Gen III OHO, Poly carbonate Doors, Gray	1		
<b>ATTENDANT SEAT</b>			
CM, Attendant's Seat, EVS 1880,Comfort, Hi-Back Child Safety w/Per4Max	1		
CM, Color, Gunmetal, Per4Max Belt, Yellow	1		
CM, Door, Diamond Plate, EVS Seat Base, M1 Latch	1		

DESCRIPTION	QTY		
CM, Attendant's Seat Base, EVS CBS Box Style Box opening to be toward CURBSIDE access door """"TO BE MOUNTED AS FAR FORWARD AS POSSIBLE TO MAXIMIZE KNEE ROOM"""" Forawrd to BH Cabinet	1		
<b>INTERIOR COLORS</b>			
CM, Backrest Cushion, EVS, Gunmetal, w/ WC Logo, Each <b>CABINET KICK PANELS</b>	1		
CM, Kick plate, Brushed SS, Face of S/B & Base wall, 148 CM <b>CABINET LATCHES- INTERIOR</b>	1		
CM, Latch, Southco, Lever, Chrome, Locking, CN 10-Rated 5lb Cabinet U1	1		
CM, Latch, M1, 3/4" Material, 2" round, Non Locking, Chrome-CN 10 Certified Sharps/Waste, GB	2		
CM, Latch, Southco M1, 2" S/S, (1/4" Door) Non-locking, CN 10-Rated 10lb (self latching) Flush Mount. Non-Locking Attendant seat door.	1		
<b>06 - ELECTRICAL GENERAL</b>			
CM, 12V Electrical system, RelayPlex system Flash Pattern- Quad Flash 75 - Per KKK	1		
Camera, Patient Compartment and Back Up	1		
Monitor to the left of the steering wheel.			
In the module mount the camera on the curbside rear of the headliner. Trigger camera display on with Master Switch.			
#HC IR250 rear back up camera with #HC20M video cable, Mount camera exterior on rear of module, off center toward driver's side. Triggered when units placed in reverse gear			
<b>COMMUNICATION</b>			
CM, Coax Cable, RG58/U, Each, Terminate: CS Dome #2 to behind pass seat with 6' pigtails S/Side From Dome #4 to behind the drivers seat with 6' pigtails S/Side From Dome #5 to behind the pass seat with 6' pigtails Hot and Ground	3		
CM, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.	1		



DESCRIPTION	QTY		
<b>POWER SOURCES</b>			
CM, Power Source, 12VDC, 20A, Ignition/Shoreline Hot (1) pre-wire coil and tagged in action area (1) pre-wire coil and tagged behind driver's seat.	2		
CM, Power Source, 12 VDC, 20 Amp (+-), Constant Hot Termination: (1) in Action Area (1) in cab console	2		
CM, Power Source, 12VDC, 40A, Constant Hot (1) Install a 40Amp Power and ground wired CONSTANT hot to a Buss bar inside the center console (1) Install a 40Amp Power and ground wired IGNITION hot to a Buss bar inside the center console	2		
CM, Buss Bar Assembly (+/-), 5 Position, (1) Power and (1) Ground Location: Front chassis cab console	2		
<b>VOLTMETER</b>			
CM, Alarm, Low Voltage, Audio/Visual Light in cab console and Buzzer in cab.	1		
<b>BATTERY SYSTEM</b>			
CM, Battery Switch, RelayPlex Electronic w/5 min Timer, Ford T3, Gasoline - Activated thru OEM ignition switch, timer function upon ignition "off". - Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer. - ONLY Module power is turned on/off. - Chassis power is NOT turned off.	1		
<b>12VDC OUTLETS</b>			
CM, Power Outlet, Power Point Style, (2), (1) Action Area (1) RF ALS Cabinet on standard 20-amp ignition hot circuit. - (1) outlet in action area - (1) in RF Cabinet "U8", wall #2, upper right	1		
CM, Power Outlet, Power Point Style, Each (1) Above squad bench, 18" up from the top deck of the squad bench, 3" over from the edge of the foot of squad bench wall. (1) in RF Cabinet L8, wall #2, upper right Ignition sw hot (1) Constant hot front bulkhead wall	3		
CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel Ignition Hot (1) Located in the cab switch panel passenger side. (1) located top left of console face. (1) located top right of console face.	3		
CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel, Addition Location in the Action area outlet panel. Ign Hot	1		

DESCRIPTION	QTY		
<b>FRONT CONSOLE</b>			
CM, Console, Drivers Switch & Radio, Center, Aluminum, Black, Ford cutaway Black polyurethane coated .090 Aluminum	1		
CM, Double Blank Panel	1		
CM, Cup Holder Panel	1		
WC, Flat Switch Panel	1		
<b>ATTENDANT CONTROL PANEL</b>			
CM, Action Area Switch Panel, Eaton Esport switches, Relocate CS Wall	1		
<b>SIREN ELECTRONIC - CONTROL HEADS / AMPS</b>			
CM, Siren Electronic, Whelen, WS-295-SLSA1	1		
<b>SIREN SPEAKERS</b>			
CM, Speakers, (2), Cast, SAD4319/SAP4319, In Bumper, Ford Cutaway	1		
CM, Switch, Siren/Horn Thru Horn Ring	1		
<b>BACK-UP ALARMS</b>			
CM, Back-Up Alarm, No Cutoff Switch	1		
CM, Switch, Emergency Master, Non Sequenced	1		
XS CM, Amber LED Beacon, Whelen L31HAF, Installed on roof of module No switch Module roof, centered 16" inboard from rear of module, Beacon will be on anytime Ignition is on and unit is in gear.	1		
<b>WARNING LIGHT FLASHERS</b>			
brake lights, comet flash, steady burn when brake is applied.			
CM, Steady Burn Light Kit, (1) Each -Rear of module red 9L Reds	1		
<b>WARNING LIGHTS</b>			
<b>LED Series - 900 (Flange Separate)</b>			
CM, Light, Whelen 900 LED, Red, Clear Lens, 90RR5SCR, External Flasher	12		
Street side Body - Upper Forward			
Street side Body - Upper Rear			
Curbside Body - Upper Forward			
Curbside Body - Upper Rear			
Rear Body - Upper Street side Corner			
Rear Body - Upper Curbside Corner			
Pri/Sec			
Front Body - Upper Curbside Inner (Cool bar)			
Front Body - Upper Street side Inner (Cool bar)			
Pri only			
Front Body - Upper Street side - angled portion of cool bar			
Front Body - Upper Curbside - angled portion of cool bar			
Pri only			
Rear Body - Lower Street side corner			
Rear Body - Lower Curbside corner			
ILO rear window lights			

DESCRIPTION	QTY		
<p>Pri/Sec W/Brake override</p> <p>CM, Light, Whelen 900 LED, Amber, Clear Lens, 90AA5SCR, External Flasher</p> <p>Rear Body - Upper Center</p>	1		
<p>CM, Light, Whelen 900 LED, Clear, 90CC5SCR, External Flasher</p> <p>Front Body - Upper Center (Cool bar)</p>	1		
<p>CM, Flange, Super 900 LED, #90FLANGC</p> <p><b>LED Series - 700 (Flange Separate)</b></p>	14		
<p>CM, Light, Whelen 700 LED, Red, Clear Lens, 70R02SCR</p> <p>(2)Front Body - Upper Curbside Corner</p> <p>(2)Front Body - Upper Street side Corner</p> <p>Pri/Sec</p> <p>(2) as rear intersections over rear wheel wells.</p> <p>Pri/Sec internal comet flash</p> <p>(2)Front intersection lights</p>	8		
<p><b>WHELEN FLANGES 7 SERIES LIGHTS (Flange Separate)</b></p>			
<p>CM, Flange, Whelen, For 7E lights (1), Mods For 7 Series Lights</p>	8		
<p><b>WARNING LIGHTS -WHELEN TIR3/LIN3 (Flange Separate)</b></p>			
<p>CM, Light, Whelen, LIN3, LED-Red, RSRO2ZCR w/Flg</p> <p>(2) Upper front grille lights Pri only internal comet flash</p> <p>(2) Lower front grille lights Pri only internal comet flash</p>	4		
<p>CM, Flange, Whelen, Chrome, For LIN3, Each</p> <p><b>EXTERIOR AUTOMOTIVE LIGHTING</b></p>	4		
<p>CM, Taillight Pkg, Whelen, LED Stop/Tail, Turn &amp; LED Backup, w/WC logo</p> <ul style="list-style-type: none"> <li>- Brake- Steady Burn</li> <li>- Turn Arrow – sequential arrow</li> <li>- 700 LED Backup</li> </ul> <p>Clear lens over all three lights</p>	1		
<p><b>ICC/MARKER LIGHTS</b></p>			
<p>CM, Light, Red, 2", Marker, LED, Each</p> <p>(2) in sides of rear bumper as running lights</p>	2		
<p>CM, Marker/Clearance Lights, Red, LED</p> <p>(3) On rear as clearance lights.</p>	3		
<p>CM, Light, Clearance, Amber LED</p> <p>(3) On Front of module as clearance lights.</p>	3		
<p>CM, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers</p> <p>- High intensity flashers;Primary/Secondary- As marker lights with headlights</p>	1		
<p><b>FLOOD AND LOAD SYSTEMS</b></p>			
<p>CM, Light, LED, Whelen, Clear, #9SC0ENZR, 24 LED, (1) w/ Chrome Flange</p>	6		

DESCRIPTION	QTY		
(2) each side as scene lights (2) on rear as load lights			
CM, Scene Lights, C/S, Activated with C/S Door Master Hot.	1		
<b>11 - INTERIOR LIGHTING</b>			
CM, Dome Lights, LED, Whelen, White Flange, (3)S/S, (3)C/S, CM+ Three (3) street side in liner and three (3) curbside in liner equally spaced	1		
Each side controlled by separate switch in action area standard. High/Off/Low			
NOTE: NO VISABLE FASTENERS OR HOLES.			
CM, Timer, Momentary Switch, 15 Minute, Constant Hot Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to street side dome lights in liner on high.	1		
WC, No Lighting Recessed into Trough Cover	1		
<b>SPOTLIGHTS / HANDHELD LIGHTS</b>			
CM, Handheld Spotlight, Novatech, Nighthawk 2000, 100,000 CP	1		
<b>ATTENDANT LIGHT</b>			
CM, Light, Intertek ZY-PIR38 12v, LED, In A/A	1		
<b>SHORELINE INLET</b>			
CM, Super Auto Eject, 20A, White Cover above comp "#2"	1		
<b>OUTLETS - 125VAC</b>			
CM, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet in the RF Cabinet "U8", wall #2, upper right.	1		
CM, Outlet, 125 VAC, Duplex, Additional, Each (1) Interior CS above foot end of squad bench mounted approx. 14" up and over 3" from rear wall. (1) telemetry area, wall 2 near wall 1, down low (1) SS of walk through down low facing RF cabinet window.	3		
<b>BLOCKHEATERS</b>			
Block Heater - With OEM Plug This option does not include a switch.	1		
CM, Inverter/Charger, Vanner LifeSine Mounted on the ceiling of compartment 2	1		
CM, Exhaust Fan, Single 12V Blower with "clamshell" vent on exterior rear of unit.	1		
<b>CITIMEDIC HVAC SYSTEM</b>			
CM, Generation I, Steel Cool Bar cover	1		
CM, Thermostat, Manual, Wabasto	1		

DESCRIPTION	QTY		
CM, Heat/AC, F3, Combo, w/Coolbar with thermostat in action area.	1		
12vdc External Condenser, in Coolbar mounted on front of module. Painted to match front of module.			
CM, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo	1		
<b>COT MOUNTING PROVISIONS</b>			
<b>Safety Hooks</b>			
CM, Cot Mount, Stryker, Rear Safety Hook Installed	1		
<b>Cot Mounts</b>			
CM, Stryker Performance/Power Load, Add Floor Structure	1		
Additional floor structure for future installation of a Stryker Power Load or Performance Load w/ inductive charging System.			
Includes pre-wire which will terminate under the module head of cot.			
CM, Cut Floor and Install Stryker Floor Plate, 6390-700-001A	1		
CM, Power source for Induction Charging, 12V, 10 Amp constant hot	1		
Center Mount	1		
<b>OXYGEN AND AIR SYSTEMS</b>			
CM, O2 Cylinder Wrench, Tethered in oxygen compartment.	1		
CM, Rack, Multiversal, Zico #QR-MV, W/ Straps	1		
<b>M Cylinder</b>			
CM, Track, Unistrut for Oxygen Rack	1		
CM, Manual, O2 System	1		
CM, O2 Regulator, Preset 50PSI	1		
CM, O2 System, Ohio Style, (2 AA, 1 Vac DISS, 1 Liner, 1 C/S)	1		
<b>Recessed Suction</b>			
<b>Ohio style outlets</b>			
<b>(2) oxygen outlets in action area</b>			
<b>(1) vacuum port in action area</b>			
<b>(1) oxygen outlet in liner at head of cot</b>			
<b>(1) oxygen outlet curbside wall at head of squad bench</b>			
CM, Lexan Flap, w/Hinge	1		
<b>SUCTION SYSTEM</b>			
CM, Suction Pump, SSCOR 90206 mounted in compartment "2"	1		
CM, Suction Holder, SSCOR 23002 with w/Canister Clip & Regulator	1		
WC, Suction Outlet and Container located in Action area recess in recessed pocket	1		

DESCRIPTION	QTY		
<b>PAIN T AND FINISH</b>			
WC, Wheeled Coach Paint Process	1		
CM, Module Paint, Single Color, OEM White	1		
Ford white: FA91:YZ			
Cab Paint - Single Color, OEM White	1		
<b>PAIN T STRIPING DESIGN</b>			
Paint Belt, None	1		