



QUOTATION

North Eastern Rescue Vehicles DEMO
 Bob Reilly
 10 Dwight Park Drive
 Syracuse, NY 13209

North Eastern Rescue Vehicles, Inc.
 Bob Reilly

Job/Order No: 640063

WO#: 640063

Page 1

DESCRIPTION		QTY
INFORMATION		
WARRANTY		
WC, Warranty, Conversion, 12 Month		1
WC, Warranty, Paint, 60 month Prorated, Standard		1
WC, Warranty, Structural, 20 Years, Std., Mods		1
WC, Warranty, Limited Electrical		1
WC, Warranty, Cabinet Construction		1
CERTIFICATIONS REQUIRED		
This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.		1
WC, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10.		1
All cabinets shall be labeled as to their capacity Rating.		
01- CHASSIS REQUIREMENTS		
FORD CHASSIS		
S WC, 2026 Ford E450, 7.3L Gasoline, Cutaway, 158" WB (2) OEM Alternator Includes 2nd battery located in RF comp. Rubber floor mat, OEM, std. Cab Headliner Vinyl		1
Domestic Chassis		1
ALTERNATORS		
Alternator(s) - Standard OEM		1
SUSPENSION		
Rear Suspension, OEM Springs		1
HIGH IDLE		
High Idle Controls, OEM		1
FRONT END ALIGNMENT		

DESCRIPTION	QTY
Front End Alignment, None- QC Check	1
OUTSIDE REAR VIEW MIRRORS	
Mirrors, Sail Mount, OEM Mirrors	1
WHEEL COVERS	
WC, Wheel Covers, Phoenix #NF12, Installed, E-Series, with Air Max Valve Extenders,	1
BASE CONVERSION	
WC, Conversion, Type III, 170 Module, Ford- 23-1	1
CAB EXTENSION	
WC, 10" Cab Extension	1
Cab Extension to utilize same flooring as Module floor.	
WC, Interior Headroom, 72 Inches	1
WC, Module, Type 3. 170" Body Length, Duraseam Doors,	1
Cutaway 170" L x 95" W	
WC, Body Width 95" Standard	1
WC, Aisle Space, 50", Type 3 (49-50" actual)	1
STRUCTURAL FRAMING - RFP	
WC, Type 3, General Body Construction Spec	1
WC, Type 3, Vehicle Body Structure Spec	1
EXTERIOR MODULE CONSTRUCTION	
WC, Stone Guard, Front, Diamond Plate, Type 3, Standard Height	1
FUEL FILLS & SPLASH PLATE	
WC, Housing Fuel Fill, Cast Aluminum, Type III	1
REAR KICKPLATE	
WC, Rear Kick plate, Under-Ride Bumper, w/ Tag recess, No lights	1
SUB-FLOOR SYSTEM	
WC, Flooring, 3/4" Marine Grade Plywood, Type 3/7/9	1
MODULE ENTRANCE	
WC, Module Access, CS Door standard location	1
MODULE DOORS, HANDLES & HOLD OPENS	
WC, Duraseam Hinged Doors with Hidden Jamb - Magnetic door switches, Standard	1
WC, Hold Open Rear Entry Doors, (2) 6" Door Grabber - Installed so doors will open as wide as possible	1
WC, Hold Open - Gas Strut, Curb Side Entry Door, 35#	1
WC, Patient Entry Door Handles, Trimark Black/Chrome Pull Handle w/"SafePass" With Round Push button Emergency release top and bottom of interior door panels.	1
WC, Rear Entry Door Trailing Latch, Side release Paddle	1
WC, Electrical Feed to Required Doors, Spring Protector (per Door)	8
POWER DOOR LOCKS	
WC, Power Door Lock, Trimark, Each Entry Door Module entry doors.	2

DESCRIPTION	QTY		
WC, Power Door Lock, Trimark, Each Compartment Door All module compartments(except battery comp) .	6		
WC, Switch, Momentary Rocker,Activate Power Door Locks (1) C/S wall at head of S/B.	1		
WC, Switch, Remote Stealth, Cab/Mod Doors In grille on passenger's side.	1		
WC, Relay Control Circuit, Power Door Locks	1		
WC, Circuit, OEM Door Lock to activate Mod Doors	1		
ENTRY DOOR INNER PANELS			
WC, Entry Panels, Durasafe, Stainless Steel, w/ Center - Durasafe Design - Aluminum Center Panels covered: reflective tape	1		
SIDE DOOR STEP			
WC, Side Entry Step Well, Type III, Aluminum Diamond Plate	1		
WC, Light, Side Entry Step well, LED, Whelen #TOCACCCR, 2"	1		
WINDOWS			
WC, Window, Upper, CS/Slider, Rr/Fixed, Privacy Tint, PAN	1		
MODULE TO CHASSIS MOUNTING SYSTEM			
WC, Module to chassis mounting system, Type III	1		
REAR BUMPER AND REAR STEP CONSTRUCTION			
WC, Rear Bumper w/ Skids & Flip Up, F3, w/ holes for 2" LED Lights w/ Gator Grip on flip up step. holes in sides of bumper for 2" marker light	1		
WC, Coating, Polyurethane, Rear Bumper Supports Black	1		
INSULATION			
WC, Insulation, Walls and Ceiling, R11 Fiberglass Batt	1		
RUB RAIL AND FENDER RINGS			
WC, Rub Rails, Skirt Line, Extruded "C" channel (E-one Style)	1		
WC, Tape, Reflective, White, For Extruded Skirt rails	1		
WC, Fender Flare, Black Rubber	1		
SPLASH GUARDS AND RUNNING BOARDS			
WC, Mud Flaps, Rear, w/ Wheeled Coach Logo	1		
WC, Running Boards, Ford Type 3, w/Gator Grip	1		
DRIP RAILS			
WC, Drip Rail Trim Moldings Over Door Openings	1		
CAB TO MODULE ACCESS			
CAB TO PATIENT AREA ACCESS			
WC, Bulkhead Cabinet, Type III Ford, 10" Cab Extension	1		
WC, Door, Sliding, Bulkhead, w/Sliding Window with sliding Lexan window	1		
LICENSE PLATE HOLDER			

DESCRIPTION	QTY		
WC, License Plate Holder, Cast LP0002-1 for Under ride Bumper in rear kick plate, centered License holder comes with (2) LED lights.	1		
EXTERIOR COMPARTMENT CONSTRUCTION			
WC, Exterior Compartment, Std, Floor 2.5" Drop Down from Door Opening, Each Compartments #4, #6 and #6.5 are STD drop down floor (Compt 2 drop is special 04-07-26SP)	3		
WC, Exterior Compartment, Sweep out, Each Compartments #1, #8 and #8.5 are sweep out.	3		
WC, Door Sill Protector, Stainless, All Comps Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage	1		
WC, Polyurethane Coating per compartment light gray	5		
WC, Exterior Battery Compartment, Polyurethane Finish	1		
EXTERIOR COMPARTMENT DOORS			
WC, Compartment Comp Handle, Trimark, Oval Pull Handle, Black/Chrome	7		
WC, Compartment Door Latch, Edge Paddle, Trimark, Trailing Door Interior edge style handle comp "#2"	1		
COMPARTMENT DOOR HOLD OPEN			
WC, Hold Open, Gas Strut, Ext Comp, 60lb for comp. #4 hold open	1		
WC, Hold Open Gas Strut, Ext Comp, 30lb Compartments 1, (2) 2, 6, 6.5	5		
WC, Hold Open, Gas Strut, RF Comp, 30lb	1		
COMPARTMENT LIGHTING			
WC, Compartment Lighting, LED Solico Reel lights, Hinge side only Hinge side vertical edge near door jamb on all compartments, Excluding the Battery Compartment. Oxygen compartment lights shall be activated also as the O2 light.	1		
COMPARTMENT #1 - STREETSIDE FWD			
WC, Compartment #1, Full Height (On type III - includes recess for stair chair storage)	1		
COMPARTMENT #2 - STREETSIDE FWD WHEELWELL			
WC, Compartment #2, 50" Aisle, Standard Configuration	1		
WC, Compartment #2, Shelf, Adjustable, w/Alum Track, First Shelf half depth for stair chair approximately 5" deep	1		

DESCRIPTION	QTY		
U WC, Compartment #2, Floor, Special Drop Down from Door Opening	1		
<p>- ADDS Drop Pan in bottom: 10"D x Max width x 4"H - as far outboard as possible</p>			
WC, Compartment #2, Strap, Seat Belt Style, Each Wall #1 to #3 for stair chair	1		
COMPARTMENT #4 - STREETSIDE AFT			
WC, Compartment #4, 3/4 Height.	1		
WC, Compartment #4, Shelf, Adjustable, w/Aluminum Track, First Shelf (1) Bottom of cabt "C4" inside/outside access opening. (2) Evenly spaced. (1) above and (1) below first shelf	1		
WC, Compartment #4, Shelf, Adjustable, Additional, Each	2		
COMPARTMENT #6 - CURBSIDE AFT			
WC, Compartment #6, Full Height	1		
WC, Compartment #6, First Divider, Vertical, 3/16" Thick, Recessed Adj Track Centered.	1		
WC, Compartment #6, Equipment Strap, Seat Belt Style, Each Nylon web strap w/ seat belt buckle and two (2) footman loops wall #1 to #3 mid height	1		
COMPARTMENT #6.5 - CURBSIDE AFT			
WHEELWELL			
WC, Compartment #6.5, Below Squad Bench Floor Level	1		
COMPARTMENT #8 - CURBSIDE UPPER FORWARD			
WC, Compartment #8/8.5, Split doors, Type 3	1		
WC, Compartment #8, Shelf, Adjustable, RF Cabinet, First shelf w/Aluminum Track (1) RF Comp "8"/cabinet "U8" area, centered.	1		
WC, Compartment #8, Shelf, Adjustable, Additional, for Aluminum Track, Each RF Comp "8"/cabinet "L8" area, centered.	1		
INTERIOR TRIM AND FEATURES			
WC, Interior Cabinets, Duralite Construction, Wood, CN10 compliant All cabinets shall be labeled with their Rated Weight Capacity.	1		
INTERIOR ADJUSTABLE SHELVES			
WC, Shelf, Interior, Wood , (1) adjustable, in Cabinet	3		
WC, Shelf Track, Cabinet, #HA24663, CN 10 Upgrade ("C" channel/exterior shelf style track)	3		
HEADLINER			

DESCRIPTION	QTY		
WC, Headliner, Flat, PVC, Hinged trough cover, 160"+	1		
FLOORING			
WC, Flooring, Lon Seal "Lonplate II "	1		
WC, Color, Gunmetal Gray #424	1		
Flooring, With approx 3" roll up both street side and curbside with Toe Kick	1		
The roll up is recessed at the bottom of the cabinet wall and Squad bench.			
WC, Floor, Thresholds, .063 Aluminum , Painted w/Black Poly-urea coating	1		
Entry Door Grab Handles			
WC, Entry Door Grab Handles (3), Custom "L" Shape, 1", Yellow	1		
Yellow Powder Coat Finish			
Ceiling Grab Rail - Center			
WC, Ceiling Grab Rail, Overhead,112", 1" diameter Handicap Style, Yellow	1		
Yellow Powder Coat Finish			
IV FLUID HANGERS			
WC, IV Hook, Perko Snap Hook w/Velcro Strap, Each	2		
Curbside and streetside standard locations.			
ACTION WALL AREA #2			
WC, Cabinet, A/A, 50" Aisle, No Bio waste, Rounded corners	1		
WC, Tray, A/A, 50" Aisle, No Bio waste, Poured, Black	1		
only for 50" aisle space units			
WC, AA Upper Cabinets, U2.5 Angled, U2, Full Ht Comp #1	1		
CABINET DOORS			
WC, Door, U2 Gray Polycarbonate Slider, CN 10 Compliant	1		
WC, Door, U2.5 , Hinged Wood	1		
Hinged on Right.			
Interior Street side #3 - CPR Seat			
WC, CPR side seat, Fixed Backrest, 25" wide Std.	1		
WC, CPR, Lid, Hinged Flip Up	1		
With Trimark Latch			
WC, Cabinet U3 or U3.5, w/ CPR seat (ONLY Available in 72" HR)	1		
Note: TO meet 43" minimum KKK requirement for space between cushion on Side seat and bottom of splint cabinet.			
WC, Cabinet C3.5, deleted For Telemetry Area	1		
WC, Cabinet L3.5, full height, std	1		
WC, "U" Barrier Bar, Padded, 1.5" SS, CPR Seat, Gunmetal	1		
Mounted Approx. 12" from the center of the seat to the side of the barrier bar.			
WC, Telemetry Tray, Poured, Black	1		
WC, Door, U3 Gray Lexan Flap Glass, CN 10 Compliant	1		
Friction Hinge hold opens			

DESCRIPTION	QTY		
WC, Doors, L3.5, Gray Polycarbonate Slider, CN 10 Compliant	1		
STREETSIDE REAR AREA #4			
WC, Cabinet U4, Combined with U3.5	1		
WC, Cabinet C4, Inside/Outside Access	1		
WC, Cabinet L4, Deleted	1		
CABINET DOORS			
WC, Doors, U4/U3.5 Combined, Gray Polycarbonate Slider - CN 10 Compliant	1		
WC, Doors, C4, Gray Polycarbonate Slider - CN 10 Compliant	1		
SQUAD BENCH AREA			
WC, Squad Bench, Bio-Waste @ Head	1		
WC, Lid, Squad Bench, Single W/Bio-Waste	1		
WC, Handle, Trimark, CPR Seat, Std.	1		
WC, Handle, Trimark, Squad Bench, STD	1		
WC, Strut, Gas, 60 LB, Installed	1		
WC, Seatbelt, Assy, (4 Point), Per4Max, Yellow, Vert. Mount, (1) Each, CN-8	3		
Above bench Lid mounting (1) for CPR side seat (2) for squad Bench			
WC, Patient Restraint Belts, Squad Bench (3)	1		
WC, Safety Net, Head of Squad Bench, 2" Straps, Yellow	1		
Attached to floor at head of squad bench, CS wall and overhead liner with removable latches.			
CURBSIDE REAR			
WC, Cabinet, Curbside Rear, Standard	1		
WC, Cabinet, Glove Box Holder, (3), Above C/S door,	1		
CURBSIDE RIGHT STACK STORAGE #8			
WC, RF ALS, Split Upper/Lower, HVAC at Top	1		
WC, Doors, RF, U8, Dual Gen III OHO, Polycarbonate Doors, Gray	1		
WC, Doors, RF, L8, Dual Gen III OHO, Polycarbonate Doors, Gray	1		
ATTENDANT SEAT			
WC, Attendant's Seat, EVS 1880, Comfort, Hi-Back Child Safety w/Per4Max	1		
WC, Color, Gunmetal, Per4Max Belt, Yellow	1		
WC, Attendant's Seat Base, EVS CBS Box Style	1		
cabinet base, opening to face CS entry door **TO BE MOUNTED AS FAR FORWARD AS POSSIBLE TO MAXIMIZE KNEE ROOM***			
INTERIOR COLORS			
WC, Mica, Dove Gray (Matte)	1		
UPHOLSTERY			
WC, Upholstery Color, Gunmetal	1		
WC, Backrest Cushion, EVS, Gunmetal, w/ WC Logo, Each	3		
CABINET KICK PANELS			
WC, Kick plate, 8" Brushed S/S, Face Of Squad Bench	1		
WC, Kick plate, 8" Brushed S/S, On Face of Base wall	1		
CABINET LATCHES- INTERIOR			
WC, Latch, Southco M1, 2" S/S, (3/4" door) Non-Locking, CN 10-Rated 10lb	4		
(self latching) Flush Mount. Non-Locking			

DESCRIPTION	QTY		
<p>(1) Sharps and Waste (1) U2.5 door (2) Circuit Board access doors</p>			
<p>WC, Latch, Southco M1, 2" S/S, (3/8" Door) Non-Locking, CN 10-Rated 10lb (self latching) Flush Mount. Non-Locking</p>	2		
<p>(1) Glove Caddy (1) U3</p>			
GENERAL WIRING			
<p>WC, Electrical System: Relay Plex System</p>	1		
<p>WC, "E" Spec, Relayplex Harness Set, No Lightbar</p>	1		
CAMERAS			
<p>WC, Camera, Hanscom Kit, HK 7211 w/ IR250</p>	1		
<p>Mount monitor to the left of the steering wheel.</p>			
<p>In the module mount the camera on the headliner next to the streetside cabinets.</p>			
<p>Trigger camera display on with Master Switch. #HC IR250 rear back up camera with #HC20M video cable,</p>			
<p>Mount camera exterior on rear of module, off center toward driver's side. Triggered when units placed in reverse gear.</p>			
COMMUNICATION			
<p>WC, Coax Cable, RG58/U, Each, Terminate:</p>	3		
<p>(1) - From module roof Dome #3 to behind passenger seat with 6' pigtails</p>			
<p>(1) - From module roof Dome #7 to behind passenger seat with 6' pigtails</p>			
<p>(1) - From module roof Dome #6 to behind passenger seat with 6' pigtails</p>			
<p>WC, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.</p>	1		
POWER SOURCES			
<p>WC, Buss Bar Assembly (+/-), 5 Position, for ground and hot IATS, Inside front console, see 40 amp power source.</p>	1		
<p>WC, Power Source, 12VDC, 20A, Ignition/Shoreline Hot 20amp 12 volt DC circuit ran to two locations, (1) pre-wire coil and tagged in action area and (1) pre-wire coil and tagged behind driver's seat.</p>	1		

DESCRIPTION	QTY		
WC, Power Source, 12 VDC, 15 Amp (+-), Ignition Hot - Ignition hot, terminating in cab console - with 6 foot tails (hot and ground).	1		
WC, Power Source, 12 VDC, 30 Amp (+-), Constant Hot - Constant Hot, to terminate behind the passenger seat - with 6 foot tails (hot and ground).	1		
WC, Power Source, 12 VDC, 40 Amp (+-), State Source Constant hot Inside front console. To include ground, connect to buss bar in console.	1		
WC, Alarm, Low Voltage, Audio/Visual Light in cab console and Buzzer in cab.	1		
WC, Voltmeter, OEM, In Dash	1		
BATTERY SYSTEM			
WC, Battery Sw, 5min Timer, F3, Gasoline, Fig 5B Activated thru OEM ignition switch timer function upon ignition "off". Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer.	1		
(1) OEM battery under hood (1) OEM battery in RF Lower Compartment			
ONLY Module power is turned on/off. Chassis power is NOT turned off.			
12VDC OUTLETS			
WC, Outlet, Power Point Style, (2), A/A - on standard 20-amp ignition hot circuit. ("elect battery switch")	1		
WC, Outlet, Power Point Style, Each	4		
(1) Above squad bench, 20" up from the top deck of the squad bench, 8" over from the edge of the foot of squad bench wall (Ign hot)			
(2) On front console, driver side, below siren (ign hot)			
(1) Bulkhead wall, close to AA cabinet, down low. For Engel Cooler (constant hot)			
WC, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel Located on the Driver side and Passenger side of the center console, Ignition hot	2		
WC, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel, Each Location in the Action area outlet panel, Ignition hot	1		

DESCRIPTION	QTY		
FRONT CONSOLE			
WC, Console, Drivers Switch & Radio, Center, Aluminum, Black, Ford cutaway Black polyurethane coated .090 Aluminum	1		
5.25 x 12.5 x 7" deep storage area at rear			
Single Blank Panel	1		
9" deep Glove Box Panel	1		
Cup Holder Panel (No Handle Notch)	1		
WC, Module Electrical Panels, Brushed Stainless Steel brushed stainless steel panels for the Outlet panels, switch panels and other faceplates in the MODULE only.	1		
ATTENDANT CONTROL PANEL			
WC, Console, A/A, Wood, Angled	1		
POWER DISTRIBUTION			
SIREN ELECTRONIC - CONTROL HEADS / AMPS			
WC, Siren, Whelen, WS-295-SLSA1, California Title 13 Compliant	1		
SIREN SPEAKERS			
WC, Speakers, (2), Cast, SAD4319/SAP4319, In Bumper, F3	1		
WC, Switch, Siren/Horn Thru Horn Ring	1		
BACK-UP ALARMS			
WC, Back-Up Alarm, w/ Cutoff, Auto Reset	1		
TRAFFIC MANAGEMENT LIGHTS			
U WC, Amber LED Beacon, Whelen L31HAF, Installed on roof of module	1		
Module roof, centered 16" inboard from rear of module, Beacon will be on anytime Ignition is on and unit is in gear.			
WARNING LIGHT FLASHERS			
WC, Brake Override Circuit Rear of module red 900 Red LED's rear lights below upper outer warning lights.	2		
WARNING LIGHTS			
Lights on unit are to have primary and secondary Triple K compliant flash patterns			
LED Series - 900 (Flange Separate)			
WC, Light, Whelen 900 LED, Red, Clear Lens, 90RR5FCR, Internal Flasher (2) each side standard location (2) on rear in upper outer corners (2) on front in upper outer corners Pri/Sec - Internal flasher - Comet flash	14		
(2) Rear Directly under upper outer red warning lights Pri/Sec - External flasher - Comet flash - (Brake over			

DESCRIPTION	QTY		
ride) Set light to steady burn			
(2) On Coolbar (1) each side of center white light Pri only - Internal flasher - Comet flash			
(2) Angled portions of Coolbar Pri only - Internal flasher - Comet flash			
WC, Light, Whelen 900 LED, Amber, Clear Lens, 90AA5FCR, Internal Flasher (1) Center rear Pri/Sec - Internal flasher - Comet flash	1		
WC, Light, Whelen 900 LED, Clear, 90CC5FCR, Internal Flasher (1) Center front on Coolbar Pri only - Internal flasher - Comet flash	1		
WC, Flange, Super 900 LED, #90FLANGC LED Series - 700 (Flange Separate)	16		
WC, Light, Whelen 700 LED, Red, Clear Lens, 70R02FCR (2) Front intersectors (2) Rear Intersectors over rear wheel wells. Pri only- Internal flash - Comet flash	4		
WC, Flange, Whelen, Chrome, 700 Series Light (1), Mods WARNING LIGHTS -WHELEN LIN3 (Flange Separate)	4		
WC, Light, Whelen, LIN3, LED-Red, RSRO2ZCR (2) in upper grille Pri only- Internal flash - Comet flash	2		
WC, Flange, Whelen, Chrome, For LIN3, Each EXTERIOR AUTOMOTIVE LIGHTING	2		
WC, Taillight Pkg, Whelen, LED Stop/Tail, Turn & LED Backup, w/WC logo - Brake- Steady Burn - Turn Arrow – sequential arrow - 700 LED Backup Clear lens over all three lights	1		
ICC/MARKER LIGHTS			
WC, Light, Clearance, Amber LED, Each On front as clearance lights.	3		
WC, Light, Clearance, Red LED, Each On rear as clearance lights.	3		
WC, Lights, Red, 2", Marker, LED, Pair in bumper	1		
WC, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers - High intensity flashers; thru separate switch	1		
FLOOD AND LOAD SYSTEMS			
WC, Light, LED, Whelen, Clear, #9SC0ENZR, 24 LED, w/Chrome Flange	6		

DESCRIPTION	QTY		
(2) each side as "Scene lights" (2) on rear over rear doors as "Load Lights"			
WC, Scene Lighting, CS, Activate on Opening of CS Entry Door	1		
11 - INTERIOR LIGHTING			
WC, Lights, Dome, LED, Whelen, White Flange, (4) S/S, (3) C/S NOTE: NO VISABLE FASTENERS OR HOLES.	1		
WC, No Lighting Recessed into Trough Cover	1		
WC, Timer, Momentary Switch, 15 Minute, Constant Hot Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to CS Domes in liner on High.	1		
SPOTLIGHTS / HANDHELD LIGHTS			
WC, Handheld Spotlight - Sho-Me 200,000 CP	1		
ATTENDANT LIGHT			
WC, Light, Intertek ZY-PIR38 12v, LED, 15 inch, Each	1		
12 - ELECTRICAL 125 VOLT AC			
SHORELINE INLET			
WC, Shoreline, 20A, Super Auto Eject, White - with white cover; mounted above compartment "#2"	1		
OUTLETS - 125VAC			
WC, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet in the RF Cabinet "U8", wall #2, upper right.	1		
WC, Outlet, 125 VAC, Duplex, Each, State Location:	2		
(1) Telemetry area, wall #2, near wall 1, mid height. (1) Interior curbside wall above foot end of squad bench mounted approx. 15" up and over 3" from rear wall.			
BLOCKHEATERS			
Block Heater - With OEM Plug This option does not include a switch.	1		
INVERTER - 125VAC			
WC, Inverter/Charger, Vanner LifeSine Mounted on ceiling in Compartment "#2" LifeSine inverter will be ignition switch activated, No Inverter switch.	1		
AUXILIARY ENVIRONMENTAL SYSTEMS			
WC, Exhaust Fan, Single 12V, in Line Blower	1		
WHEELED COACH HVAC UNITS			
WC, Hoses, Heater, No Max, to Rear	1		
WC, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo	1		
WC, Heat/AC Located RF corner, over ALS cabinet.	1		
WC. Generation III Fiberglass Cool Bar cover	1		
WC, Heat/AC, F3, Combo, w/Coolbar, Brushless Motor 12vdc External Condenser, in Coolbar mounted on front	1		

DESCRIPTION	QTY		
WC, Thermostat, Hoseline Master Control Digital CM5000, Brushless Motor	1		
COT MOUNTING PROVISIONS			
Cot Mounts			
WC, Stryker Performance/Power Load, Add Floor Structure Plates & Wiring for Futu Additional floor structure for future installation of a Stryker Power Load or Performance Load w/ inductive charging System.	1		
WC, Cut Floor and Install Cot Mount Floor plate, 6390-700-001A, for Powerload For Powerload Load Cot mounts.	1		
Note: Stryker Deutsch connection to be coiled up on the interior of the module			
Center Mount	1		
OXYGEN AND AIR SYSTEMS			
WC, O2 Cylinder Wrench ,Tethered in oxygen comp.	1		
WC, O2 Cylinder Bracket, Multiversal, #QR-MV, W/ Straps	1		
WC, Track, Unistrut for Oxygen Rack	1		
WC, Manual, O2 System	1		
WC, O2 Regulator, Preset 50 PSI	1		
WC, O2 Outlets, Ohio Style (2 in Action Area, 1 CS Wall) (2) in Action Area, (1) CS wall above squad bench	1		
WC, Lexan Flap, w/Hinge	1		
PORTABLE O2 HOLDERS			
WC, O2 Cylinder Holder, Single, Zico QR-D-2 Strapless, CN 10 Certified Installed aisle side of RF L8 stack mounted approx. 3" off floor centered.	2		
SUCTION SYSTEM			
WC, Suction Pump, SSCOR 90206 In Compt "#2" on ceiling close to inverter. Expanded metal cage. Make sure cage is tight and space in #2 is maximized.	1		
WC, Suction Port, Hole Only, No Outlet Plate Located in recessed area	1		

