



DEALER: North Eastern Rescue Vehicles
CUSTOMER: _____
Street or P.O. Box 10 Dwight Park Drive
City, State, Zip Syracuse, NY 13209
Customer Contact: _____
Customer Email: _____
Customer Phone #: _____
Sales Associate: _____
Sales Engineer: _____

VIN#: _____

Chassis Model Yr		2025
MEDIX Model		Metro Express 153 Type I
CHASSIS		Ford F-450 XLT, 6.7L DIT Diesel, 169" WB, 16,500 GVWR 84" CA, 4x4
BODY		153"L x 94" W x 72" Interior Headroom
QTY		Description
1		Chassis & Conversion
		Chassis Model Year Adjustment
		New Sales Model w/Drop Skirt Curbside & Wider Compartment #1
		Liquid Spring Suspension
		-
	01-	Flooring & Interior Colors
1		Cabinets: Laminated Wood Color: TITANIUM
1		Upholstery: Color: Black Brand: EVS
1		Flooring: Lonseal, LonPlate (Diamond Plate), ILOS Lonspeck TS Twilight Specify Color: 443 TXM Midnight
1		Flooring: Skid tape at entry door thresholds to be Yellow/Black ILOS Black
		-
	02-	Body & Chassis
1		This chassis is equipped with a Diesel Exhaust Fluid (DEF) System to meet the EPA Diesel Emissions Standards.
1		Anti-Theft Device: Security System, for Ford F-Series Chassis

		Front wall lights will be located higher than standard position to accommodate graphics between the lights and cab.
		See special front wall for turn arrow locations; Delete the static vent over the side entry door
1		Camera System: Ford "F" 'Series Super Duty OEM Surface Mount Back-Up Camera and Harness tied into OEM display in dash. Includes RVS-MV3-IR camera and RVS-OA08 Harness.
1		All Exterior compartments coated with light gray colored rubberized polyurethane material.
1		Pass-Thru: With accordion boot. Sliding, latching polycarbonate window.
1		Compartment Lights: Optronics ILL36CB LED Compartment lights- ALL Models Locate: (1) Ceiling of Compt #1; (2) in Compt #2- (1) URH, (1) LLH; (1) in ceiling of Compartment #3; (2) in Compt #4/5; (1) in Compt #6 (if applicable).
1		Compartment #1 SS Forward: Smooth Aluminum body, ADP interior door panel, O2 "M" cylinder storage for STEEL tank, Door w/gas-strut hold-open.
1		Compartment #2 SS Center: <u>Smooth Aluminum</u> body, <u>ADP interior door panel</u> , Open Storage, Door w/gas strut hold-open and Seat Belt Strap.
1		Compartment #3 SS Rear: Smooth Aluminum body, ADP interior door panel, Mid-height open storage. Door w/gas strut hold-open.
2		Rear Entry Doors: Single piece laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels.
1		Compartment #4/5 CS Forward: NO body <u>above floor</u> , <u>ADP interior door panel</u> , ALS Cabinet w/ Inside/Outside access, Full-height, single Door w/gas strut hold-open. Bottom section aluminum body open storage standard. (Optional location for additional battery with roll-out battery tray and removable, latching door.)
1		Drop Skirt - 4" on Curbside forward of the rear wheelwell. Taller front stone guard on passenger side.
1		Curbside Entry Door: Taller for 4" drop skirt. Door handle to remain aligned with Compt #4/5 handle; Single door system w/exterior/interior, locking paddle handles; window w/ fixed glass; Gas strut hold-open. Sealed access to paddle handles in door panel. LED Step well light. Two-piece interior door panel.
1		Curbside Entry Door Stepwell: Dual, smooth aluminum steps coated with a rubberized urethane liner material. There will be a Dri-Dek insert on each step surface.
1		Compartment #6 CS Rear: Smooth Aluminum, Vertical backboard storage w/2 belts. Door w/nylon strap hold-open.

1		Compartment #7: CS rear, smooth aluminum body. Open Storage, single access door with gas strut hold-open. Sealed access to paddle handles in door panel. (1) LED light in ceiling. Installed between CS rear wheelwell and compartment #6 IATS.
1		All Entry Door paddle handle and rotary latching components will include emergency door releases located top and bottom of each door and shall meet the FMVSS 206 30G Test Requirement
1		Power Door Locks: All Entry and Compartment Doors, wired to OEM door lock system. (Does not include additional lock switches inside module)
1		Rear Bumper: ADP corner pods w/Dock bumper pads, Center grip-strut flip-up step, powder coated steel frame
2		IV Hangers: (2) Cast black rubber fold-down over knee area of Cot and Squad Bench
3		Mirrors, OEM: (1) each cab door, (1) on interior windshield
1		Wheel Covers: Stainless steel covers w/Valve Extenders
4		Stone Guards: (3) Lower body corners, ADP; (1) 4" taller ADP on Curbside front
1		Kick Plate, Rear: ADP, below rear doors across to corner posts.
1		Rub Rails: C-Channel, tapered ends, Lower Body off-set mount with neoprene spacers.
2		Running Boards: Diamond Plate, Type I w/starburst pattern
1		Fender Flares: Black rubber
2		Fuel Fill Bezel: Cast aluminum; DEF Fill Bezel: Cast Aluminum
1		Insulation: Pink, double sided radiant barrier/acoustic material, installed on curbside and streetside rear wheel wells.
1		Insulation: Spray in place foam applied to curbside entry step well and both rear wheel wells
1		Undercoating: Per QVM Guidelines
		-
	03-	Brake, Turn & Back-Up Lights
1		Lights: Turn Arrows, (2) Whelen 600 Series Amber LED, with color tinted lenses and chrome flanges, mounted on front wall below outboard flasher. IATS
		See prints for mounting Positions for 6 x 4 Amber Arrow Turn Signals and Front of Body 9 x 7 Warning Lights.
1		Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 600 Series LED. (Turn and brake will have color lenses also)
1		DOT Marker Lights: TecNiq LED, rubber grommet bezels; (7) S34-AC09-1 Amber- (5) on front of body as Marker lights, (2) side facing on rear extrusions as Turn Signals; (7) S34-RC90-1 Red- (5) on rear of Body as Marker lights, (2) side facing as Turn Signals.

1		<p>Lights: DOT Marker, (2) TecNiq LED S34-AC09-1 Amber marker lights, (1) each side of body at front corner extrusion. Wire to Turn Signal Circuit. IATS.</p> <p>Locate: at same height as standard marker lights at rear corners.</p>
		-
	04-	Electrical, Power Distribution, Control Center & Interior Lighting
1		Battery Switch, Automatic: TST CDR-400. Located in Electrical Cabinet.
2		Batteries: OEM, under hood
1		Front Console/ Switch Panel: Formed Aluminum body powder coated black and attached to chassis floor. Switch panel: Engraved black plastic with LED lighted switches for Emergency Master, Primary/Secondary Modes, Siren/Horn, Left, Rear and Right Floods, Back-Up Alarm, Module Disconnect. Siren mounted in engraved panel below switches.
2		Antenna, Radio Coax Cables: Terminated behind driver's seat w/Power & Ground for each
8		Lights: Dome, LED w/flange, switched separately with Hi/Lo functions.
1		Action Area Light: 12 VDC LED light, with On/Off switch on rear control panel
1		USB Port: Vanner VSS-USB dual port 2Amp mounted on A/A wall
1		Shoreline: 125 VAC, 20-Amp, 60 Hz straight-blade inlet w/hinged, weatherproof cover, located to rear of Compartment #1
1		Timer: 5-minute check-out, wired to CS High mode dome lights
1		<p>Switching: Timer, Momentary 15-Minute timer switch for patient compartment dome lights. Wired to CS high mode dome lights ILOS.</p> <p>LOCATE: Switch in 2-Position Positron switch panel in standard position on curbside wall.</p>
1		<p>Inverter: Vanner LSC12-1100- 1100watt with 3-Stage 55Amp battery charger, 20Amp power supply and built in GFI. Remote controlled with switch in the rear switch panel. (This option deletes the GFI in the A/A wall). ILOS</p> <p>Location: Lower Pass Through Cabinet "E"</p>
1		Electrical: Battery Charger, DELETE STANDARD (when adding Inverter with integral charger)
1		Electrical: Fan, Mechantronics Fan, (1) Axial 120x25MM 12VDC ventilation fan PN: E1225E12AB-FSR mounted on cabinet door or side wall when any inverter is mounted in an interior, enclosed cabinet.
1		Breaker Box: 125 VAC w/20-Amp Breaker located in the lower aisle-facing bulkhead cabinet "E".
3		12 VDC Outlets: (1) in Action Area, (1) in ALS Cabinet, (1) in 2nd Action Area

3		125 VAC Outlets: Duplex, located (1) in Action Area, (1) in ALS, (1) in 2nd Action Area
1		Electrical: 125VAC, Duplex Outlet, IATS SPECIFY LOCATION: (1) on the CS wall over head of bench below the timer switch.
1		Rear Switch Panel: Engraved black plastic panel with (10) LED lighted switch positions for Dome Lights (2), Vacuum (1), Vent (1), Cabinet Light (1) , A.A. Light (1), Inverter (1), Spare switches and digital clock w/Mode Buttons. MX01517.
1		Electrical Cabinet: Located over cabin-module connection w/latching, recessed, vented door
4		Lighting: Cabinet: (1) TecNiq E44-W03V-1 Flexible LEDs, WHITE - 13.5" for interior cabinet - to be wired to an interior cabinet light switch and tied to other cabinet lights. Locate: (2) in "A1", (2) in "C"
3		Lighting: Cabinet: (1) TecNiq E44-W05V-1 Flexible LEDs, WHITE - 22.5" for interior cabinet - to be wired to the interior cabinet light switch. Locate: (1) each SB OH Section and (1) Rear Overhead
		-
	05-	Warning Lights & Sirens
		Front wall lights will be located higher than standard position to accommodate graphics between the lights and cab.
		Mid-Body lights to only work when light bar switch is on (will still be wired to Pri/Sec.) (The front inner (4) lights will also be on the light bar switch.
1		Lights: Warning, Whelen 900 series LED Emergency Lighting package with <u>COLOR</u> LENSES ILOS Whelen LED package with clear lenses. (Does not include LED Scene or Load Lights.) Front of Body: (7) 9x7 Whelen LEDs- Specify pattern by LED Color (4) Red and (3) White: in R-W-R-W-R-W-R pattern. Outer (2) lights and (1) Center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console. Sides of Body: (4) Whelen 900 Series Red Super-LEDs: (2) each side in upper corners. Rear of Body: (4) Whelen 900 Series Red Super-LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level (MID BODY WILL ONLY WORK WHEN LIGHT BAR SWITCH IS ON); (1) Whelen 900 Series Amber Super-LED in the center position over the rear doors. Brake, Turn & Back-Up Lights: Whelen 600 Series LEDs Intersection Lights: (2) Whelen 700 series Red Super-LEDs with Color lenses on Front Fenders.
1		Lights: Warning, (2) Whelen 700 Series Red Super LED 70R02FRR with RED lens and chrome flange 7EFLANGE, IATS above rear wheel wells as rear intersection lights.

2		Lights, Warning, Grille: LINZ6R Red LED w/clear lenses & chrome flanges on center grille bar
6		Lights: Scene/Load, Whelen 900 Series Super-LED 9SC0ENZR Gradient Opti-Scenelight™ with chrome flange- ILOS Halogen Specify Locations: Two (2) Each Side of Module Upper and Two (2) Rear of Module Upper over Rear Entry Doors.
1		Flasher: Dual mode flasher for Warning Light system, Vanner 9860GCPE
2		Siren Speakers: dual 100 Watt drivers mounted behind the front grille
1		Siren: Whelen 295 SLSA1, 200 Watt
		-
	06-	Oxygen, Vacuum & Miscellaneous Items
3		Oxygen Outlets: Quick-connect style, (2) in Action Area, (1) over Squad Bench
1		Suction Aspirator System: Rico disposable container mounted in Action Area w/gauge and quick-connect; SSCOR vacuum pump mounted in lower bulkhead hallway cabinet "E".
1		Oxygen Cylinder Retention: For "M" cylinder, black steel w/3-spring buckle straps and top collar, located in Compartment #1
1		O2 Regulator: Amvex, 50psi, pre-set
		-
	07-	AC / Heat
1		HVAC System: High capacity free blow combination Heat-AC system with digital thermostat control on the action area wall. HVAC unit is mounted in bulkhead at the top of the ALS.
		-
	08-	Cabinets, Hardware & Miscellaneous Items
1		Main Streetside Wall Cabinets: Specify desired configuration-
1		Streetside Cabinet Configuration shall include a CPR Seat with Pro-4 seat belt system. The seat belt system shall include a custom contoured seat back, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort and a heat embossed Medix LOGO at the head area. There shall be a 2nd Action Area, which includes (1) 125VAC and (1) 12VDC outlet, located aft of the CPR seating area.
		Main Wall Cabinets will have (1) adjustable shelf in each and sliding polycarbonate doors with full height extruded handles.
1		Action Area Overhead Cabinet: Single cabinet full-height/full-depth of Action Area with sliding polycarbonate doors and full height extruded handles.
2		Cabinets: Main Cabinet Wall, Restocking Feature, Interior Cabinet, Sliding Acrylic door with hinged, keyed frame with (2) Titan 20-pound gas struts and (2) spring-loaded elbow catches. Location: One (1) Streetside Upper Rear Main Cabinet "A1; One (1) Action Area Overhead "C".

1		Action Area and Switch Panel: Laminated, sealed countertop and vertical ALUMINUM panel with Suction system collection canister, Vacuum gauge, (2) Oxygen outlets, (1) USB, (1) 12VDC Outlet, (1) 125VAC Outlet and digital Thermostat. Switch panel MX01517 includes (10) switch positions and digital clock w/Mode Buttons.
1		Cabinets: Countertop, Solid Surface Material, 1st and 2nd Action Areas, Color: Grey with Black top and full perimeter accent color. To extend over the edge of cabinet main.
1		Bulkhead Wall Cabinets: Electrical Cabinet above cabin-module connection w/hinged, latching, vented door.
1		Bulkhead Cabinets: Upper cabinet- general storage w/hinged, latching door; Lower cabinet general storage w/hinged, latching, vented door and location for inverter and vacuum pump on floor.
1		ALS Cabinet: Combine Lower and Middle to create a single opening with dual, full height 1/2" Acrylic doors, non-locking doors with Two Point Paddle Latches, one per door, and (2) Adjustable Shelves. ILOS NOTE:Type I 153 Models Only
1		Glove Box Holders: (3) with hinged, black 11ga steel powder-coated door, above Curbside Entry Door. NOTE: DELETES STATIC VENT OVER SIDE ENTRY DOOR
1		Cargo Net: Head of squad bench- Type I / III 150/153 Models. Squad Bench to accommodate mounting plate and cover secured to wall structure.
1		Squad Bench: (Box out around Compt #7)
		Full length hinged lid w/TriMark latch for access to interior storage; Full length upholstered seat cushion except over Sharps/Waste Area.
		2) EVS Pro-4 seat belt system seating positions. The seat belt positions shall include a custom contoured seat back, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort, a custom retractor for securing a secondary patient and a heat embossed Medix LOGO at the heat area.
		Stainless steel kick panel along lower face of bench.
1		Sharps/Waste: Drop-in style with aluminum, powder coated red, hinged lid and standard containers, located at head of squad bench.
1		Cabinets: Squad Bench Overhead, with (2) flip-up 1/2" Acrylic doors, (1) Two Point Paddle latch per door and Austin constant torque hinges.
1		Cabinets: Rear Overhead, Cabinet over rear doors opening with (1) flush mount, flip-up 1/2" acrylic door, (3) constant torque hinges and (1) Life-Defender latch ILOS.

1		Seating: EVS 1880 Child Safety Seat, (1) Technician's Seat MDX-1880S4B with 10° back. Rear facing automotive style seat to include a Pro-4 black belt system, comfort shoulder padding with heat embossed Medix LOGO at the head area of the backrest and the child safety seat system. -ILOS Pro-4 seat.
1		Seating: EVS Seat Base, EVS CBWD reinforced cabinet base with door to storage and latch- ILOS
1		Assist Rail: 72" - 1.25", Powder Coated Safety Yellow SS 1.25" with Radius Ends, ILOS -All Models
1		Grab Handles: (3) 12", Powder Coated Safety Yellow 1.25: SS with Radius Ends- ILOS -All Models
1		Reflective Striping, Door Open Protection: .50" Red reflective striping around interior door pan of all body doors.
		-
	09-	Cots & Miscellaneous Items
1		Cot Mount: Stryker, Power/Performance Load Systems, install floor plate "Only". ILOS 175-4.
		-
	10-	Paint & Lettering
1		Paint: Body all OEM White

		SHIP LOOSE
2	STD	Fire Extinguisher: (2) 5 lb- Ship Loose is Standard