



North Eastern Rescue Vehicles, Inc.  
 Bob Reilly  
 10 Dwight Park Drive  
 Syracuse, NY 13209

WO#: 629102

DESCRIPTION	QTY
<b>ORDER COORDINATOR</b>	
	1
<b>INFORMATION</b>	
	1
<b>WARRANTY</b>	
WC, Warranty, Conversion, 12 Month	1
WC, Warranty, Paint, 60 month Prorated,	1
WC, Warranty, Structural, 20 Years, Std., Mods	1
WC, Warranty, Limited Electrical	1
WC, Warranty, Cabinet Construction	1
<b>CERTIFICATIONS REQUIRED</b>	
This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.	1
WC, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	1
All cabinets shall be labeled as to their capacity Rating.	
<b>01- CHASSIS REQUIREMENTS</b>	
<b>FORD CHASSIS</b>	
S WC, 2026 Ford E450, 7.3L Gasoline, Cutaway, 158" WB	1
(2) OEM Alternator Includes 2nd battery located in RF comp. Rubber floor mat, OEM, Cab Headliner Vinyl	
Domestic Chassis	1
<b>ALTERNATORS</b>	
Alternator - Standard OEM	1
<b>SUSPENSION</b>	
Rear Suspension, OEM Springs	1
<b>HIGH IDLE</b>	
High Idle Controls, OEM	1
<b>FRONT END ALIGNMENT</b>	
Front End Alignment, None- QC Check -Standard	1
<b>OUTSIDE REAR VIEW MIRRORS</b>	
Mirrors, Sail Mount, OEM Mirrors	1

DESCRIPTION	QTY		
<b>WHEEL COVERS</b>			
WC, Wheel Covers, Phoenix #NF12, Installed, E-Series, with Air Max Valve Extenders,	1		
<b>BASE CONVERSION</b>			
MD, Conversion, Type III, 170 Module, Ford- 23-1	1		
<b>CAB EXTENSION</b>			
WC, 10" Cab Extension	1		
WC, Interior Headroom, 72 Inches	1		
WC, Module, Type 3. 170" Body Length, Duraseam Doors, Cutaway 170" L x 95" W	1		
WC, Body Width 95" Standard	1		
WC, Aisle Space, 50", Type 3 (49-50" actual)	1		
<b>STRUCTURAL FRAMING - RFP</b>			
WC, Type 3, General Body Construction Spec	1		
WC, Type 3, Vehicle Body Structure Spec	1		
<b>UNDERCOATING</b>			
<b>EXTERIOR MODULE CONSTRUCTION</b>			
WC, Stone Guard, Front, Diamond Plate, Type 3, Height	1		
<b>FUEL FILLS &amp; SPLASH PLATE</b>			
WC, Housing Fuel Fill, Cast Aluminum, Type III	1		
<b>REAR KICKPLATE</b>			
WC, Rear Kick plate, Under-Ride Bumper, w/ Tag recess, No lights	1		
<b>SUB-FLOOR SYSTEM</b>			
WC, Flooring, 3/4" Marine Grade Plywood, Type 3/7/9	1		
<b>MODULE ENTRANCE</b>			
WC, Module Access, CS Door standard location	1		
<b>MODULE DOORS, HANDLES &amp; HOLD OPENS</b>			
WC, Duraseam Hinged Doors with Hidden Jamb <b>- Magnetic door switches</b>	1		
WC, Hold Open Rear Entry Doors, (2) 6" Cast Grabber <b>- Installed so doors will open as wide as possible</b> <b>- Mount at BOTTOM OF DOORS</b>	1		
WC, Hold Open - Gas Strut, Curb Side Entry Door, 35#	1		
WC, Patient Entry Door Handles, Trimark Black/Chrome Pull Handle w/"SafePass" With Round Push button Emergency release top and bottom of interior door panels.	1		
WC, Rear Entry Door Trailing Latch, Side release Paddle	1		
WC, Electrical Feed to Required Doors, Spring Protector (per Door)	8		
<b>POWER DOOR LOCKS</b>			
WC, Power Door Lock, Trimark, Each Entry Door	2		
<b>Module entry doors.</b>			
WC, Power Door Lock, Trimark, Each Compartment Door	6		

DESCRIPTION		QTY
All module compartments(except battery comp) .		
WC, Switch, Momentary Rocker,Activate Power Door Locks	1	
Installed on C/S wall at head of S/B.		
WC, Switch, Remote Stealth, Cab/Mod Doors	1	
In grille on passenger's side.		
WC, Relay Control Circuit, Power Door Locks	1	
WC, Circuit, OEM Door Lock to activate Mod Doors	1	
<b>ENTRY DOOR INNER PANELS</b>		
S MD, Entry Panels, Durasafe, Stainless Steel, w/ Center Chevrons,	1	
- Durasafe Design (SAP# ) DOT Blue ILOS, chevrons		
Aluminum Center Panels covered: white/blue reflective tape		
<b>SIDE DOOR STEP</b>		
WC, Side Entry Step Well, Type III, Aluminum Diamond Plate	1	
WC, Light, Side Entry Step well, LED, Whelen #TOCACCCR, 2"	1	
<b>WINDOWS</b>		
WC, Window, Upper, CS/Slider, Rr/Fixed, Privacy Tint, PAN	1	
<b>MODULE TO CHASSIS MOUNTING SYSTEM</b>		
WC, Module to chassis mounting system, Type III	1	
<b>REAR BUMPER AND REAR STEP CONSTRUCTION</b>		
WC, Rear Bumper w/ Skids & Flip Up, F3, w/ holes for 2" LED Lights	1	
w/ Gator Grip on flip up step. Lights in side of bumper pod Steady burn with lights on		
WC, Coating, Polyurethane, Rear Bumper Supports Black	1	
<b>INSULATION</b>		
WC, Insulation, Walls and Ceiling, R11 Fiberglass Batt	1	
<b>RUB RAIL AND FENDER RINGS</b>		
WC, Rub Rails, Skirt Line, Extruded "C" channel (E-one Style)	1	
WC, Tape, Reflective, White, For Extruded Skirt rails	1	
WC, Fender Flare, Bright Finish Aluminum	1	
<b>SPLASH GUARDS AND RUNNING BOARDS</b>		
WC, Mud Flaps, Rear, w/ Wheeled Coach Logo	1	
WC, Running Boards, Ford Type 3, w/Gator Grip	1	
<b>DRIP RAILS</b>		
WC, Drip Rail Trim Moldings Over Door Openings	1	
<b>CAB TO PATIENT AREA ACCESS</b>		
WC, Bulkhead Cabinet, Type III Ford, 10" Cab Extension	1	
WC, Door, Sliding, Bulkhead, w/Sliding Window with sliding Lexan window	1	

DESCRIPTION	QTY		
<b>LICENSE PLATE HOLDER</b>			
WC, License Plate Holder, Cast LP0002-1 for Under ride Bumper in rear kick plate, centered License holder comes with (2) LED lights.	1		
<b>EXTERIOR COMPARTMENT CONSTRUCTION</b>			
WC, Exterior Compartment, Std, Floor 2.5" Drop Down from Door Opening, Each  compartments #2, #4, #6 and #6.5 are STD drop down floor	4		
U Special drop pan for bottom of Compartment "E"	1		
- ADDS Drop Pan in bottom: 10"D x Max width x 4"H - as far outboard as possible			
WC, Exterior Compartment, Sweep out, Each - Compartments #1 and #8 are standard sweep out	2		
WC, Door Sill Protector, Stainless, All Comps Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage	1		
WC, Polyurethane Coating per compartment light gray	6		
WC, Exterior Battery Compartment, Polyurethane Finish	1		
<b>EXTERIOR COMPARTMENT DOORS</b>			
WC, Compartment Comp Handle, Trimark, Oval Pull Handle, Black/Chrome	7		
WC, Compartment Door Latch, Edge Paddle, Trimark, Trailing Door Interior edge style handle comp "#2"	1		
<b>COMPARTMENT DOOR HOLD OPEN</b>			
WC, Hold Open, Gas Strut, Ext Comp, 60lb for comp. #4 hold open	1		
WC, Hold Open Gas Strut, Ext Comp, 30lb Compartments 1, (2)2, 6, 6.5	5		
WC, Hold Open, Gas Strut, RF Comp, 30lb	1		
<b>COMPARTMENT LIGHTING</b>			
WC, Oxygen Light, 3" Surface mount Whelen LED, Clear Mounted in Oxygen Compartment Wall #3	1		
WC, Compartment Light, LED, Whelen #TOCACCCR, 2in, Each Compartment  1 - Ceiling centered 2 - Wall #1 below electrical shelf if optioned 4 - Wall #3 in access panel	7		

DESCRIPTION	QTY	ID	REF. NO
<p>6 - Ceiling centered                      6.5 - Wall #3                      (2) L8 and U8 Right front Cabinet - 1 each section on Wall #3</p>			
<b>COMPARTMENT #1 - STREETSIDE FWD</b>			
WC, Compartment #1, Full Height	1		
<b>COMPARTMENT #2 - STREETSIDE FWD WHEELWEL</b>			
WC, Compartment #2, 50" Aisle, Standard Configuration with double doors	1		
WC, Compartment #2, Shelf, Adjustable, w/Alum Track, First Shelf half depth for stair chair approximately 5" deep	1		
<b>COMPARTMENT #4 - STREETSIDE AFT</b>			
WC, Compartment #4, 3/4 Height. Single door	1		
WC, Compartment #4, Shelf, Adjustable, w/Aluminum Track, First Shelf at bottom of cabt "C4" inside/outside access opening.	1		
WC, Compartment #4, Shelf, Adjustable, Additional, Each 1 above and 1 below the standard shelf. Note total of 3 shelves in compt 4 approx evenly spaced.	2		
<b>COMPARTMENT #6 - CURBSIDE AFT</b>			
WC, Compartment #6, Full Height	1		
WC, Compartment #6, First Divider, Vertical, 3/16" Thick, Recessed Adj Track  centered.	1		
S MD, Compartment #6, Equipment Strap, Seat Belt Style, Each Nylon web strap w/ seat belt buckle and two (2) footman loops	2		
<b>COMPARTMENT #6 AND COMPARTMENT #2 FOR STAIR CHAIR</b>			
Compt. 6 Wall #1 to#3			
<b>COMPARTMENT #6.5 - CURBSIDE AFT WHEELWELI</b>			
WC, Compartment #6.5, Below Squad Bench Floor Level	1		
<b>COMPARTMENT #8 - CURBSIDE UPPER FORWARD</b>			
WC, Compartment #8/8.5, Split doors, Type 3	1		
WC, Compartment #8, Shelf, Adjustable, RF Cabinet, First shelf w/Aluminum Track (1) RF Comp "8"/cabinet "U8" area, centered.	1		
WC, Compartment #8, Shelf, Adjustable, Additional, for Aluminum Track, Each RF Comp "8"/cabinet "L8" area, centered.	1		
<b>INTERIOR TRIM AND FEATURES</b>			

DESCRIPTION	QTY		
WC, Interior Cabinets, Duralite Construction, Wood, CN10 compliant All cabinets shall be labeled with their Rated Weight Capacity.	1		
<b>INTERIOR ADJUSTABLE SHELVES</b>			
WC, Shelf, Interior, Wood , (1) adjustable, in Cabinet U4 U2 L3.5	3		
WC, Shelf Track, Cabinet, #HA24663, CN 10 Upgrade U4 U2 L3.5	3		
<b>HEADLINER</b>			
WC, Headliner, Flat, PVC, Hinged trough cover, 160"+	1		
<b>FLOORING</b>			
WC, Flooring, Lon Seal "Lonplate II " With approximately 3" roll up both street side and curbside.	1		
WC, Color, Gunmetal Gray #424	1		
WC, Floor, Thresholds, .063 Aluminum , Painted w/Black Poly-urea coating	1		
<b>Entry Door Grab Handles</b>			
WC, Entry Door Grab Handles (3), Custom "L" Shape, 1", Yellow - Yellow Powder Coat Finish Stainless Steel Grab Handles	1		
<b>Ceiling Grab Rail - Center</b>			
WC, Ceiling Grab Rail, Overhead, 112", 1" diameter Handicap Style, Yellow Yellow Powder Coat Finish	1		
<b>IV FLUID HANGERS</b>			
WC, IV Hook, Perko Snap Hook w/Velcro Strap, Each	2		
<b>Curbside and streetside standard location</b>			
<b>ACTION WALL AREA #2</b>			
WC, Cabinet, A/A, 50" Aisle, No Bio waste, Rounded corners	1		
WC, Tray, A/A, 50" Aisle, No Bio waste, Poured, Black	1		
WC, AA Upper Cabinets, U2.5 Angled, U2, Full Ht Comp #1	1		
WC, Door, U2 Gray Polycarbonate Slider, CN 10 Compliant	1		
WC, Door, U2.5 , Hinged Wood	1		
<b>Hinged on Right.</b>			
<b>Interior Street side #3 - CPR Seat</b>			
WC, CPR side seat, Fixed Backrest, 25" wide Std.	1		
WC, CPR, Lid, Hinged Flip Up With Trimark Latch	1		
WC, Cabinet U3 or U3.5, w/ CPR seat (ONLY Available in 72" HR)	1		
<b>Note: TO meet 43" minimum KKK requirement for space between cushion on Side seat and bottom of splint cabinet.</b>			

DESCRIPTION	QTY	REF. NO
WC, Cabinet C3.5, deleted For Telemetry Area	1	
WC, Cabinet L3.5, full height, std	1	
WC, "U" Barrier Bar, Padded, 1.5" SS, CPR Seat, Gunmetal	1	
Mounted at the front of the CPR side seat vertically in line with the Padded head cushion on the upper AA cabinets.		
WC, Telemetry Tray, Poured, Black, Narrow, 50" Aisle, Type 3	1	
WC, Door, U3 Gray Lexan Flap Glass, CN 10 Compliant	1	
WC, Doors, L3.5, Gray Polycarbonate Slider, CN 10 Compliant	1	
<b>STREETSIDE REAR AREA #4</b>		
WC, Cabinet U4, Combined with U3.5	1	
WC, Cabinet C4, Inside/Outside Access	1	
<b>CABINET DOORS</b>		
WC, Doors, U4/U3.5 Combined, Gray Polycarbonate Slider - CN 10 Compliant	1	
WC, Doors, C4, Gray Polycarbonate Slider - CN 10 Compliant	1	
<b>SQUAD BENCH AREA</b>		
WC, Squad Bench, Bio-Waste @ Head	1	
WC, Lid, Squad Bench, Single W/Bio-Waste	1	
WC, Handle, Trimark, CPR Seat, Std.	1	
WC, Handle, Trimark, Squad Bench, STD	1	
WC, Strut, Gas, 60 LB, Installed	1	
WC, Seatbelt, Assy, (4 Point), Per4Max, Yellow, Vert. Mount, (1) Each, CN-8	3	
(1) for CPR side seat		
(2) for Squad bench		
WC, Patient Restraint Belts, Squad Bench (3)	1	
WC, Safety Net, Head of Squad Bench, 2" Straps, Yellow	1	
attached to floor at head of squad bench, CS wall and overhead liner with removable latches.		
<b>CURBSIDE REAR</b>		
WC, Cabinet, Curbside Rear, Standard	1	
WC, Cabinet, Glove Box Holder, (3), Above C/S door,	1	
<b>CURBSIDE RIGHT STACK STORAGE #8</b>		
WC, RF ALS, Split Upper/Lower, HVAC at Top	1	
WC, Doors, RF, U8, Dual Gen III OHO, Polycarbonate Doors, Gray	1	
WC, Doors, RF, L8, Dual Gen III OHO, Polycarbonate Doors, Gray	1	
<b>ATTENDANT SEAT</b>		
WC, Attendant's Seat, EVS 1880, Comfort, Hi-Back Child Safety w/Per4Max	1	
WC, Color, Gunmetal, Per4Max Belt, Yellow	1	
WC, Attendant's Seat Base, EVS CBS Box Style	1	
cabinet base, opening to face CS entry door		
**TO BE MOUNTED AS FAR FORWARD AS POSSIBLE TO MAXIMIZE KNEE ROOM***		
<b>INTERIOR COLORS</b>		
WC, Mica, Dove Gray (Matte)	1	
<b>UPHOLSTERY</b>		

DESCRIPTION	QTY		
WC, Upholstery Color, Gunmetal	1		
WC, Backrest Cushion, EVS, Gunmetal, w/ WC Logo, Each	3		
(1) CPR			
(2) Squad Bench			
<b>CABINET KICK PANELS</b>			
WC, Kick plate, 8" Brushed S/S, Face Of Squad Bench	1		
WC, Kick plate, 8" Brushed S/S, On Face of Base wall	1		
<b>CABINET LATCHES- INTERIOR</b>			
WC, Latch, Southco M1, 2" S/S, (3/4" door) Non-Locking,	1		
CN 10-Rated 10lb			
(self latching) Flush Mount. Non-Locking			
Sharps and waste			
U2.5			
WC, Latch, Southco M1, 2" S/S, (3/8" Door) Non-Locking,	2		
CN 10-Rated 10lb			
(self latching) Flush Mount. Non-Locking			
Glove Caddy			
U3			
<b>GENERAL WIRING</b>			
WC, Electrical System: Relay Plex System	1		
WC, "E" Spec, Relayplex Harness Set, No Lightbar	1		
<b>CAMERAS</b>			
U Camera, Patient Compartment and Back Up	1		
Camera, Patient Compartment Ref			
Hanscom			
kit HK 7211.			
In the module mount the camera on the headliner next to the streetside cabinets.			
Trigger camera display on with Master Switch.			
#HC IR250 rear back up camera with #HC20M video cable,			
Mount camera exterior on rear of module, off center toward driver's side. Triggered when units placed in reverse gear.			
<b>COMMUNICATION</b>			
WC, Coax Cable, RG58/U, Each, Terminate:	3		
- From module roof port Dome #7 to behind			
the passenger seat Standard - with 6' pigtails			
- From module roof Dome #3 to behind passenger seat			
standard - with 6' pigtails			
Dome# 6 to behind drivers seat with 6' pigtails			

DESCRIPTION	QTY		
WC, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.	1		
<b>POWER SOURCES</b>			
WC, Buss Bar Assembly (+/-), 5 Position, for ground and hot IATS, Inside front console, see 40 amp power source.	1		
WC, Power Source, 12VDC, 20A, Ignition/Shoreline Hot 20amp 12 volt DC circuit ran to two locations (1) pre-wire coil and tagged in action area (1) pre-wire coil and tagged behind driver's seat.	1		
WC, Power Source, 12 VDC, 15 Amp (+-), Ignition Hot - Ignition hot, terminating in cab console - with 6 foot tails (hot and ground).	1		
WC, Power Source, 12 VDC, 30 Amp (+-), Constant Hot - Constant Hot, to terminate behind the passenger seat - with 6 foot tails (hot and ground).	1		
WC, Power Source, 12 VDC, 40 Amp (+-), Constant Hot Constant hot Inside front console. To include ground, connect to buss bar in console.	1		
WC, Alarm, Low Voltage, Audio/Visual Light in cab console and Buzzer in cab.	1		
WC, Voltmeter, OEM, In Dash	1		
<b>BATTERY SYSTEM</b>			
WC, Battery Sw, 5min Timer, F3, Gasoline, Fig 5B Activated thru OEM ignition switch timer function upon ignition "off". Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer.  (1) OEM battery (1) OEM battery in RF Lower Compartment  ONLY Module power is turned on/off. Chassis power is NOT turned off.	1		
WC, Outlet, Power Point Style, (2), A/A - on standard 20-amp ignition hot circuit.	1		
WC, Outlet, Power Point Style, Each  (1) Above squad bench, 20" up from the top deck of the squad bench, 8" over from the edge of the foot of squad bench wall (Ign hot) (2) On front console, driver side, below siren (ign hot) (1) Front bulkhead wall area for Engel Cooler (constant hot)	4		
WC, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel	2		

DESCRIPTION	QTY		
<p>Located on the passenger side of the center console,ignition Hot</p>			
<p>WC, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel, Each Location in the Action area outlet panel.</p>	1		
<p><b>IGN HOT</b></p>			
<p><b>FRONT CONSOLE</b></p>			
<p>WC, Console, Drivers Switch &amp; Radio, Center, Aluminum, Black, Ford cutaway Black polyurethane coated .090 Aluminum  See below for Optional panels 5.25 x 12.5 x 7" deep storage area at rear</p>	1		
<p>Single Blank Panel</p>	1		
<p>9" deep Glove Box Panel</p>	1		
<p>Cup Holder Panel (No Handle Notch)</p>	1		
<p>WC, Flat Switch Panel</p>	1		
<p>WC, Module Electrical Panels, Brushed Stainless Steel brushed stainless steel panels for the Outlet panels, switch panels and other faceplates in the MODULE only.</p>	1		
<p><b>ATTENDANT CONTROL PANEL</b></p>			
<p>WC, Console, A/A, Wood, Angled</p>	1		
<p><b>SIREN ELECTRONIC - CONTROL HEADS / AMPS</b></p>			
<p>WC, Siren, Whelen, WS-295-SLSA1, California Title 13 Compliant</p>	1		
<p><b>SIREN SPEAKERS</b></p>			
<p>WC, Speakers, (2), Cast, SAD4319/SAP4319, In Bumper,</p>	1		
<p>WC, Switch, Siren/Horn Thru Horn Ring</p>	1		
<p><b>BACK-UP ALARMS</b></p>			
<p>WC, Back-Up Alarm, w/ Cutoff, Auto Reset</p>	1		
<p><b>WARNING LIGHT FLASHERS</b></p>			
<p>WC, Brake Override Circuit Rear of module red 900 Red LED's rear lights under, upper outer warning lights.</p>	2		
<p><b>WARNING LIGHTS</b></p>			
<p>Lights on unit are to have primary and secondary Triple K compliant flash patterns</p>			
<p>U LED Beacon, Whelen L31HAF, Installed Top of Module SR#220895F Item# 8 SAP#10548552 No switch Module roof, centered 16" inboard from rear of module, Beacon will be on anytime Ign is on and units in gear. Reference Previous Unit 666777</p>	1		
<p><b>LED Series - 900 (Flange Separate)</b></p>			
<p>WC, Light, Whelen 900 LED, Red, Clear Lens, 90RR5FCR, Internal Flasher</p>	14		

DESCRIPTION	QTY		
- (2) each side standard location - (2) on rear in upper outer corners - (2) on front in upper outer corners Pri/Sec internal comet flash			
(2) Rear Directly under upper outer red warning lights Pri/Sec external comet AFM560 (Brake over ride) Set light to steady burn (2) Front 1 each side of center white light (Cool bar) Pri only internal comet flash (2) angled ends of cool bar Pri only internal comet flash			
WC, Light, Whelen 900 LED, Amber, Clear Lens, 90AA5FCR, Internal Flasher	1		
Center rear Pri/Sec Comet Flash			
WC, Light, Whelen 900 LED, Clear, 90CC5FCR, Internal Flasher	1		
Center front on coolbar Pri ONLY Comet Flash			
WC, Flange, Super 900 LED, #90FLANGC <b>LED Series - 700 (Flange Separate)</b>	16		
WC, Light, Whelen 700 LED, Red, Clear Lens, 70R02FCR	4		
Front intersectors ILOS Pri only internal comet flash (2) Rear Intersections over rear wheel wells. Pri only internal comet flash			
<p style="text-align: center;"><b>WHELEN FLANGES 7 SERIES LIGHTS (Flange Separate)</b></p>			
WC, Flange, Whelen, Chrome, 700 Series Light (1), Mods - For 7 Series Lights	4		
<p style="text-align: center;"><b>WARNING LIGHTS -WHELEN MICRON</b></p>			
WC, Light, Whelen, LIN3, LED-Red, RSRO2ZCR - (2) in upper grille - (2) in lower grille Primary only Comet Flash	4		
WC, Flange, Whelen, Chrome, For LIN3, Each <b>EXTERIOR AUTOMOTIVE LIGHTING</b>	4		
WC, Taillight Pkg, Whelen, LED Stop/Tail, Turn & LED Backup, w/WC logo - Brake- Steady Burn - Turn Arrow – sequential arrow - 700 LED Backup Clear lens over all three lights	1		

DESCRIPTION	QTY		
<b>ICC/MARKER LIGHTS</b>			
WC, Light, Clearance, Amber LED, Each On front as clearance lights.	3		
WC, Light, Clearance, Red LED, Each On rear as clearance lights.	3		
WC, Lights, Red, 2", Marker, LED, Pair in bumper	1		
WC, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers - High intensity flashers; thru separate switch	1		
<b>FLOOD AND LOAD SYSTEMS</b>			
WC, Light, LED, Whelen, Clear, #9SC0ENZR, 24 LED, w/Chrome Flange	6		
(2) each side as scene lights (2) On rear as load lights			
WC, Scene Lighting, CS, Activate on Opening of CS Entry Door	1		
<b>11 - INTERIOR LIGHTING</b>			
WC, Lights, Dome, LED, Whelen, White Flange, (4) S/S, (3) C/S <b>NOTE: NO VISABLE FASTENERS OR HOLES.</b>	1		
WC, No Lighting Recessed into Trough Cover	1		
WC, Timer, Momentary Switch, 15 Minute, Constant Hot	1		
Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to CS Domes in liner on High.			
<b>SPOTLIGHTS / HANDHELD LIGHTS</b>			
WC, Handheld Spotlight - Sho-Me 200,000 CP	1		
<b>ATTENDANT LIGHT</b>			
WC, Light, Intertek ZY-PIR38 12v, LED, 15 inch, Each	1		
<b>12 - ELECTRICAL 125 VOLT AC</b>			
<b>SHORELINE INLET</b>			
WC, Shoreline, 20A, Super Auto Eject, White - with white cover; Mounted FORWARD of COMPT 1	1		
<b>OUTLETS - 125VAC</b>			
WC, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet in the RF Cabinet "U8", wall #2, upper right.	1		
WC, Outlet, 125 VAC, Duplex, Each, State Location: (1) Telemetry area, wall #2, near wall 1, mid height. (1) Interior CS Wall above foot end of squad bench mounted approx. 15" up Eng Note: Reference Previous unit 324365 for this location	2		
<b>BLOCKHEATERS</b>			

DESCRIPTION	QTY		
Block Heater - With OEM Plug This option does not include a switch. (STANDARD).	1		
<b>INVERTER - 125VAC</b>			
WC, Inverter/Charger, Vanner LifeSine - Mounted on ceiling of compartment "2" upper left hand corner with expanded metal cage. Make sure inverter cage is tight and space in Compt#2 is maximized.	1		
<b>AUXILIARY ENVIRONMENTAL SYSTEMS</b>			
WC, Exhaust Fan, Single 12V, in Line Blower	1		
<b>WHEELED COACH HVAC UNITS</b>			
WC, Hoses, Heater, No Max, to Rear	1		
WC, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo	1		
WC, Heat/AC Located RF corner, over ALS cabinet.	1		
WC. Generation III Fiberglass Cool Bar cover	1		
WC, Heat/AC, F3, Combo, w/Coolbar, Brushless Motor 12vdc External Condenser, in Coolbar mounted on front of module. Painted to match front of module.	1		
WC, Thermostat, Hoseline Master Control Digital CM5000, Brushless Motor	1		
Mount probe in front of evaporator Streetside AA			
<b>COT MOUNTING PROVISIONS</b>			
<b>Cot Mounts</b>			
WC, Stryker Performance Load, Add Floor Structure Plates & Wiring for Future Ins	1		
Additional floor structure for future installation of a Stryker Performance Load system Includes pre-wire which will terminate			
Note: Stryker Deutsch connection to be coiled up on the interior of the module.			
WC, Cut Floor and Install Cot Mount Floor plate, 6390-700-001A For Powerload or Performance Load Cot mounts.	1		
Center Mount	1		
<b>OXYGEN AND AIR SYSTEMS</b>			
WC, O2 Cylinder Wrench ,Tethered  in oxygen comp.	1		
WC, O2 Cylinder Bracket, Multiversal, #QR-MV, W/ Straps  Set for M Cylinder	1		
WC, Track, Unistrut for Oxygen Rack	1		
WC, Manual, O2 System	1		
WC, O2 Regulator, Preset 50 PSI	1		

DESCRIPTION	QTY		
WC, O2 Outlets, Ohio Style (2 in Action Area, 1 CS Wall) (2) in Action Area, (1) CS wall above squad bench	1		
WC, Lexan Flap, w/Hinge	1		
<b>PORTABLE O2 HOLDERS</b>			
WC, O2 Cylinder Holder, Single, Zico QR-D-2 Strapless, CN 10 Certified	2		
Installed aisle side of RF ALS stack mounted approx. 3" off floor centered.			
<b>SUCTION SYSTEM</b>			
WC, Suction Pump, SSCOR 90206	1		
In Compt "2" on ceiling close to inverter. Expanded metal cage. Make sure cage is tight and space in Compt #2 is maximized.			
WC, Suction Port, Hole Only, No Outlet Plate	1		
Located in wall of Action Area			
WC, Suction System, SSCOR 23002 Disposable w/Canister Clip & Regulator	1		
<b>PAINT AND FINISH</b>			
WC, Wheeled Coach Paint Process	1		
Module Paint, Single Color, OEM White	1		
Ford white: FA91:YZ			
Cab Paint - Single Color, OEM White	1		
<b>PAINT STRIPING DESIGN</b>			
Paint Belt, None	1		
<b>DECALS AND NOMENCLATURE</b>			
	1		
WC, Ship Loose, W.C. Standard Items	1		
WC, Fire Extinguisher, (1), 5 lb. ABC, Ship Loose	2		
HD Amerex Bracket #861H with Amerex 5LB fire extinguisher.			
	1		