



Specification Summary

North Eastern Rescue Vehicles

10 Dwight Park Drive
Syracuse, NY 13209

(315) 414-9999

Name	Specifications
<p data-bbox="131 877 261 909">Type II - TS</p> 	<p data-bbox="870 877 1187 909">Overall Length 236" (599 cm)</p> <p data-bbox="870 909 1166 940">Overall Width 98" (249 cm)</p> <p data-bbox="870 940 1195 972">Overall Height 103" (262 cm)*</p> <p data-bbox="870 972 1130 1003">Headroom 69" (175 cm)</p> <p data-bbox="870 1003 1149 1035">Wheelbase 148" (376 cm)</p> <p data-bbox="870 1035 1328 1066">Payload Capacity Up to 2,500 lbs (1134 kg)</p> <p data-bbox="870 1098 1463 1161">*Total height of vehicle may differ according to chassis and suspension</p>

Sales Options by Category

Name/Description	Quantity
<p data-bbox="370 1654 643 1686">Street side configuration</p> <p data-bbox="370 1686 1190 1755">be sure middle rear compartment has no doors or shelves;with 120V & 12V outlets. Add cardiac monitor base (turning only)</p>	1.00



change order - dual usb outlets (cab console)	1.00
change order - rear amber light clear amber light must stay on when doors open	1.00
change order - O2 compartment strap replace o2 compartment standard strap with 3 cam bucked strap	1.00
change order - upholstery color change order all upholstery to be gray. the padding above the doors is to remain yellow.	1.00
change order - pre wire for warning light change order pre-wire for steady burn red warning. Upper center Aero Cab Riser.	1.00
change order - dip switch siren programming change order replace std siren for Whelen 295FFSA7	1.00
change order - super auto eject 20 amps	1.00
change order -flip-up doors add flip-up door w/ss lockage handle in middle upper section	1.00
change order - additionnal 120v. outlet add 1 x 120v. outlet in the wall behind the driver seat.	1.00
change order - tinted privacy glass tinted privacy glass for rear and right side windows to be added	1.00

10-Base (BAS)

<i>Name/Description</i>	<i>Quantity</i>
Type II - Van	1.00

11-Chassis (CH*)

<i>Name/Description</i>	<i>Quantity</i>
Conversion Ford T250 Van Conversion Ford T250 Van	1.00
Ford Transit T250 Gas Van AWD Ford Transit T250 Gas Van AWD	1.00



3,5L EcoBoost® V6 Gasoline Engine
 Mid Height Roof
 Wheelbase 148" (3760 mm)

16-Emergency and Working Lights (EWL)

<i>Name/Description</i>	<i>Quantity</i>
Demers T2 Aero Cab Riser TS 2RR-2C3RC-2RR Demers Aerodynamic Cab Riser (500 series), 2RR-2C3RC-2RR	1.00
Two (2) LED in grille (LINZ6) Two (2) LED in front grille. LINZ6 series (4 X 2) LED lights. (Standard setup contains red lighting)	1.00
Intersection Lights, (2) LED (700) Two (2) intersection lights. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red lighting)	1.00
Emergency Lights, (2) LED, Inter. Side Mount (700) Two (2) emergency lights, intermediate side mount. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red lighting)	1.00
Four (4) LED lateral emergency lights (600) Four (4) LED lateral emergency lights (two (2) on each side, 600 series 6 X 4) (Standard setup contains red lighting)	1.00
Scene Lights, Four (4), Clear LED, (600) Four (4) lateral LED scene lights (two (2) on each side) 600 series 4 x 6	1.00
Rear Spoiler TS 1R-1W-1A-1W-1R Demers aerodynamic rear spoiler with 1 red / 1 white / 1 amber / 1 white / 1 red (500 series 5 X 1, perimeter lights 8 X 2)	1.00
Two (2) Rear LED lights (700 series 7 X 3) Two (2) Rear LED lights (700 series 7 X 3) (Standard setup contains red lighting)	1.00

17-Audible Warning System (WRN)

<i>Name/Description</i>	<i>Quantity</i>
Back-Up Alarm Back up alarm (97dB) with override switch.	1.00
Whelen 295SLS Hands-Free Siren Whelen model 295HFSA1 siren amplifier with 17 Scan-Lock™ siren tones.	1.00
Upgrade Siren to Whelen 295-HFSA7 dual-tone Siren upgraded to Whelen 295-HFSA7 dual-tone ILO standard	1.00
Whelen SA315 Series Speakers Whelen SA315 series speakers is a compact speaker meeting SAE Class A requirements when paired with Whelen 100 watt siren amplifier.	1.00

18-Exterior Vehicle features (VFT)

<i>Name/Description</i>	<i>Quantity</i>
Front cab mud guards Front cab mug guard flaps ford	1.00
OEM exterior mirrors Keep OEM exterior mirrors	1.00
Undercoating Protection Undercoating protection for module and chassis.	1.00
Van Anti-skid rear steps Van Anti-skid rear steps.	1.00



Van Lateral Steps, Anti-Skid Material & Mud Guards	1.00
Anti-skid lateral steps includes: mud guards	

19-Convenience (CNV)

<i>Name/Description</i>	<i>Quantity</i>
Demers Fast Idle Demers fast idle is generated by the multiplex module, it allows fast charging of the batteries by the engine when specific conditions are met.	1.00
Anti-Theft System The anti-theft allows leaving the vehicle without keys and the engine running to keep the vehicle at the ideal operating temperature. It protects against theft by turning off the engine if the vehicle moves.	1.00

22-Drivers Compartment (CAB)

<i>Name/Description</i>	<i>Quantity</i>
Spotlight in Front Cab, Hand-Held, with Bracket Hand-held spotlight, 2000 lumens, with trigger-type switch and bracket.	1.00
Control Center lower, switches and LED pictograms Lower dashboard control center with switches and LED backlit pictograms	1.00
Cab headliner with OEM reading lights Sprinter Type 2 ceiling with access flaps	1.00
Goose neck reading lamp Goose neck reading lamp on front console.	1.00

23-Curbside Configuration (CRB)

<i>Name/Description</i>	<i>Quantity</i>
Small cushion, front squad bench Small cushion, front squad bench	1.00
Safety Net Safety net at the head of the curbside configuration, by the side entry door (C2).	1.00
Full Length Seat Backrest Single full length molded seat backrest	1.00
Single full length molded seat cushion Full length molded seat cushion (Medium : 45 - 50 inches)	1.00
Seating for two (2) passenger, 6 pts safety belt Seating for two (2) passenger, 6 pts safety belt	1.00

24-Streetside Configuration (STR)

<i>Name/Description</i>	<i>Quantity</i>
Flip-Up Door, Clear Sliding Window Aluminum flip-up frames, self latching for easy restocking of cabinets. Polycarbonate clear sliding windows.	3.00
Flip up door with stainless steel lockable handle Flip up door with stainless steel lockable handle in middle upper section.	1.00
Polycarbonate Clear Sliding Windows Polycarbonate clear sliding windows. Type 2	4.00
Lower Medical Cabinet, Full storage for TS Medical cabinet with long counter top and full storage area	1.00

25-Forward Bulkhead (FWB)

<i>Name/Description</i>	<i>Quantity</i>
Pass-through sliding window Pass-through sliding window on front division for communication with cab. Type 2	1.00



Upper front partition with retaining straps	1.00
Upper front partition with retaining straps in front TS ALS compartment	
Lower front partition with retaining straps	1.00
Lower front partition with retaining straps in front TS ALS compartment	
Right side division TS	1.00
Right side division TS, Stair chair location and fixed shelf	

26-Attendant Seat (AST)

<i>Name/Description</i>	<i>Quantity</i>
EVS 1860 3Pts Vac-Formed Seamless ChildSeat, Fixed	1.00
EVS 1860 3Pts Vac-Formed Seamless Child Seat, Fixed Base	

27-Cot Configuration (COT)

<i>Name/Description</i>	<i>Quantity</i>
Floor Plate & Pre-wire Power-LOAD - GEN 2 (NEW)	1.00
Stryker Power-Load floor plate. No cot fastener included. Include pre-wiring for charging feature. Default option for new Power-LOAD system from the field.	
Wheel guide for cot location	1.00
Cot wheel guides for left side location	
Left side floor mount cot configuration	1.00
Left side floor mount cot configuration Type 2	

28-Rear Control Panel (CAR)

<i>Name/Description</i>	<i>Quantity</i>
Switches with LED backlit pictogram - TYPE II	1.00
Switches with LED backlit pictogram - TYPE II	

29-Oxygen (OXY)

<i>Name/Description</i>	<i>Quantity</i>
Oxygen Compartment rear curbside	1.00
Vertical Oxygen Compartment rear curbside Pivoting access door for oxygen tank.	
Oxygen Outlets, Three (3)	1.00
Three (3) oxygen outlet, two (2) in ECC, one (1) on curbside	
Oxygen Outlet, Quick-Connect	3.00
Quick-connect style oxygen outlet.	
Oxygen Regulator, Manual, 50 PSI	1.00
Manual oxygen regulator (50PSI).	
"D-size" Portable oxy storage (2) in squad bench	1.00
"D-size" Portable oxygen cylinder storage (2) located in squad bench	
Universal vert oxygen cylinder holder "K" or "M"	1.00
Universal vertical holder for main oxygen cylinder type "K" or "M"	

31-Suction (SUC)

<i>Name/Description</i>	<i>Quantity</i>
Suction System location in ECC	1.00
Main suction system is located in front streetside action area.	
Thomas high flow vacuum pump	1.00
Thomas high flow vacuum pump	
Vacuum regulator with disposable canister	1.00
Vacuum regulator with disposable canister	

32-Electrical System (ELE)

<i>Name/Description</i>	<i>Quantity</i>
Power Inverter, Xantrex Freedom, True Sine, 1000W	1.00



The inverter/charger provides AC power using the DC power from the conversion battery bank. Recharge all battery banks and power all 120 volts AC outlets when the external shoreline is connected.

Electrical Outlet, 120V AC with Indicator	1.00
120V AC hospital-grade electrical outlets with indicator.	
Grey 15 amps standard outlet with indicator	1.00
Grey 15 amps standard outlet with indicator	
Add 120V AC Duplex outlet with indicator	1.00
Additional 120V AC Duplex outlet with indicator. Details and location are as follows: wall behind the driver seat (in the cab)	
Electrical Outlet, 12V DC 20 amp with Indicator	1.00
12V DC, 20 amp Duplex electrical outlets.	
Add Dual USB DC outlet with indicator	1.00
Additional dual USB DC outlet with indicator. Details and location are as follows: -upper front of cab console	
Two (2) OEM batteries	1.00
Two (2) OEM batteries for Type II vehicles.	
Demers Multiplex system - Type II (TS)	1.00
Demers Electronic Management System (DEMS) - Multiplex system - Type II (TS).	

33-Communication System (COM)

<i>Name/Description</i>	<i>Quantity</i>
Pre-Wiring for 2-Way Radio, Two (2) Antenna Cables	1.00
Wiring preparation for two-way radio, with two (2) antenna cables.(routed from front cab to radio communication compartment)	
Radio Communications Compartment	1.00
Radio communications compartment universal board, Bussmann blade-type fuse panels, and harness to power the radio communication devices.(12V battery feed, ground, ignition).	

34-HVAC (CVC)

<i>Name/Description</i>	<i>Quantity</i>
Ducted combo AC/heating unit tie-in to OEM	1.00
Ducted combo air conditioning / heating unit tie-in to OEM on curbside	
Exhaust fan single	1.00
One (1) exhaust fan for contaminated air. Activated by front control interface or rear console switch. (Included)	

35-Interior Lights (ILG)

<i>Name/Description</i>	<i>Quantity</i>
LED Dome Lights, Adjustable, Dig. Timer	7.00
The ceiling lights have four (4) different intensities. Each time the ceiling lights button is pushed, the intensity increases, until maximum intensity is reached.	

36-Grab Handles (GBR)

<i>Name/Description</i>	<i>Quantity</i>
Grab Bars Color, Yellow	1.00
Color of selected grab bars is Yellow.	
Two (2) rear door mounted soft grab bar, 7"	1.00
Two (2) door mounted grab bars, 7", inside of rear doors (A1 and A2).	
Embarking Grab Bars, 12"	1.00
Two (2) entry grab bars, 12" each, mounted inside the patient compartment. One (1) near the curbside entry door, and one (1) near the R2 rear entry door.	



One (1) ceiling mounted grab rail, 60"	1.00
One (1) ceiling mounted grab rail, 60"	

37-Finish and Trim (FNS)

<i>Name/Description</i>	<i>Quantity</i>
Rear doors trims	1.00
Rear Exterior Door finish TS.	
Lonseal, Lonplate II, Gun metal	1.00
Lonseal, Lonplate II, Gun Metal floor covering.	
Ambassador Grey Upholstery	1.00
Ambassador grey vinyl upholstery for seat and padding covering.	
Black Upholstery	1.00
Black vinyl upholstery for seat and padding covering.	
Safety Yellow Upholstery	1.00
Yellow vinyl upholstery for safety exit padding covering.	
Insulation ethafoam between chassis and floor	1.00
Insulation (0,125 ethafoam) between chassis and floor boards.	
Plywood wood flooring	1.00
Exterior grade plywood, 0,625 inches thick.	
Fiberglass Ceiling	1.00
Fiberglass ceiling in Patient Compartment.	
General Vehicle Identification	1.00
Vehicle general labels identification.	

38-Functionality (FCT)

<i>Name/Description</i>	<i>Quantity</i>
Fire extinguisher ABC with heavy duty bracket	1.00
Fire extinguisher (5 lbs) ABC with heavy duty bracket in patient compartment	
Two (2) recessed/flexible IV hooks in ceiling	1.00
Two (2) recessed/flexible IV hooks in ceiling	
Trash Container, Flip-Down, Hands-Free	1.00
Trash container bracket in curbside flip-down container.	
Two (2) recessed radio speakers	1.00
Two (2) recessed radio speakers.	