



QUOTATION

North Eastern Rescue Vehicles, Inc.
 Bob Reilly
 10 Dwight Park Drive
 Syracuse, NY 13209

North Eastern Rescue Vehicles, Inc
 Bob Reilly
 10 Dwight Park Drive
 Syracuse, NY 13209

Job/Order No: 643300

DESCRIPTION	QTY
WARRANTY	1
WC, Warranty, Conversion, 12 Month	1
WC, Warranty, Paint, 60 month Prorated	1
WC, Warranty, Structural, 20 Years, Mods	1
WC, Warranty, Limited Electrical	1
WC, Warranty, Cabinet Construction	1
== WC- Type 1 CitiMedic Gen2 148"	
This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.	1
WC, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	1
All cabinets shall be labeled as to their capacity Rating.	
01- CHASSIS REQUIREMENTS	
CM, 2026 Ford F350, 4x4, 6.7L ,169" WB Auto throttle OEM Ford 410 Alternator OEM Ford Mirrors, OEM, Heated/Remote Cab seats OEM 40/20/40 split bench (Center removed) Sync 4 8" LCD Capacitive Touchscreen with Swipe Capability Wireless Phone connection AppLink w/app catalog 911 assist Apple carPlay and Android Auto Compatibility Digital Owners manual Smart-charging USB-C Ports (2)	1
FRONT END ALIGNMENT	
Front End Alignment, None- QC Check	1
MODULE BODIES:	
CM, Module, Type 1, 148" Body Length, 90" Wide, Duraseam Doors, 148" L x 90" W	1
EXTERIOR MODULE CONSTRUCTION	
CM, Stone Guard, Front, Diamond Plate, Type 1, Standard Height	1
CM, Drop Skirt both sides, 3" forward of rear wheels	1
FUEL FILLS & SPLASH PLATE	
CM, Housing Fuel Fill, Cast, Type 1	1

DESCRIPTION	QTY
DEF FILL HOUSING AND SPLASH PLATE	
REAR KICKPLATE	
CM, Rear Kick plate, Under-Ride Bumper, w/ Tag recess, No lights, CM+	1
SUB-FLOOR SYSTEM	
CM, Flooring, 3/4" Marine Grade Plywood, Type 1	1
MODULE ENTRANCE	
MODULE DOORS, HANDLES & HOLD OPENS	
CM, Duraseam Hinged Doors with Hidden Jambs	1
- Magnetic door switches	
CM, Hold Open Rear Entry Doors, (2) 6" Door Grabber	1
- Installed so doors will open as wide as possible	
- Mount at Bottom of doors.	
CM, Hold Open, Gas Strut, Curb Side Entry Door, 35#	1
CM, Patient Entry Door Handles, Trimark Black/Chrome Pull Handle w/"Push Button"	1
With Round Push button Emergency release top and bottom of interior door panels.	
CM, Rear Entry Door Trailing Latch, Side release Paddle	1
CM, Power Door Locks, All Module doors (except Batt)	1
Wiring to Module Compartment and Access Doors for electric locks, wiring to CS wall for Switch.	
ENTRY DOOR INNER PANELS	
CM, Entry Door Panels, Upper/Lower, S/S	1
- Durasafe Design	
- Logo to be cut in the lower entry door panel with a Red reflective 3M material (to match the chevron on the lock box) attached to an aluminum panel behind the logo.	
SIDE DOOR STEP	
CM, Side Entry Step Well, Type I, Aluminum Diamond Plate	1
CM, Light, Side Entry Step well, LED, 2", Whelen #TOCACCCR	1
WINDOWS	
CM, Window, Upper, CS/Slider, Rr/Fixed, Privacy Tint, PAN	1
Curbside window with lower slider section	
Rear windows fixed	
Privacy Tint	
MODULE TO CHASSIS MOUNTING SYSTEM	
INSULATION	
CM, Insulation, Walls and Ceiling, R11 Fiberglass Batt	1
There shall be double bubble insulation in the entry and compartment doors.	
RUB RAIL AND FENDER RINGS	
CM, Rub Rails, Skirt Line, Extruded "C" channel (E-one Style), 148"	1
CM, Fender Flare, Black Rubber	1
CM, Mud Flaps, Rear, w/ Wheeled Coach Logo	1
CAB TO PATIENT AREA ACCESS	
LICENSE PLATE HOLDER	
EXTERIOR COMPARTMENT CONSTRUCTION	
CM, Compartments, Std, Floor Drop Down	3
Compartment #6 (more than 2.5" for spare tire)	
Compartment #2 -2.5" drop-down	
Compartment #4, 4" drop-down	
CM, Compartments, Sweep out	2
Compartments #1 & #8.5 are standard sweep out	
CM, Door Sill Protector, Stainless, All Comps	1
CM, Compartments, Diamond Plate Finish Per Comp	5
Machine stamped louvers located above the floor line for venting.	
Comp #1, 2,4,6, 8.5	

DESCRIPTION	QTY
EXTERIOR COMPARTMENT DOORS	
CM, Compartment Comp Handle, Trimark, Oval Pull Handle, Black/Chrome	5
COMPARTMENT DOOR HOLD OPEN	
CM, Hold Open, Gas Strut, Ext Comp, 30lb. Compartments "#6", "#1", & "#2"	3
CM, Hold Open, Gas Strut, Comp Door Only, 110 Degree, 30lb, Comp #4 to allow easier access to the Stair chair.	1
CM, Hold Open, Gas Strut, RF Comp, 30lb #8	1
COMPARTMENT LIGHTING	
CM, Oxygen Light, 3" Surface mount Whelen LED, Clear Mounted in Oxygen Compartment	1
CM, Compartment Light, 4" Optronic,#BUL43-CBK, LED, Each Compartment	6
1 - Access Panel Wall 1 2 - Wall #1 4 - Ceiling 6 - Wall #3 U8- in access panel L8- in access panel	
COMPARTMENT #1 - STREETSIDE FWD	
CM, Compartment #1, 3/4 High, CitiMedic.	1
COMPARTMENT #2 - STREETSIDE FWD WHEELWELL	
CM, Compartment #2, Citimedic, Type 1 Mount the inverter on the ceiling of compartment.	1
CM, Compartment #2, Shelf, ADP, Fixed for Electrical storage Screw in shelf that extends from wall 1 to the recessed suction and wall 2 to flush with the face of the suction dogleg	1
Add Dogleg in Comp #2 for Recessed Suction in Face of A/A	1
COMPARTMENT #4 - STREETSIDE AFT	
CM, Compartment #4, Full Height, Dual Depth, Citimedic - Full height backboard storage on the #4 compartment door. - The upper section is 8" D due to dogleg for interior cabinetry. Bottom section is 15" deep. Floor drop of 4" for the entire compartment	1
CM, Compartment #4, Bracket, Backboard Mount on Door Diamond plate "C-style boxes mounted to the door of Comp #4 one at top and bottom to allow backboards or scoop stretcher to be slid in from the outboard side.	1
COMPARTMENT #6 - CURBSIDE AFT	
CM, Compartment #6, Spare Tire, With special Drop pan for spare tire. Do NOT install spare tire bracket.	1
CM, Compartment #6, Shelf, Custom, Adjustable, First Shelf wall #1 to #3 mid height	1

DESCRIPTION	QTY
COMPARTMENT #8 - CURBSIDE UPPER FORWARD	
CM, Compartment #8/8.5, Single Door, Type 1 Single door with inside /outside access, upper area. Outside access only to lower area. Battery storage, under hood.	1
CM, Compartment #8, Shelf, Adjustable, First Shelf RF Comp "8"/cabinet "U8" area - centered top to bottom.	1
INTERIOR TRIM AND FEATURES	
CM, Interior Cabinets, Duralite Construction, Wood	1
INTERIOR ADJUSTABLE SHELVES	
CM, Cabinet Shelf, Interior, Wood, Additional, Adjustable in U4	1
HEADLINER	
CM, Headliner, Flat, PVC, Hinged trough cover	1
FLOORING	
CM, Flooring, Lonplate II, Gunpowder Gray #424TX	1
CM, Flooring, Roll up, 3-4" Approx....., No Toe Kick	1
The roll up is not recessed it is installed on the cabinet wall and Squad bench.	
CM, Floor, Thresholds, .063 Aluminum, Painted w/Black Poly-urea coating	1
GRAB RAILS	
Rear Entry Door Grab Handles	
CM, Entry Door Grab Handles (3), Custom "L" Shape, 1", Yellow Yellow Powder Coat Finish	1
Ceiling Grab Rail - Center	
CM, Ceiling Grab Rail, Overhead, 84", 1" Diameter Handicap Style, Yellow Yellow Powder Coat Finish	1
IV FLUID HANGERS	
CM, IV Hangers, Perko (1), W/Straps Each	2
(1) CS wall up high centered between seats (1) SS Forward of U3.5	
CABINET DOORS	
Interior Street side #3 - CPR Seat	
SEAT BELTS/ SAFETY NETS	
CM, Safety Net, Head of Squad Bench, 2" Straps, Yellow attached to floor at head of squad bench, CS wall and overhead liner with removable latches.	1
CURBSIDE REAR	
CM, Cabinet, Curbside Rear, In Rear wall, U6,C6 Gray OHO doors, w/two shelves	1
(1) adjustable shelf in cabinet U6 (1) adjustable shelf in cabinet C6	
BIOHAZARD-	
CM, Glove Butler-Cabinet, (3), Above C/S door	1
CURBSIDE RIGHT STACK STORAGE #8	
CM, RF ALS, Split Upper/Lower, HVAC at Top	1
ATTENDANT SEAT	
CM, Attendant's Seat, EVS 1880, Comfort, Hi-Back Child Safety w/Per4Max	1
INTERIOR COLORS	
CM, Mica, Dove Gray (Matte)	1
UPHOLSTERY	

DESCRIPTION	QTY
CM, Upholstery, Seamless, Gunmetal MISC. INTERIOR OPTIONS	1
CM, Marine Hasp, for Padlock Installed on U-1 cabinet	1
CABINET KICK PANELS	
CM, Kick plate, Brushed SS, Face of S/B & Base wall, 148 CM CABINET LATCHES- INTERIOR 06 - ELECTRICAL GENERAL	1
CM, 12V Electrical system, RelayPlex system Flash Pattern- Quad Flash 75 - Per KKK	1
CM, Camera, Hanscom Kit, HK 7211 W/ IR250 Camera, Patient Compartment Hanscom kit HK 7211. Mount monitor to the left of the steering wheel. Bracket Part #10130864 In the module mount the camera on the headliner next to the to the curbside of the hinged trough. Trigger camera display on with Master Switch. #HC IR250 rear back up camera with #HC20M video cable, Mount camera exterior on rear of module, off center toward driver's side between rear load and center amber. Triggered when units placed in reverse gear.	1
COMMUNICATION	
CM, Coax Cable, RG58/U, Each, Terminate: CS Dome #2 to behind pass seat with 6' pigtails S/S Dome #4 to behind the drivers seat with 6' pigtails S/S Dome #5 to behind the pass seat with 6' pigtails	3
CM, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.	1
POWER SOURCES	
CM, Power Source, 12VDC, 20A, Ignition/Shoreline Hot 20amp 12 volt DC circuit routed to two locations, (1) pre-wire coil and tagged in action area and (1) pre-wire coil and tagged behind driver's seat.	1
CM, Power Source, 12 VDC, 15 Amp (+-), Std Model only - Ignition hot, terminating in cab console - with 6 foot tails (hot and ground).	1
CM, Power Source, 12VDC, 40A, Constant Hot (1)Install a 40Amp Power and ground wired CONSTANT hot to a Buss bar inside the center console (1)Install a 40Amp Power and ground wired IGNITION hot to a Buss bar inside the center console	2
CM, Buss Bar Assembly (+/-), 5 Position, (1) Power and (1) Ground Location: Center console	2
VOLTMETER	
CM, Voltmeter, Smart with Alarm, Audio/Visual With additional light on Cab Console for visual alarm.	1
12VDC OUTLETS	

DESCRIPTION	QTY
CM, Power Outlet, Power Point Style, (2), (1) Action Area (1) RF ALS Cabinet on standard 20-amp ignition hot circuit. - (1) outlet in action area - (1) in RF Cabinet "U8", wall #2, upper right	1
CM, Power Outlet, Power Point Style, Each Ignition Hot (1) At foot of squad bench just above 110v outlet. Approx 3" over from the edge cabinet C6. (1) in RF Cabinet L8, wall #2, upper right	2
CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel (1) Located in the cab switch panel passenger side. (1) located top left of console face. (1) located top right of console face. - Ignition Hot	3
CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel, Addition	1
ATTENDANT CONTROL PANEL	
CM, Action Area Switch Panel, Eaton Esport switches, Relocate CS Wall	1
POWER DISTRIBUTION	
SIREN ELECTRONIC - CONTROL HEADS / AMPS	
CM, Siren Electronic, Whelen, WS-295-SLSA1, California Title 13 Compliant	1
CM, Switch, Siren/Horn Thru Horn Ring	1
BACK-UP ALARMS	
CM, Back-Up Alarm, No Cutoff Switch	1
CM, Switch, Emergency Master	1
One Emergency Master Switch to turn all warning lights on.	
CM, Beacon Prewire, Ignition Hot to Rearmost Streetside dome	1
No switch Module roof, centered 16" inboard from rear of module, Beacon will be on anytime Ignition is on and unit is in gear.	
WARNING LIGHT FLASHERS	
RelayPlex Flash Pattern- Quad Flash 75 - Per KKK	
CM, Brake Override Circuit	1
For rear lights below upper outer corner.	
WARNING LIGHTS	
LED Series - 900 (Flange Separate)	
CM, Light, Whelen 900 LED, Red, Clear Lens, 90RR5SCR, External Flasher	12
MODULE SIDES LIGHTING	
Street side Body - Upper Forward	
Street side Body - Upper Rear	
Curbside Body - Upper Forward	
Curbside Body - Upper Rear	
Pri/Sec flashed thru relayplex quad flash 75	
MODULE REAR LIGHTING	
Rear Body - Upper Street side Corner	
Rear Body - Upper Curbside Corner	
Pri/Sec flashed thru relayplex quad flash 75	
FRONT UPPER BODY LIGHTING	
Front Body - Upper Curbside Outer Angled portion of	

DESCRIPTION	QTY
Coolbar	
Front Body - Upper Curbside Inner on Coolbar	
Front Body - Upper Street side Inner on Coolbar	
Front Body - Upper Street side Outer Angled portion of Coolbar	
Pri only flashed thru relayplex quad flash 75	
MODULE REAR LIGHTING	
(2) Rear just below upper outer lights.	
Pri/Sec flashed thru relayplex quad flash 75	
W/Brake override	
CM, Light, Whelen 900 LED, Amber, Clear Lens, 90AA5SCR, External Flasher	1
MODULE REAR LIGHTING	
Rear Body - Upper Center	
Pri/Sec flashed thru relayplex quad flash 75	
CM, Light, Whelen 900 LED, Clear, 90CC5SCR, External Flasher	1
FRONT UPPER BODY LIGHTING	
Front Body - Upper Center on Coolbar	
Pri Only flashed thru relayplex quad flash 75	
CM, Flange, Super 900 LED, #90FLANGC	14
LED Series - 700 (Flange Separate)	
CM, Light, Whelen 700 LED, Red, Clear Lens, 70R02SCR	8
FRONT UPPER BODY LIGHTING	
(2) Front Body - Upper Curbside Corner stacked	
(2) Front Body - Upper Street side Corner stacked	
Pri/Sec flashed thru relayplex quad flash 75	
FRONT FENDER INTERSECTION LIGHTING	
Front Fender Warning - Intersectors - LH Side	
Front Fender Warning - Intersectors - RH Side	
Pri only flashed thru relayplex quad flash 75	
REAR WHEEL WELL INTERSECTION LIGHTING	
Rear wheel well Warning - Intersectors - LH Side	
Rear wheel well Warning - Intersectors - RH Side	
Pri/Sec flashed thru relayplex quad flash 75	
CM, Flange, Whelen, Chrome, 700 Series Light (1)	8
For 7 Series Lights	
WHELEN LINZ6	
EXTERIOR AUTOMOTIVE LIGHTING	
CM, Taillight Pkg, Whelen, LED Stop/Tail, Turn & LED Backup, w/WC logo	1
- Brake- Steady Burn	
- Turn Arrow – sequential arrow	
- 700 LED Backup	
Clear lens over all three lights	
ICC/MARKER LIGHTS	
CM, Clearance Lights, Red, LED	3
(3) On rear as clearance lights.	
CM, Light, Clearance, Amber LED	3
(3) On Front of module as clearance lights.	

DESCRIPTION	QTY
CM, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers - High intensity flashers;Primary/Secondary- As marker lights with headlights	1
FLOOD AND LOAD SYSTEMS	
CM, Light, LED, Whelen, Clear, #9SC0ENZR, 24 LED, (1) w/ Chrm Flange, Steady Bur (2) each side as scene lights (2) on rear as load lights	6
CM, Scene Lights, C/S, Activated with C/S Door Master Hot.	1
11 - INTERIOR LIGHTING	
CM, Dome Lights, LED, Whelen,White Flange,(3)S/S,(3)C/S, CM+ Three (3) street side in liner and three (3) curbside in liner equally spaced Each side controlled by separate switch in action area standard. High/Off/Low	1
NOTE: NO VISABLE FASTENERS OR HOLES.	
CM, Timer, Momentary Switch, 15 Minute, Constant Hot Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to street side dome lights in liner on high.	1
SPOTLIGHTS / HANDHELD LIGHTS	
CM, Handheld Spotlight, Novatech, Nighthawk 2000, 100,000 CP	1
ATTENDANT LIGHT	
CM, Light, Intertek ZY-PIR38 12v, 15" LED, In A/A	1
SHORELINE INLET	
CM, Super Auto Eject, 20A, White Cover above comp "#2"	1
OUTLETS - 125VAC	
CM, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet in the RF Cabinet "U8", wall #2, upper right	1
CM, Outlet, 125 VAC, Duplex, Additional, Each (1) Interior CS above foot end of squad bench mounted approx. 14" up and over 3" from cabinet C6. (1) telemetry area, wall 2 near wall 1, mid height	2
BLOCKHEATERS	
INVERTER - 125VAC	
CM, Inverter/Charger, Vanner LifeSine Mounted in compt. #2 on the ceiling	1
AUXILIARY ENVIRONMENTAL SYSTEMS	
CM, Exhaust Fan, Single 12V Blower with "clamshell" vent on exterior forward of #4	1
CM, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo	1
COT MOUNTING PROVISIONS	
Safety Hooks	
CM, Cot Mount, Stryker, Rear Safety Hook Installed Ship loose with unit	1
Cot Mounts	

DESCRIPTION	QTY
CM, Stryker Performance/Power Load, Add Floor Structure Plates & Wiring for Futu Additional floor structure for future installation of a Stryker Power Load or Performance Load w/ inductive charging System.	1
OXYGEN AND AIR SYSTEMS	
CM, O2 Cylinder Wrench, Tethered in oxygen compartment.	1
CM, Rack, Multiversal, Zico #QR-MV, W/ Straps Set up for M cylinder	1
CM, Manual, O2 System	1
CM, O2 System, Ohio Style, (2 AA, 1 Vac Diss, 1 Liner, 1 C/S) Ohio style outlets (2) oxygen outlets in action area (1) vacuum Diss outlet in action area (1) oxygen outlet in liner at head of cot (1) oxygen outlet curbside wall at head of squad bench	1
CM, Lexan Flap, w/Hinge	1
SUCTION SYSTEM	
CM, Suction Pump, SSCOR 90206 mounted in compartment "2"	1
CM, Suction Holder, SSCOR 23002 with w/Canister Clip & Regulator See oxygen system for type of fitting used for container	1
WC, Suction Outlet and Container located in Action area recess Suction container in recess in cabinet recess in wall below action area countertop.	1
PAINT AND FINISH	
WC, Wheeled Coach Paint Process	1
RM & CM, Module Paint, Single Color, OEM White Ford White: PPG Code - FBCH978045	1
	1
	1
	1
	1