



QUOTATION

North Eastern Rescue Vehicles, Inc.
Bob Reilly

North Eastern Rescue Vehicles, Inc.
Bob Reilly

WO#: 684247

Page 1

DESCRIPTION	QTY
WARRANTY	
WC, Warranty, Conversion, 12 Month	1
WC, Warranty, Paint, 60 month Prorated, Standard	1
WC, Warranty, Structural, 20 Years, Std., Mods	1
WC, Warranty, Limited Electrical	1
WC, Warranty, Cabinet Construction	1
CERTIFICATIONS REQUIRED	
< This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.	1
< WC, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	1
All cabinets shall be labeled as to their capacity Rating.	
01- CHASSIS REQUIREMENTS	
FORD CHASSIS	
S < > CM, 2026 Ford E350, 7.3L, Gasoline,Cutaway, 138"WB Auto throttle OEM Ford (1) OEM Alternator Includes 2nd battery OEM Cab Headliner Vinyl	1
Domestic Chassis	1
SUSPENSION	
Rear Suspension, OEM Springs	1
HIGH IDLE	
High Idle Controls, OEM	1
FRONT END ALIGNMENT	
Front End Alignment, None- QC Check -Standard	1
OUTSIDE REAR VIEW MIRRORS	
Mirrors, Sail Mount, OEM Mirrors	1
WHEEL COVERS	
< CM, Wheel Covers, Phoenix #NF12, Installed,E-Series with Air Max Valve Extenders	1

DESCRIPTION	QTY
BASE CONVERSION	
CM, Conversion, Type 3, 148 Module, Ford - 23-1	1
CAB EXTENSION	
< CM, 8" Cab Extension, Ford, CitiMedic E350 Cab Extension to utilize same flooring as Module floor.	1
MODULE BODIES:	
CM, Interior Headroom, 68 Inches	1
< CM, Module, Type 3, 148" Body Length, 90" wide, Duraseam Doors, Cutaway 148" L x 90" W	1
< CM, Aisle Space, 49", CityMedic Plus (48-49" actual)	1
03 - MODULE EXTERIOR	
EXTERIOR MODULE CONSTRUCTION	
> CM, Stone Guard, Front, Diamond Plate, Type 3, Standard Height	1
FUEL FILLS & SPLASH PLATE	
CM, Housing Fuel Fill, Cast, Type III	1
REAR KICKPLATE	
CM, Rear Kick plate, Under-Ride Bumper, w/ Tag recess, No lights, CM+	1
SUB-FLOOR SYSTEM	
CM, Flooring, 3/4" Marine Grade Plywood, Type 3/7/9	1
MODULE ENTRANCE	
MODULE DOORS, HANDLES & HOLD OPENS	
< CM, Duraseam Hinged Doors with Hidden Jambs - Magnetic door switches	1
< > CM, Hold Open Rear Entry Doors, (2) 6" Door Grabber - Installed so doors will open as wide as possible - Mount at Bottom of doors.	1
CM, Hold Open, Gas Strut, Curb Side Entry Door, 35#	1
< CM, Patient Entry Door Handles, Trimark Black/Chrome Pull Handle w/"Push Button" With Round Push button Emergency release top and bottom of interior door panels.	1
> CM, Rear Entry Door Trailing Latch, Side release Paddle	1
> CM, Electrical Feed to Required Doors, Spring Protector (Per Door)	7
POWER DOOR LOCKS	
< > CM, Power Door Locks, All Module doors (except Batt) Access Doors and Module Compartment doors (except Battery) for electric locks, wiring to CS wall for Switch.	1
< CM, Switch, Stealth, for Power Door Locks In grille on passenger's side	1
< > CM, Switch, 12VDC, (3) Position Rocker, For Power Door Locks, Additional (1) Right rear entry door, interior lower panel, in top left corner. For power door locks.	1

DESCRIPTION	QTY
> CM, Relay Control Circuit, Power Door Locks	1
> CM, Circuit, OEM Door Lock to activate Mod Doors (Not Dodge)	1
ENTRY DOOR INNER PANELS	
< > CM, Entry Door Panels, Upper/Lower, S/S - Durasafe Design	1
> CM, Blue/White Center Chevron, w/WC Logo	1
SIDE DOOR STEP	
CM, Side Entry Step Well, Type III, Aluminum Diamond Plate	1
CM, Light, Side Entry Step well, LED, 2", Whelen #TOCACCCR	1
WINDOWS	
< CM, Window, Upper, CS/Slider, Rr/Fixed, Privacy Tint, PAN Curbside window with lower slider section Rear windows fixed Privacy Tint	1
REAR BUMPER AND REAR STEP CONSTRUCTION	
< CM, Rear Bumper, Ford Cutaway, w/ holes for 2" LED Lights with Gator Grip on flip up step. holes in sides of bumper for 2" marker light	1
CM, BLACK Polyurethane Coating, Rear Bumper Supports	1
INSULATION	
< > CM, Insulation, Walls and Ceiling, R11 Fiberglass Batt There shall be double bubble insulation in the entry and compartment doors.	1
RUB RAIL AND FENDER RINGS	
CM, Rub Rails, Skirt Line, Extruded "C" channel (E-one Style), 148"	1
CM, Tape, Reflective, White, For Extruded Skirt rails	1
CM, Fender Flare, Black Rubber	1
SPLASH GUARDS AND RUNNING BOARDS	
CM, Mud Flaps, Rear, w/ Wheeled Coach Logo	1
CM, Running Boards, Ford Cutaway, w/Gator Grip,	1
CAB TO MODULE ACCESS	
< CM, Bulkhead Cabinet, Type 3, walk-thru w/8" Cab extension - with 8" extended cab area - With walk thru door	1
< CM, Bulkhead, Door, Sliding w/Sliding Window with sliding Lexan window	1
LICENSE PLATE HOLDER	
< CM, License Plate Holder, Cast LP0002, for Under ride Bumper in rear kick plate, centered License holder comes with (2) LED lights.	1
EXTERIOR COMPARTMENT CONSTRUCTION	
< CM, Compartments, Floor Drop Down Compartment #2 - 2.5" drop Compartment #4 - 4" drop	3

DESCRIPTION	QTY
<p>Compartment #6 (5.5" for spare tire) Drop down floors to have drain hole standard.</p>	
<p>< CM, Compartments, Sweep out Compartments #1 & #8.5 are standard sweep out</p>	2
<p>< CM, Door Sill Protector, Stainless, All Comps Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage</p>	1
<p>< > CM, Compartments, Diamond Plate Finish Per Comp Machine stamped louvers located above the floor line for venting. Comp #1, 2, 4, and 6</p>	4
<p>> CM, Exterior Battery Compartment, Diamond Plate Finish EXTERIOR COMPARTMENT DOORS</p>	1
<p>> CM, Compartment Comp Handle, Trimark, Oval Pull Handle, Black/Chrome COMPARTMENT DOOR HOLD OPEN</p>	6
<p>< CM, Hold Open, Gas Strut, Ext Comp, 30lb. Compartments "#6", "#1", & "#2"</p>	3
<p>< CM, Hold Open, Gas Strut, Comp Door Only, 110 Degree, 30lb, Comp #4 to allow easier access to the Stair chair.</p>	1
<p>< CM, Hold Open, Gas Strut, RF Comp, 30lb #8</p>	1
<p>COMPARTMENT LIGHTING</p>	
<p>< CM, Oxygen Light, 3" Surface mount Whelen LED, Clear Mounted in Oxygen Compartment per eng design</p>	1
<p>< CM, Compartment Light, 4" Optronic,#BUL43-CBK, LED, Each Compartment</p> <p>1 - Access Panel Wall 1 2 - Wall #1 4 - Ceiling 6 - Wall #3 8- Wall #3 in access panel</p>	6
<p>COMPARTMENT #1 - STREETSIDE FWD</p>	
<p>CM, Compartment #1, 3/4 High, CitiMedic.</p>	1
<p>COMPARTMENT #2 - STREETSIDE FWD WHEELWELL</p>	
<p>< CM, Compartment #2, Citimedic , Type 3 Mount the inverter on the ceiling of compartment.</p>	1
<p>< CM, Compartment #2, Shelf, ADP, Fixed for Electrical storage Screw in shelf that extends from wall 1 to the recessed suction and wall 2 to flush with the face of the suction dogleg</p>	1
<p>COMPARTMENT #4 - STREETSIDE AFT</p>	
<p>< CM, Compartment #4, Full Height, Dual Depth, Citimedic - Full height backboard storage on the #4 compartment door.</p>	1

DESCRIPTION	QTY
<p>- The upper section is 8" D due to dogleg for interior cabinetry. Bottom section is 15" deep.</p>	
<p>Floor drop of 4" for the entire compartment</p>	
<p>< CM, Compartment #4, Strap, Seat Belt Style, Each (1) on comp #4 door for Backboards (1) from wall #1 to Wall #3 about 6" from wall 2 for the Stair chair.</p>	2
<p>< CM, Compartment #4, Bracket, Backboard Mount on Door Diamond plate "C-style boxes mounted to the door of Comp #4 one at top and bottom to allow backboards or scoop stretcher to be slid in from the outboard side.</p>	1
<p style="text-align: center;">COMPARTMENT #6 - CURBSIDE AFT</p>	
<p>< CM, Compartment #6, Spare Tire, With special Drop pan for spare tire. Do NOT install spare tire bracket.</p>	1
<p>< CM, Compartment #6, Shelf, Custom, Adjustable, First Shelf wall#1 to wall#3 Mid height</p>	1
<p style="text-align: center;">COMPARTMENT #8 - CURBSIDE UPPER FORWARD</p>	
<p>< CM, Compartment #8/8.5, Split Doors, 8" Cab Extension, Upper compartment, with inside /outside access Lower compartment for (2) battery</p>	1
<p>< CM, Compartment #8, Shelf, Adjustable, First Shelf RF Comp "8"/cabinet "U8" area - centered top to bottom.</p>	1
<p>< CM, Compartment #8, Shelf, Additional, Adjustable, Each RF Comp "8"/cabinet "L8" area centered top to bottom.</p>	1
<p style="text-align: center;">INTERIOR TRIM AND FEATURES</p>	
<p>> CM, Interior Cabinets, Duralite Construction, Wood < > CM, Cabinet Shelf, Interior, Wood, Adjustable, First shelf Cabinets U4, U6, C6</p>	1 3
<p>< CM, Cabinet Shelf, Interior, Wood, Additional, Adjustable Cabinet U4 (2 total)</p>	1
<p style="text-align: center;">HEADLINER</p>	
<p>> CM, Headliner, Flat, PVC, Hinged trough cover, Std</p>	1
<p style="text-align: center;">FLOORING</p>	
<p>CM, Flooring, Lonplate II, Gunpowder Gray #424TX</p>	1
<p>< > CM, Flooring, Roll up, 3-4" Approx....., No Toe Kick The roll up is not recessed it is installed on the cabinet wall and Squad bench.</p>	1
<p>CM, Floor, Thresholds, .063 Aluminum, Painted w/Black Poly-urea coating</p>	1

DESCRIPTION	QTY
GRAB RAILS	
Rear Entry Door Grab Handles	
< CM, Entry Door Grab Handles (3), Custom "L" Shape, 1", Yellow Yellow Powder Coat Finish	1
Ceiling Grab Rail - Center	
< CM, Ceiling Grab Rail, Overhead, 84", 1" Diameter Handicap Style, Yellow Yellow Powder Coat Finish	1
IV FLUID HANGERS	
< CM, IV Hangers, Perko (1), W/Straps Each (1) CS wall up high centered between seats (1) SS Forward of U3.5	2
BASEWALL CABINET:	
< > CM, Cabinet, Base wall, 8" ext, CPR Seat, w/Telemetry Area, Recessed suction Telemetry area to have poured black surface. Cabinet L3.5	1
< CM, Cabinet, Street side Upper, 148 Module, w/CPR Seat , 68" HR Cabinet U2, U1 wood door	1
< CM, Street side rear, with side seat, 68" HR Cabinet U4 with (2) adjustable shelves Cabinet U3.5	1
CM, Tray, A/A, Std Aisle No Bio waste, Poured, Black	1
CABINET DOORS	
< > CM, Door, U1 Hinged Wood U1 cabinet will be used as a locking drug cabinet.	1
CM, Door, U2 Gray Polycarbonate Slider, CN 10 Compliant	1
Interior Street side #3 - CPR Seat	
CM, CPR side seat, Fixed Backrest	1
CM, CPR, Lid, Hinged Flip Up With Trimark Latch	1
CM, Door, U3.5, OHO Top Hinged Gray Polycarbonate (CWTG) CN 10 Complia CWTG = with gas strut	1
CM, Door, L3.5, OHO Bottom Hinged Gray Polycarbonate, (CWBD) CN 10 Comp	1
CM, Door, U4, OHO Dual Hinged Gray Polycarbonate (CWDX) CN 10 Compliant	1
CM, CPR Seat, "U" Barrier Bar, Padded, 1.5" SS, Gunmetal Mounted Approx. 12" from the center of the seat to the side of the barrier bar.	1
CM, Telemetry Tray, Poured, Black	1
SQUAD BENCH AREA	
< > CM, Cabinet, Squad Bench, CM+, w/ Bio waste With Bio waste at the head of the squad bench cabinet.	1

DESCRIPTION	QTY
CM, Lid, Squad Bench, Single W/Bio-Waste Lift up lid ONLY over storage area	1
CM, Squad Bench, Handle, Trimark CM, Strut, Gas, 30 LB, Installed CPR Side seat Squad Bench	1 2
CM, CPR, Handle, Trimark CM, Bio-waste Cover, Etched Red Plastic	1 1
SEAT BELTS/ SAFETY NETS	
CM, CPR Seat, Seatbelt, Assy, (4 Point), Per4Max, Yellow, (1) Each, CN-8 Above the lid	1
< > CM, Squad Bench, Seatbelt, Assy, (4 Point) Per4Max, Yellow, (2) Each Above the lid On squad bench	1
CM, Patient Restraint Belts, Squad Bench (3)	1
< CM, Safety Net, Head of Squad Bench, 2" Straps, Yellow attached to floor at head of squad bench, CS wall and overhead liner with removable latches.	1
CURBSIDE REAR	
< CM, Cabinet, Curbside Rear, In Rear wall, U6,C6 Gray OHO doors, w/two shelves (1) adjustable shelf in cabinet U6 (1) adjustable shelf in cabinet C6	1
BIOHAZARD-	
> CM, Glove Butler-Cabinet, (3),Above C/S door	1
CURBSIDE RIGHT STACK STORAGE #8	
< CM, RF ALS, Split Upper/Lower, HVAC at Top Upper Cabinet U8 Lower Cabinet L8	1
Cabinet - Upper Right Stack U8	
CM, Doors, RF, U8, Dual Gen III OHO, Polycarbonate Doors, Gray	1
CM, Doors, RF, L8, Dual Gen III OHO, Polycarbonate Doors, Gray	1
ATTENDANT SEAT	
CM, Attendant's Seat, EVS 1880,Comfort, Hi-Back Child Safety w/Per4Max	1
> CM, Color, Gunmetal, Per4Max Belt, Yellow	1
> CM, Door, Diamond Plate, EVS Seat Base, M1 Latch	1
< > CM, Attendant's Seat Base, EVS CBS Box Style Box opening to be toward CURBSIDE access door	1
INTERIOR COLORS	
CM, Mica, Dove Gray (Matte)	1
UPHOLSTERY	
CM, Upholstery, Seamless, Gunmetal	1
> CM, Backrest Cushion, EVS, Gunmetal, w/ WC Logo, Each	3
MISC. INTERIOR OPTIONS	
< > CM, Marine Hasp, for Padlock Installed on U-1 cabinet	1

DESCRIPTION		QTY
CABINET KICK PANELS		
	CM, Kick plate, Brushed SS, Face of S/B & Base wall, 148 CM	1
CABINET LATCHES- INTERIOR		
< >	CM, Latch, M1, 3/4" Material, 2" round, Non Locking, Chrome-CN 10 Certified (1) Sharps/Waste (1) U1 with HASP (3) Bulkhead	5
< >	CM, Latch, Southco M1, 2" S/S, (1/4" Door) Locking, CN 10-Rated 10lb (self latching) Flush Mount. Non-Locking Attendant seat base door	1
< >	CM, Latch, Southco M1, 2" S/S, (3/8" Door) Non-Locking, CN 10-Rated 10lb (self latching) Flush Mount. Non-Locking Glove Caddy	1
06 - ELECTRICAL GENERAL		
<	CM, 12V Electrical system, RelayPlex system Flash Pattern- Quad Flash 75 - Per KKK	1
CAMERAS		
U <	Camera, Patient Compartment and Back Up	1
	Camera, Patient Compartment SAP#10495001Hanscom kit HK 7211. Mount monitor to the left of the steering wheel. Bracket Part #10130864 In the module mount the camera on the headliner next to the StreetSide cabinets. Trigger camera display on with Master Switch. #HC IR250 rear back up camera with #HC20M video cable, Mount camera exterior on rear of module, off center toward driver's side. Triggered when units placed in reverse gear. See reference picture on file	
COMMUNICATION		
<	CM, Coax Cable, RG58/U, Each, Terminate: CS Dome #2 to behind pass seat with 6' pigtails S/Side From Dome #4 to behind the drivers seat with 6' pigtails S/Side From Dome #5 to behind the pass seat with 6' pigtails	3
<	CM, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.	1
POWER SOURCES		

DESCRIPTION	QTY	ID	REF. NO
< CM, Power Source, 12VDC, 20A, Ignition/Shoreline Hot (1) pre-wire coil and tagged in action area (1) pre-wire coil and tagged behind driver's seat.	1		
< CM, Power Source, 12 VDC, 20 Amp (+-), Constant Hot Termination: (1) in Action Area (1) in cab console	2		
< CM, Power Source, 12 VDC, 30 Amp (+-), Ignition Hot (2) Behind Passenger seat with 6 ft coiled wire	2		
< CM, Power Source, 12VDC, 40A, Constant Hot (1) Install a 40Amp Power and ground wired CONSTANT hot to a Buss bar inside the center console (1) Install a 40Amp Power and ground wired IGNITION hot to a Buss bar inside the center console	2		
< > CM, Buss Bar Assembly (+/-), 5 Position, (1) Power and (1) Ground Location: Front chassis cab console	2		
VOLTMETER			
< CM, Alarm, Low Voltage, Audio/Visual Light in cab console and Buzzer in cab.	1		
BATTERY SYSTEM			
< CM, Battery Switch, RelayPlex Electronic w/5 min Timer, Ford T3, Gasoline - Activated thru OEM ignition switch, timer function upon ignition "off". - Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer. - ONLY Module power is turned on/off. - Chassis power is NOT turned off.	1		
12VDC OUTLETS			
< CM, Power Outlet, Power Point Style, (2), (1) Action Area (1) RF ALS Cabinet on standard 20-amp ignition hot circuit. - (1) outlet in action area - (1) in RF Cabinet "U8", wall #2, upper right	1		
< > CM, Power Outlet, Power Point Style, Each Ignition Hot (1) At foot of squad bench just above 110v outlet. Approx 3" over from the edge cabinet C6. (1) in RF Cabinet L8, wall #2, upper right (1) Constant power: Located on the aisle side bottom of circuit board cabinet in crawl-thru area.	3		
< CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel	3		

DESCRIPTION	QTY
<p>Ignition Hot (1) Located in the cab switch panel passenger side. (1) located top left of console face. (1) located top right of console face.</p>	
<p>< > CM, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel, Addition Location in the Action area outlet panel.-Ign Hot</p>	1
FRONT CONSOLE	
<p>< CM, Console, Drivers Switch & Radio, Center, Aluminum, Black, Ford cutaway Black polyurethane coated .090 Aluminum Configuration 1</p>	1
<p>> CM, Single Blank Panel</p>	1
<p>> CM, 9" deep Glove Box Panel</p>	1
<p>> CM, Cup Holder Panel (No Handle Notch)</p>	1
<p>WC, Flat Switch Panel</p>	1
ATTENDANT CONTROL PANEL	
<p>CM, Action Area Switch Panel, Eaton Esport switches, Relocate CS Wall</p>	1
POWER DISTRIBUTION	
SIREN ELECTRONIC - CONTROL HEADS / AMPS	
<p>CM, Siren Electronic, Whelen, WS-295-SLSA1, California Title 13 Compliant</p>	1
SIREN SPEAKERS	
<p>CM, Speakers, (2), Cast, SAD4319/SAP4319, In Bumper, Ford Cutaway</p>	1
<p>CM, Switch, Siren/Horn Thru Horn Ring</p>	1
BACK-UP ALARMS	
<p>CM, Back-Up Alarm, No Cutoff Switch</p>	1
<p>< CM, Switch, Emergency Master One Emergency Master Switch to turn all warning lights on</p>	1
<p>< CM, Beacon Prewire, Ignition Hot to Rearmost Streetside dome No switch Module roof, centered 16" inboard from rear of module, Beacon will be on anytime Ignition is on and unit is in gear.</p>	1
WARNING LIGHT FLASHERS	
<p>< CM, Automatic Secondary, Park/Neutral, w/Momentary Switch, Auto Reset</p>	1
<p>When unit is placed into Park, Automatically defaults to cut off all "Primary Only" Defined lighting, the circuit would automatically reset when the gear shift lever is placed back into gear.</p>	
<p>There shall be an override switch to turn back on the "Primary Only" defined lighting.</p>	
<p>This removes the Primary and Secondary Buttons on Switches.</p>	
<p>< > CM, Circuit, Lights Alternating Pattern Alternating pattern. for a (7) light grouping across the front</p>	1

DESCRIPTION	QTY
<p>Passenger corner light will be Phase 1 Outboard light on Passenger side will be Phase 2P Inboard light on Passenger side will be Phase 1P Center light will be phase 2P Inboard light on Drivers side will be Phase 1P Outboard light on Drivers side will be Phase 2P Drivers side corner light will be phase 1</p> <p>Passenger upper grille light will be Phase 2P Drivers upper grille light will be Phase 1P</p> <p>Passenger lower grille light will be Phase 1P Drivers lower grille light will be Phase 2P</p> <p>Curbside Front intersection will be phase 2P Front upper corner will be Phase 1 Rear intersection will be Phase 1 Rear upper corner will be Phase 2</p> <p>Street side Front intersection will be phase 1P Front upper corner will be Phase 2 Rear intersection will be Phase 2 Rear upper corner will be Phase 1</p> <p>Rear Street side upper corner will be Phase 1 Center upper light shall be Phase 2 Curbside upper corner will be Phase 1</p> <p>Street side below upper outer corner will be Phase 2 Curbside below upper outer corner will be Phase 2</p> <p>NOTE: Hundred series lights must be set to steady burn and flashed thru RelayPlex</p>	
<p>< CM, Brake Override Circuit For rear lights below upper outer corner</p>	<p>1</p>
<p style="text-align: center;">WARNING LIGHTS</p> <p>> LED Series - 900 (Flange Separate)</p> <p>< > CM, Light, Whelen 900 LED, Red, Clear Lens, 90RR5SCR, External Flasher</p> <p>MODULE SIDES LIGHTING Street side Body - Upper Forward Street side Body - Upper Rear Curbside Body - Upper Forward Curbside Body - Upper Rear Pri/Sec flashed thru relayplex quad flash 75</p> <p>MODULE REAR LIGHTING Rear Body - Upper Street side Corner Rear Body - Upper Curbside Corner Pri/Sec flashed thru relayplex quad flash 75</p> <p>FRONT UPPER BODY LIGHTING Front Body - Upper Curbside Outer Angled portion of Coolbar Front Body - Upper Curbside Inner on Coolbar</p>	<p>12</p>

DESCRIPTION	QTY
<p>Front Body - Upper Street side Inner on Coolbar Front Body - Upper Street side Outer Angled portion of Coolbar Pri only flashed thru relayplex quad flash 75</p>	
<p>MODULE REAR LIGHTING (2) Rear just below upper outer lights. Pri/Sec flashed thru relayplex quad flash 75 W/Brake override</p>	
<p>< > CM, Light, Whelen 900 LED, Amber, Clear Lens, 90AA5SCR, External Flasher MODULE REAR LIGHTING Rear Body - Upper Center Pri/Sec flashed thru relayplex quad flash 75</p>	1
<p>< > CM, Light, Whelen 900 LED, Clear, 90CC5SCR, External Flasher FRONT UPPER BODY LIGHTING Front Body - Upper Center on Coolbar Pri Only flashed thru relayplex quad flash 75</p>	1
<p>CM, Flange, Super 900 LED, #90FLANGC > LED Series - 700 (Flange Separate)</p>	14
<p>< > CM, Light, Whelen 700 LED, Red, Clear Lens, 70R02SCR FRONT UPPER BODY LIGHTING (2) Front Body - Upper Curbside Corner stacked (2) Front Body - Upper Street side Corner stacked Pri/Sec flashed thru relayplex quad flash 75</p> <p>FRONT FENDER INTERSECTION LIGHTING Front Fender Warning - Intersectors - LH Side Front Fender Warning - Intersectors - RH Side Pri only flashed thru relayplex quad flash 75</p> <p>REAR WHEEL WELL INTERSECTION LIGHTING Rear wheel well Warning - Intersectors - LH Side Rear wheel well Warning - Intersectors - RH Side Pri/Sec flashed thru relayplex quad flash 75</p>	8
<p>WHELEN FLANGES 7 SERIES LIGHTS (Flange Separate)</p>	
<p>< CM, Flange, Whelen, Chrome, 700 Series Light (1) For 7 Series Lights</p>	8
<p>WARNING LIGHTS -WHELEN LIN3 (Flange Separat < > CM, Light, Whelen, LIN3, LED-Red, RSRO2ZCR w/Flg FRONT GRILL LIGHTING Grille - LH Upper Corner Grille - RH Upper Corner Grille - LH Lower Corner Grille - RH LowerCorner</p> <p>Pri only flashed thru relayplex quad flash 75 X-pattern Flash</p>	4
<p>CM, Flange, Whelen, Chrome, For LIN3, Each EXTERIOR AUTOMOTIVE LIGHTING</p>	4
<p>< CM, Taillight Pkg, Whelen, LED Stop/Tail, Turn & LED Backup, w/WC logo - Brake- Steady Burn</p>	1

DESCRIPTION	QTY
<p>- Turn Arrow – sequential arrow - 700 LED Backup Clear lens over all three lights</p>	
<p>ICC/MARKER LIGHTS</p>	
<p>< CM, Light, Red, 2", Marker, LED, Each in bumper</p>	2
<p>< CM, Clearance Lights, Red, LED (3) On rear as clearance lights.</p>	3
<p>< CM, Light, Clearance, Amber LED (3) On Front of module as clearance lights.</p>	3
<p>< CM, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers - High intensity flashers;Primary/Secondary- As marker lights with headlights</p>	1
<p>FLOOD AND LOAD SYSTEMS</p>	
<p>< CM, Light, LED, Whelen, Clear, #9SC0ENZR, 24 LED, (1) w/ Chrome Flange (2) each side as scene lights (2) on rear as load lights</p>	6
<p>< CM, Scene Lights, C/S, Activated with C/S Door Master Hot.</p>	1
<p>11 - INTERIOR LIGHTING</p>	
<p>< CM, Dome Lights, LED, Whelen,White Flange,(3)S/S,(3)C/S, CM+ Three (3) street side in liner and three (3) curbside in liner equally spaced</p>	1
<p>Each side controlled by separate switch in action area standard. High/Off/Low</p>	
<p>NOTE: NO VISABLE FASTENERS OR HOLES.</p>	
<p>< CM, Timer, Momentary Switch, 15 Minute, Constant Hot Mount switch on C/S wall at the head of the squad bench in the standard location. Switch to allow activation and also deactivation. Wire to street side dome lights in liner on high.</p>	1
<p>WC, No Lighting Recessed into Trough Cover</p>	1
<p>SPOTLIGHTS / HANDHELD LIGHTS</p>	
<p>CM, Handheld Spotlight, Novatech, Nighthawk 2000, 100,000 CP</p>	1
<p>ATTENDANT LIGHT</p>	
<p>CM, Light, Intertek ZY-PIR38 12v, 15" LED, In A/A</p>	1
<p>SHORELINE INLET</p>	
<p>< CM, Super Auto Eject, 20A, White Cover above comp "#2"</p>	1
<p>OUTLETS - 125VAC</p>	
<p>< CM, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet in the RF Cabinet "U8", wall #2, upper right.</p>	1

DESCRIPTION	QTY
<p>< > CM, Outlet, 125 VAC, Duplex, Additional, Each (1) Interior CS above foot end of squad bench mounted approx. 14" up and over 3" from cabinet C6.</p> <p>(1) telemetry area, wall 2 near wall 1, mid height</p> <p>(1) Located on the aisle side bottom of circuit board cabinet in walk-thru area.</p>	<p>3</p>
BLOCKHEATERS	
<p>< Block Heater - With OEM Plug This option does not include a switch.</p>	<p>1</p>
INVERTER - 125VAC	
<p>< > CM, Inverter/Charger, Vanner LifeSine Mounted on ceiling of comp#2</p>	<p>1</p>
AUXILIARY ENVIRONMENTAL SYSTEMS	
<p>< CM, Exhaust Fan, Single 12V Blower with "clamshell" vent on exterior forward of #4</p>	<p>1</p>
<p>CM, Generation I, Steel Cool Bar cover</p>	<p>1</p>
CITIMEDIC BRUSHLESS HVAC SYSTEM	
<p>< > CM, Heat/AC, F3, Combo, Brushless, w/Coolbar with thermostat in action area.</p>	<p>1</p>
<p>12vdc External Condenser, in Coolbar mounted on front of module. Ford White: PPG Code - FBCH978045</p>	
<p>CM, Thermostat, Master Control Digital CM5000, Brushless</p>	<p>1</p>
<p>Cover, Cool Bar, (5) 900 series lights, LED Lights</p>	<p>1</p>
<p>CM, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo</p>	<p>1</p>
<p>> WC, Heat/AC Located RF corner, over ALS cabinet.</p>	<p>1</p>
COT MOUNTING PROVISIONS	
Safety Hooks	
<p>< CM, Cot Mount, Stryker, Rear Safety Hook Installed Ship Loose</p>	<p>1</p>
Cot Mounts	
<p>< > CM, Stryker Performance/Power Load, Add Floor Structure Plates & Wiring for Futu Additional floor structure for future installation of a Stryker Performance Load w/ inductive charging System.</p>	<p>1</p>
<p>< CM, Cut Floor and Install Stryker Floor Plate, 6390-700-001A, for Performance For Performance Load Cot mounts.</p>	<p>1</p>
<p>Note: Stryker Deutsch connection to be coiled up on the interior of the module under attendant seat base</p>	
<p>CM, Power source for Induction Charging, 12V, 10 Amp constant hot</p>	<p>1</p>
<p>Center Mount</p>	<p>1</p>

DESCRIPTION	QTY
OXYGEN AND AIR SYSTEMS	
CM, O2 Cylinder Wrench, Tethered in oxygen compartment.	1
CM, Rack, Multiversal, Zico #QR-MV, W/ Straps Set up for M cylinder size	1
CM, Track, Unistrut for Oxygen Rack	1
CM, Manual, O2 System	1
CM, O2 Regulator, Preset 50PSI Ship Loose	1
CM, O2 System, Ohio Style, (2 AA, 1 Vac Diss, 1 Liner, 1 C/S) Ohio style outlets (2) oxygen outlets in action area (1) vacuum Diss Outlet in action area (1) oxygen outlet in liner at the chest of cot (1) oxygen outlet curbside wall at head of squad bench	1
CM, Lexan Flap, w/Hinge	1
SUCTION SYSTEM	
< CM, Suction Pump, SSCOR 90206 mounted in compartment "2"	1
< > CM, Suction Holder, SSCOR 23002 with w/Canister Clip & Regulator See oxygen system for type of fitting used for container	1
< > WC, Suction Outlet and Container located in Action area recess Suction container in recess in cabinet recess in wall below action area countertop.	1
MISC MEDICAL	
< CM, Fire Extinguisher, Additional, 5 LB. ABC, Ship Loose, Each HD Amerex Bracket #861H with Amerex 5LB fire extinguisher.	1
PAINT AND FINISH	
WC, Wheeled Coach Paint Process	1
< > RM & CM, Module Paint, Single Color, OEM White Ford White: PPG Code - FBCH978045	1
< > RM & CM, Cab Paint - Single Color, OEM White Ford White: PPG Code - FBCH978045	1
PAINT STRIPING DESIGN	
Paint Belt, None	1
	1
SHIP LOOSE ITEMS	
< CM, Bracket, Spare Tire Mounting, Ship Loose Indemnification Statement	1

DESCRIPTION	QTY		