



Specification Summary

Name	Specifications
Type I - MXP170DF	

Sales Options by Category

10-Base (BAS)

Name/Description	Quantity
TYPE I - MXP170DF TYPE I - MXP170DF	1.00
Type I - Pick up Type I - Pick up	1.00
New Configuration (4pts) New SAE J3026 configuration	1.00

11-Chassis (CH*)

Name/Description	Quantity
Conversion Ford F350/F450 Chassis Cab Conversion Ford F350/F450 Chassis Cab	1.00
Ford F550XLT Super Duty Diesel Chassis Cab 4X4 193 Ford F550 XLT Super Duty Chassis Cab 4 X 46,7L POWER STROKE V8 Diesel EngineWheelbase 193" (4902 mm)GVWR (Gross vehicle weight rating)19,500 Lbs /8,845 Kg	1.00
Regular chassis cab Regular chassis cab	1.00

12-Suspension (SUS)

Name/Description	Quantity
------------------	----------



LiquidSpring™ Suspension Type I	1.00
Compressible Liquid Adaptive Suspension System, is a smart suspension systems. Liquid-based struts and an on-board processor provide better handling and control, and a smoother, softer ride. The reduced vehicle vibration increases comfort.	

13-Module (MOD)

<i>Name/Description</i>	<i>Quantity</i>
MXP170DF Ambulance Module	1.00
Ambulance Module Structure / Door Structure and Accessories. (Included)	

14-Module Configuration (MCF)

<i>Name/Description</i>	<i>Quantity</i>
C1, Curbside Entry Door, with Opening Window	1.00
Side entry door on curbside (C1) for patient compartment access, with flush-mounted, automotive-style opening window.	
C2 Door, Cabinet Access and Battery Location	1.00
Second door on curbside (C2) for Side Cabinet access and battery slide out sealed compartment. (Included)	
C3 Door, Storage Exterior Compartment	1.00
Third door on curbside (C3) for backboard or other storage. (Included)	
Stair Chair Location, Two (2) Adjustable Shelves	1.00
Stair chair location with two (2) adjustable shelves and retaining safety belt for backboard in C3 compartment.	
Third door (C3) Compartment In/Out Access	1.00
Third door (C3) Compartment In/Out Access	
4"-Diameter Compartment Lights, LED	1.00
4"-diameter LED Compartment lights. With Side entry Door Steps.	
E Door, Electrical Exterior Compartment	1.00
Upper door (E) for electrical panel access. (Included)	
A1 and A2, Rear Entry Doors, with Defrost	1.00
Two (2) rear entry doors for patient compartment access, each with its individual exterior door handle. Includes frameless flush-mounted tinted windows and defrost feature.	
S1 Door, Main Oxygen Exterior Compartment	1.00
First door on streetside (S1) for main vertical oxygen cylinder. (Included)	
Full-Depth Shelf, One (1), Adjustable	1.00
One (1) full-depth, adjustable shelf in S2 compartment.	
Fire Extinguisher, ABC-Rated, 5 lbs, with Bracket	1.00
Fire extinguisher, 5 lbs, ABC-rated, with heavy duty bracket in S2 compartment.	
S2 Door, Storage Exterior Comp	1.00
Second door on streetside (S2) for equipment storage for MX/MXP170. (included)	
S3 Compartment, Equipment Storage, Full height	1.00
Third door on streetside (S3) for equipment storage.Full height compartment.	
Full-Depth Shelves, Three (3), Adjustable	1.00
Three (3) full-depth, adjustable shelves in S3 compartment.	

15-Lighting (LGT)

<i>Name/Description</i>	<i>Quantity</i>
Turn Signal Arrows, Amber (2), LED	1.00
Two (2) amber turn-signal arrows, installed on the front of the module. Whelen 600 series (6 x 4) LED lights.	
Turn Signal Lights, Amber (2), LED	1.00

Two (2) amber turn-signal lights, intermediate side mount. Whelen 700 series (7 x 3) LED lights.	
Third Upper Brake Light, LED	1.00
Third upper brake light at rear of module. Whelen 600 series (6 x 4) LED light.	
Mid-Height Lights: Arrow, Brake, Reverse	1.00
Two (2) amber arrows, two (2) red brake lights, and two (2) reverse lights at mid height. Whelen 600 series LED lights (6 x 4).	
Rear Step Plate: Brake and Reverse Light	1.00
Four (4) red brake/tail lights, and two (2) reverse lights installed in rear step plate. Round LED lights.	
Marker Lights, Amber (7) and Red (7), LED	1.00
Seven (7) front upper center and corner amber LED marker lights. Seven (7) rear upper center and corner red LED marker lights.	
Marker Lights, Two (2) rear mid-height red LED	1.00
Two (2) rear mid-height red LED marker lights.	

16-Emergency and Working Lights (EWL)

<i>Name/Description</i>	<i>Quantity</i>
Clear Lenses	1.00
Clear lenses.	
Chrome bezels	36.00
Chrome bezels	
Emergency Lights, (7) LED (900)	1.00
Seven (7) emergency lights installed on the front of the module. Whelen 900 series (7 x 9) LED lights. (Standard setup includes three (3) red, one (1) white, and three (3) red)	
Lights in Front Grille, (4) SERIES T, WIG WAG	1.00
Four (4) lights in front grille with Wig Wag flash pattern. T series LED lights. (Standard setup includes (2) red and (2) clear)	
Emergency Lights on Inside of Doors, Two (2) each	1.00
Two red emergency lights on each compartment and entry door inside panel. Total of sixteen (16) round LED lights.	
Intersection Lights, (2) LED (700)	1.00
Two (2) intersection lights with turning priority. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red/clear lighting)	
Emergency Lights, (2) LED, Inter. Side Mount (700)	1.00
Two (2) emergency lights, intermediate side mount. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red lighting)	
Four (4) LED lateral emergency lights (900)	1.00
Four (4) lateral emergency lights (two (2) on each side). Whelen 900 series (7 x 9) LED lights. (Standard setup contains red lighting)	
Scene Lights, Four (4), Clear LED, (900)	1.00
Four (4) lateral scene lights (two (2) on each side). Whelen 900 series (7 X 9) LED scene lights.	
Emergency Lights, (2) LED, Rear Corners (900)	1.00
Two (2) rear emergency lights at upper rear corners. Whelen 900 series (7 x 9) LED lights. (Standard setup contains red lighting)	
Emergency Lights, (2) LED (600)	1.00
Two (2) rear upper lights. Whelen 600 series (6 x 4) LED lights. (Standard setup contains amber lighting)	
Loading Lights, Two (2), LED (600)	1.00
Two (2) rear loading lights. Whelen 600 series (6 x 4) LED lights.	
Emergency Lights, (2) LED, Addt'l, Window Hgt (900)	1.00



Two (2) additional lights at window height. Whelen 900 series (7 x 9) LED lights.
(Standard setup contains red lighting)

17-Audible Warning System (WRN)

<i>Name/Description</i>	<i>Quantity</i>
Back-Up Alarm Back up alarm (97dB) with override switch. (Included)	1.00
Buell Emergency Air Horn Buell Dual Emergency Horns 10" and 12" Air Horns	1.00
Whelen Howler Low Frequency Tone Siren Whelen Howler is a add-on to any 100/200 watt siren amplifier. Uses low frequency tones to synchronize with the vehicles primary siren tones. Includes low frequency siren amplifier and speakers.	1.00
Whelen 295SLS Hands-Free Siren Whelen model 295HFSA1 siren amplifier with 17 Scan-Lock™ siren tones.	1.00
Switch to Mute OEM Horn when Siren Speakers Active Switch to mute the OEM horn when the siren speakers are activated.	1.00
Whelen SA315 Series Speakers Whelen SA315 series speakers is a compact speaker meeting SAE Class A requirements when paired with Whelen 100 watt siren amplifier.	1.00

18-Exterior Vehicle features (VFT)

<i>Name/Description</i>	<i>Quantity</i>
OEM exterior mirrors Keep OEM exterior mirrors	1.00
Module Rub Rails, Aluminum Aluminium rub rails on module sides. (Included)	1.00
Module Corner Protectors, Stainless-Steel Stainless-steel protectors on module corners. (Included)	1.00
Module Wheel Trims, Fiberglass Formed fiberglass wheel trimming on module.(Included)	1.00
Undercoating Protection Undercoating protection for module and chassis. (Included)	1.00
Rear Wheel Mud Guards Mud guards on module for rear wheels. (Included)	1.00
License Plate with Light Surface mounted license plate location with LED light.	1.00
Cab Steps, Anti-Skid Material with Mud Guards Anti-skid lateral steps. Includes mud guards for front wheels. (Included)	1.00
Rear Step Bumper, Retractable Center Section Anti-skid rear retractable step. Diamond plate corner bumper. Rubber bumperette. (Included)	1.00

19-Convenience (CNV)

<i>Name/Description</i>	<i>Quantity</i>
Valet Switch in Front Grille The door unlock valet switch is located on the back of the front grille, on the driver's side half portion of the grille. It allows to unlock all doors of the vehicle, but cannot lock the doors. (Included)	1.00
Demers Fast Idle	1.00

Demers fast idle is generated by the multiplex module, it allows fast charging of the batteries by the engine when specific conditions are met. (Included)

Black Back-Up Camera 1.00

RearView Safety standard back-up camera with build-in audio support and infra-red night vision.

Black Dome Interior Camera 1.00

RearView Safety dome interior camera with build-in audio support and 130 degree viewing angle.

7 inch Mirror Monitor 1.00

RearView Safety 7" backup digital LCD mirror monitor is a stand-alone monitor and cable kit that connects to camera(s) installed on your vehicle.

Anti-Theft System 1.00

The anti-theft allows leaving the vehicle without keys and the engine running to keep the vehicle at the ideal operating temperature. It protects against theft by turning off the engine if the vehicle moves.

ECOSMART Anti-Idling System 1.00

The ECOSMART Anti-Idling System automatically stops and restarts the engine of the vehicle in idling conditions. The ECOSMART Anti-Idling System is managed by the Demers Electronic MultiplexSystem (DEMS).

21-Paint and Decals (DEC)

<i>Name/Description</i>	<i>Quantity</i>
Urethane Paint	1.00
Two (2) coats of primer with two (2) coats of urethane. All four (4) sides and roof. No sanding. No buffing.	

22-Drivers Compartment (CAB)

<i>Name/Description</i>	<i>Quantity</i>
Floor-Mounted Console with control	1.00
Floor-mounted console in front cab.	
Storage for Flare and Fire Extinguisher	1.00
Storage compartment in front cab for flares and one (1) five-pound (5 lbs) fire extinguisher.	
Armrests, Driver and Passenger, Individual	1.00
Individual driver- and passenger-side armrests on sides of floor-mounted console.	
Cup Holders, Dual, in Floor-Mounted Console	1.00
Dual cup holders in floor-mounted console.	
Control Center with 4.3in Touch Screen	1.00
Control center with 4.3in touch screen in the floor mounted console.	
Cab headliner with Reading Lights, Red/Clear (2)	1.00
Two (2) clear and red overhead LED reading lights.	

23-Curbside Configuration (CRB)

<i>Name/Description</i>	<i>Quantity</i>
Mid Height Curbside ALS Cabinet, with Drawer	1.00
Mid height ALS cabinet on curbside. Includes four (2) aluminum extruded doors with see-through windows, adjustable shelve, one (1) drawer, LED strip lighting, and inside/outside access via curbside door.	
Full-Length Seat Cushion	1.00
Full-length, thermoformed, molded seat cushion.	
Seat Backrest	2.00
Individual, thermoformed, molded backrests.	



Seating, Two (2) EMT, 4pts Safety Belt	1.00
Seating for two (2) EMT with 4pts safety belt - Squad bench	

24-Streetside Configuration (STR)

<i>Name/Description</i>	<i>Quantity</i>
Flip-Up Door, Tinted Self Latching Sliding Windows	2.00
Aluminum flip-up frames, self latching for easy restocking of cabinets. Polycarbonate tinted self latching sliding windows.	
Additional drawer below rear action area	1.00
Additional drawer below rear action area added below existing drawer	
Additional drawer below action area	1.00
Additional drawer below action area added in front of S2 compartment.	
Corner Cabinet, Streetside, Two Adjustable Shelves	1.00
Corner cabinet on streetside of front wall. Includes two (2) aluminum extruded doors with see through windows, two (2) adjustable shelves and LED strip lighting.	
Locking Radio Communication Compartment	1.00
Lockable compartment on street side for radio communication	
Medical Cabinet, CPR Bench Seat, Without Access	1.00
Medical cabinet with CPR bench seat, the rear lower location is blank to provide extra S3 exterior compartment space.	
Seating, One(1) EMT, 4pts Safety Belt	1.00
Seating for one(1) EMT with 4pts Single Click safety belt - CPR seat	

25-Forward Bulkhead (FWB)

<i>Name/Description</i>	<i>Quantity</i>
Sliding Door Crawl-Through	1.00
Crawl-through with sliding door on front division to access to the cab.	

26-Attendant Seat (AST)

<i>Name/Description</i>	<i>Quantity</i>
EVS Swivel Seat Base, Two (2) Positions	1.00
EVS swivel 360 degrees seat base, locking in two (2) positions, forward and rearward positions	
EVS 1880, One(1) EMT, 4pts Safety Belt Child seat	1.00
Seating for one (1) passenger with EVS 1880 4pts safety belt, vac-formed seamless attendant's seat. Integrated child restraint system that allows uninjured children weighing between 20-65 lbs to be transported in a five point safety harness. When it is not needed, the child-insert can be folded into the seat and allow an adult to use the seat as a standard attendant's seat.	

27-Cot Configuration (COT)

<i>Name/Description</i>	<i>Quantity</i>
Floor Plate & Pre-wire Power-LOAD - GEN 2 (NEW)	1.00
Stryker Power-Load floor plate. No cot fastener included. Include pre-wiring for charging feature. Default option for new Power-LOAD system from the field.	
Center Floor-Mount Cot Configuration	1.00
Center floor mount cot configuration	

28-Rear Control Panel (CAR)

<i>Name/Description</i>	<i>Quantity</i>
Color Touch Screen Controls, 4.3in	1.00
Auxiliary 4.3in color touchscreen controls.	
4.3in color touch screen console	1.00
4.3in color touch screen console	

29-Oxygen (OXY)

<i>Name/Description</i>	<i>Quantity</i>
Oxygen Outlets, Four (4) Four (4) oxygen outlets. Two (2) in ECC, one (1) on curbside, and one (1) on the ceiling.	1.00
Oxygen Outlet, Quick-Connect Quick-connect style oxygen outlet.	4.00
Oxygen Regulator, Manual, Sensor and Dig. Read-Out Manual oxygen regulator with pressure sensor and digital read-out.	1.00
Oxygen Control Valve, Electronic, Manual By-Pass Electronic oxygen control valve with manual by-pass.	1.00
Storage for Two (2) "D-Size" Portable Cylinders "D-size" Portable oxygen cylinder storage (2), located in side entry door.	1.00
Universal Vertical Holder for Main Oxygen Cylinder Universal vertical holder for types "K" or "M" main oxygen cylinder in S1 streetside exterior compartment.	1.00

31-Suction (SUC)

<i>Name/Description</i>	<i>Quantity</i>
Suction System location in ECC Main suction system is located in front streetside action area.	1.00
Thomas high flow vacuum pump Thomas high flow vacuum pump	1.00
Vacuum regulator with disposable canister Vacuum regulator with disposable canister	1.00

32-Electrical System (ELE)

<i>Name/Description</i>	<i>Quantity</i>
Power Inverter, Xantrex Freedom, True Sine, 1000W The inverter/charger provides AC power using the DC power from the conversion battery bank. Recharge all battery banks and power all 120 volts AC outlets when the external shoreline is connected.	1.00
Super Auto Eject Power Inlet, 20 Amps, Yellow Kusmaull 120 Volts AC, 20 Amps - Automatically disconnects shoreline - Completely sealed - Yellow cover - Indicator light.	1.00
Electrical Outlet, 120V AC with Indicator 120V AC hospital-grade electrical outlets with indicator.	1.00
ACDelco Conversion Batteries Two (2) ACDelco conversion Batteries.	1.00
Electrical Outlet, 12V DC 20 amp with Indicator 12V DC, 20 amp Duplex electrical outlets.	1.00
Management System (DEMS) – MMC system. (Included) Management System (DEMS) – MMC system.	1.00

33-Communication System (COM)

<i>Name/Description</i>	<i>Quantity</i>
Pre-Wiring for 2-Way Radio, Two (2) Antenna Cables Wiring preparation for two-way radio, with two (2) antenna cables.(routed from front cab to radio communication compartment)	1.00
Radio Communications Compartment Radio communications compartment universal board, Bussmann blade-type fuse panels, and harness to power the radio communication devices.(12V battery feed, ground, ignition).	1.00
Radio Communications Front Console	1.00

Radio communications front console universal board, Bussmann blade-type fuse panels, and harness.

Data recorder signals available through dedicated CAN in electrical compartment 1.00

Data recorder signals available through dedicated CAN port in electrical compartment

34-HVAC (CVC)

<i>Name/Description</i>	<i>Quantity</i>
Dual In-Line condenser 60000 BTU, Front	1.00
Auxiliary dual in line condenser installed on the front of module - Hoseline 60000 BTU	
Independent Air Conditioning System	1.00
The compressor, condenser and evaporator form an assembly independent of the OEM, cooling the air of the patient compartment through the ducted outlets.	
Air Conditioning Outlets, Round	1.00
Round outlets for ducted air conditioning unit.	
OEM Tie-In Heating Unit	1.00
The heating system is an extension of the OEM heating system, heating the patient compartment area through invisible opening underneath the medical cabinet at floor level.	
Exhaust Fans (2)	1.00
Two (2) exhaust fans for contaminated air. Activated by front control interface or rear console switch.	

35-Interior Lights (ILG)

<i>Name/Description</i>	<i>Quantity</i>
LED Dome Lights, Adjustable, Dig. Timer	9.00
The ceiling lights have four (4) different intensities. Each time the ceiling lights button is pushed, the intensity increases, until maximum intensity is reached.	

36-Grab Handles (GBR)

<i>Name/Description</i>	<i>Quantity</i>
Grab Bars Color, Yellow	1.00
Color of selected grab bars is Yellow.	
Rear Door-Mounted Grab Bars, 16" x 16"	1.00
Two (2) door-mounted grab bars, 16" x 16", inside of rear doors (A1 and A2).	
One (1) curbside door mounted grab bar 24"	1.00
One (1) curbside door mounted grab bar 24"	
Embarking Grab Bars, 12"	1.00
Two (2) entry grab bars, 12" each, mounted inside the patient compartment. One (1) near the curbside entry door, and one (1) near the R2 rear entry door.	
Ceiling Grab Rails, 90", Two (2)	1.00
Two (2) ceiling-mounted grab rails, 90".	

37-Finish and Trim (FNS)

<i>Name/Description</i>	<i>Quantity</i>
Lonseal, Lonplate II, Gun metal	1.00
Lonseal, Lonplate II, Gun Metal floor covering.	
Cobalt Blue Upholstery	1.00
Colbalt blue vinyl upholstery for seat and padding covering. (Included)	
Safety Yellow Upholstery	1.00
Yellow vinyl upholstery for safety exit padding covering. (Included)	
Wood Flooring	1.00
Exterior grade plywood, 0,75 inches thick.	
Fiberglass Ceiling	1.00
Fiberglass ceiling in Patient Compartment. (Included)	

General Vehicle Identification		1.00
Vehicle general labels identification. (Included)		
38-Functionality (FCT)		
<i>Name/Description</i>		<i>Quantity</i>
Glove Box (4) Holders at Rear of Medical Cabinet		1.00
Recessed holder contain four (4) gloves box, at rear of medical cabinet next to rear entry door. Restocking via pivoting door. (Glove box not included)		
Radio Speakers, Recessed, Two (2)		1.00
Two (2) recessed radio speakers.(Included)		
IV Hooks, Recessed in Ceiling, Flexible, Four (4)		1.00
Four (4) recessed flexible IV hooks in ceiling.		
Trash Container, Flip-Down, Hands-Free		1.00
Trash container bracket in curbside flip-down container.		
Glove Box Holder - Five (5)		1.00
Glove Box Holder - Five (5) below curbside upper cabinet		
Recessed sharps and trash in squad bench		1.00
Squad Bench w/ Recessed Sharps (2 gallons) & Trash (3 gallons) at head with top access with sliding door. (Deletes kick-out trash)		
Storage Compartment, Three Sliding Doors		1.00
Storage compartment, Three (3) cabinets, LED strip lighting, and sliding doors.		
Digital clock with driver intention indicators ove		1.00
Digital clock with driver intention indicators (direction, braking) located in padding above the rear doors.		