



QUOTATION

Road Rescue®

WO#: 663880

DESCRIPTION	QTY
	1
INFORMATION	
RR, Information - Scope, Purpose and Classification	1
Manufacturer Certified ISO 9001	1
WARRANTY	
RR, Warranty, Documentation	1
RR, Warranty, Module Structural	1
RR, Warranty, Electrical, Standard System	1
RR, Warranty, Paint	1
RR, Warranty, Conversion	1
== RR-Type 3 - UM 170" Module - 1.044 11/07/22 ==	
RR, This unit built in accordance with KKK-A-1822F CN 10 Cabinet Requirements	1
This unit as specified meets all requirements of KKK-A1822-F Change notice 10.	
All cabinets shall be labeled as to their capacity Rating.	
01- CHASSIS REQUIREMENTS	
FORD CHASSIS	
U RR, 2026 Ford E450, 7.3L G, Cutaway, 158" WB T3	1
(2) OEM Alternator	
Includes 2nd battery located in RF comp.	
Rubber floor mat, OEM, std.	
Cab Headliner Vinyl	
W/ Ford CO-Pilot 360	
ALTERNATORS	
Alternator(s) - Standard OEM	1
SUSPENSION	
RR, Front Suspension, Ford E-Series	1
RR, Rear Suspension, Ford E-Series OEM	1
RR, Front Sway Bar, OEM	1
RR, Rear Sway Bar, OEM	1
FRONT END ALIGNMENT	
Front End Alignment, None- QC Check	1
OUTSIDE REAR VIEW MIRRORS	

DESCRIPTION		QTY
	RR, Mirrors, OEM Standard	1
	RR-CAB INTERIOR OPTIONS	
	RR, Insulation, Cab, Thinsulate in Cab Ceiling	1
	SAFETY OPTIONS	
		1
	WHEEL COVERS	
	RR, Wheel Covers, Phoenix w/ Lug Nut covers, E-Series	1
	BASE CONVERSION	
S	RR, Conversion, Ultramedic, Type 3, 170 Module, Ford -22-3	1
	02 - MODULE REQUIREMENTS	
	RR, Ultramedic, 170" x 96"W Type 3 Module	1
	Ultramedic III - 170"L x 96"W Type III (A.D.) Walk-Through Module. Includes 6" cab recess. Aisle width to be 50". The interior headroom shall be 72".	
	RR, Standard Cab Extension of 6"	1
	There shall be a 6" recessed bulkhead on the cab side of the module to insure that the driver and passenger seats have additional seat travel and that the incline adjustment on the seats is capable of providing the driver and passenger with a comfortable seating position.	
	RR, Interior Headroom, 72"	1
	RR, Aisle Space, 50" , Ultramedic III	1
	MATERIALS	
	RR, Sub floor Materials,	1
	RR, Type I & Type III, Interior Materials	1
	RR, Type I & Type III, Materials	1
	03 - MODULE EXTERIOR	
	UNDERCOATING	
	RR, Undercoating Module	1
	EXTERIOR MODULE CONSTRUCTION	
	RR, Exterior Module Construction Specifications	1
	RR, Stone Guards Type 3 Std Height, w/Full Height Diamond Plate Corner Guards	1
	Extend Standard Stone Guard from Top of the Front and Rear Stone/Kick Panels to the Bottom Edge of the Drip Rail on all (4) Vertical Corner Radii	
	The type 3 standard stone guard height is 24 inch	
	In addition to this dimension a drop skirt will be added to the stone guard accordingly.	
	RR, Module Roof Radius, 3" High	1
	RR, Extreme Bonding Tape	1
	RR, Sub-floor Gusset Supports	1
	RR, One Piece Side Body Panels	1
	RR, Reinforce Rear Header	1
	RR, Single Sheet Module Roof Sheet	1
	DROP SKIRTS	
	RR, Drop Curbside Fwd Body Skirt, 3" (w/step close out) Light Duty Cutaway	1
	The manufacturer shall drop the lower body skirt along the curbside of the module ahead of the rear wheel well at the bottom of the module by approximately 3". This shall lower the height of the side entry step and provide easier access through the side entry door.	

	DESCRIPTION	QTY
	FUEL FILLS & SPLASH PLATE	
	RR, Housing Fuel Fill , Pocket, Round	1
	SUB-FLOOR SYSTEM	
	RR, 1 Inch Composite Floor Pan	1
	RR, Composite Floor Material	1
	RR, Sub-Floor Assembly, Installation	1
	RR, Sub-Floor Assembly, 1/8" PVC	1
	MODULE ENTRANCE	
	RR, Module Access, CS Door standard location	1
	The module shall include one side entry door on the curb side of the module, and one set of double doors for entry to the rear of the module. The curb side door shall provide a clear opening that is approximately 30" W x 70"H. The rear double doors shall provide a clear opening that is approximately 50"W x 60"H.	
	MODULE DOORS, HANDLES & HOLD OPENS	
	RR, Entry Doors, Hidden Hinge, Seal on Door ,W/Push Button Fail Safe Latching	1
	This includes the Fail Safe Latching mechanisms on all three entrance doors.	
	RR, Hold Open Rear Entry Doors, (2) 4.5" Door Grabbers	1
	RR, Hold Open, Curb Side Entry Door, Heavy Duty Gas Spring	1
	Curbside Door Restraint - Heavy Duty gas spring hold opens. - Attached by 1/4" x 20 SS Machine Screws with 1/4" x 20 Nut Inserts into Corner Gusset in Door Side entrance door to open to 90+ degrees.	
	RR, Entry Door Handles , TriMark Logo Chrome/Black (includes interior handles)	1
	With Push button Emergency Release top and bottom of each door.	
	RR, Door Lubrication, Paddle Handles and Latches	1
	Lubricate all Door Hardware All paddle handles, latches, rods and springs shall be lubricated prior to delivery.	
	RR, Magnetic Entry Door Switches	1
	RR, Door Panel Mounting Screws	1
	RR, Coil Cords for Electrical Circuits	1
	DOOR REFLECTORS & FLASHERS	
	RR, Door Flashers, (3) Whelen 4" Dia Red LED, (1) Per Entry Door	1
	(3) Whelen 4" Round Red LED warning lights in rubber grommets. - Installed on the module entrance doors, (2) on the outboard lower corners of the rear interior door panels and (1) on the outboard lower corner of the curbside interior door panel. Each light to flash when the respective door is opened.	
	RR, Power Door Locks, Module Entry Doors,w/Hidden Switch	1
	Install power door locks in side and rear entrance doors. Includes (2) lock/unlock switches, one at side door and one at rear door. Also includes (1) hidden switch in rear license frame for unlock function only. System will be tied to OEM chassis power locks so that both systems operate as one. Does not include wireless remote.	
	RR, Inner Door Panel - Stainless Steel , Two Piece	1

	DESCRIPTION	QTY
	<p>INTERIOR DOOR PANEL. The interior finish of the entry doors shall be stainless steel, 2 piece design for ease of serviceability.</p>	
	<p>RR, Lock Boxes, White Diamond Grade The lock boxes for the interior door handles are to be covered with White Diamond Grade reflective material. Includes (1) white logo per lock box.</p>	1
	<p align="center">SIDE DOOR STEP</p>	
	<p>RR, Dual Side Entry Step Well, Increased Depth, Lower Grip, Upper Diamond Plate Increase the depth of step well inboard as far as sub structure permits. Side surfaces to be Diamond Plate. Step surface to be a combination of NFPA Diamond Plate and removable 9" Grip Strut insert. The Diamond Plate section of the floor to be supported with rigid foam floor insulation in the same manner as the module floor. The lower step with grip strut will include a drain hole with plug. The second step to be fabricated of NFPA Diamond Plate and installed so that the step surface is midway between the step well floor surface and the module floor surface making two equal steps into the vehicle.</p>	1
	<p>RR, Light, Side Entry Step well, LED, Whelen OS Mini, Clear There shall be a Whelen OS Mini LED light, 45 degree, installed in the curbside step well to automatically light when the side entrance door is opened.</p>	1
	<p align="center">WINDOWS</p>	
	RR, Module Window Requirements	1
	WINDOW- Side Entry Door	
	RR, Window, Side Entry Door, 18X18, Slider - Standard Glass	1
	WINDOW - Rear Entry Doors	
	RR, Window, Rear Entry Doors, (2) 18 x 24, Fixed, Standard Glass	1
	MODULE TO CHASSIS MOUNTING SYSTEM	
	RR, Module to chassis mounting system, Type III	1
	RR, Cab to Module Attachment, Type III	1
	REAR BUMPER AND REAR STEP CONSTRUCTION	
	RR, Rear Bumper, Recessed 9" Pocket, Flip-up	1
	RR, Bumper Pods, CPI Cast Aluminum w/RR Logo. (UM & UM-150) Cast Products Bumper Pods, High Polish Finish. Mounted on the outboard rear step bumper frame members. The CPI cast aluminum pod shall include a RR Logo embossed in the cast pattern on the step tread.	1
	RR, Whelen, Pair OS Mini In Bumper Pocket Install (2) Whelen OS Mini (white LED) marker lights to illuminate the rear bumper step. Lights shall be located on the inside opposing faces of the bumper pocket. Lights shall turn ON when the curbside rear entry door is open.	1
	INSULATION	
	RR, Whisper Quiet, Sound Dampening/Thermal Insulation Package (UM) The module interior walls, roof and doors shall be insulated to enhance the interior environment and minimize the conduction of heat, cold and external noise from entering the module. The wall and ceiling insulation shall be a non-settling, 2 inch thick, self-extinguishing polystyrene foam planking.	1

	DESCRIPTION	QTY	
	<p>There shall be 3M brand acoustical Thinsulate installed over all exterior compartments and wheel wells for added acoustical insulation.</p> <p>In addition to the polystyrene foam planking, the ceiling shall include a layer of 1/2 inch closed cell foam rubber padding installed prior to the vinyl ceiling material. The foam and vinyl shall provide additional safety and insulation.</p> <p>There shall be a single layer of 3M Thinsulate insulation between the OEM head liner and the cab roof to reduce noise.</p> <p>The patient compartment entrance doors and the exterior compartment doors shall have 2 in. thick, self-extinguishing polystyrene foam insulation. The foam shall be glued to the interior and exterior panel.</p> <p>The interior walls of the module shall be insulated with 1" polystyrene block foam insulation installed between the extruded structural framing. Wall areas that are too irregular for 1" block foam insulation, or where the block foam will interfere with wall outlets and wire chases, are to be insulated with 3M brand acoustical Thinsulate insulation. After the foam is installed, the entire interior of the unit shall be wrapped with 5/16" foil wrapped two sides radiant barrier foam style insulation to enhance the thermal and acoustical properties of the modular unit. The wheel well and interior compartment wall areas shall be wrapped with Barymat sound proofing material installed under 3M brand acoustical Thinsulate insulation and the underside of the module floor will be coated with a Dow Chemical two part spray in place acoustical/thermal polyurethane insulation. This package provides an enhanced thermal/acoustical insulation package designed to provide an extremely quiet, environmentally efficient patient compartment.</p> <p>Reflective Barrier/Barymat/Spray Foam Thermal Insulation Package:</p> <p>A. Reflective Barrier - Low-E Foil Wrapped Insulation System - The module walls shall be insulated with high density 1" block foam. Wall areas that are too irregular for 1" block foam insulation, or where the block foam will interfere with wall outlets and wire chases, are to be insulated with 3M brand acoustical Thinsulate insulation. Then the entire interior of the module shall be wrapped with 1/4" Low-E foil wrapped radiant barrier foam style insulation.</p> <p>B. This radiant barrier material will cover the following: Full ceiling and wrapping over the corner radius and down the sidewall Full side, front and rear walls from the top of the wall to the lowest possible point along the side, front and rear walls Seams to be taped with silver / foil ducting tape to secure seams.</p> <p>C. Barymat sound deadening insulation over wheel wells and interior side of exterior compartment walls. (Installed under 3M brand acoustical Thinsulate insulation).</p> <p>D. Spray foam underbody insulation prior to undercoat application, full sub floor coverage where applicable. Includes curbside step well area.</p>		

	DESCRIPTION	QTY	
	<p align="center">ELECTROLYSIS PREVENTION</p> <p>RR, Electrolysis Prevention, Fluid Film Fluid Film is used at Every Point Where the Mounting Process has the Propensity to Break Paint.</p>	1	
	<p align="center">COMBINATION RUB RAIL AND FENDER RING</p> <p>RR, Rub Rail, Skirt Line and Fender Ring Extruded Black Rubber Rub Rail and Fender Ring - The lower body Rub Rail and Fender Ring to made of Black extruded rubber. The aluminum extrusion that the rubber rub rail and fender rings sets into for added strength will stand off of the exterior body with nylon spacer for ease of cleaning between the rub rail and the exterior body. The rub rail and fender ring assembly will then be through bolted to the lower body. The lower body rub rails will transition to the fender ring and will have polished aluminum corner caps. At each end of the rub rails there will be a polish aluminum end caps. The rubber rub rail extrusion to accept multiple selections of reflective vinyl color inserts.</p>	1	
	<p>RR, White Scotchlite Insert for Rubber Rail</p> <p align="center">SPLASH GUARDS AND RUNNING BOARDS</p> <p>RR, Running Board w/7" Grip Strut Inserts, E-Series This feature includes a mud flap at the forward end of the running boards to protect the grip strut insert from wheel splash.</p>	1	
	<p>RR, Mud Flaps, Rear, Black w/ Road Rescue Logo Heavy Duty Rubber Mud Flaps w/ RR Logo Heavy Duty Rubber Mud Flaps to be bolted to the wheel liner behind the rear duals with 1/4" x 20 Stainless Steel bolts, washer and nylon locknut for ease of maintenance and repair.</p>	1	
	<p align="center">DRIP RAILS</p> <p>RR, Drip Rails Polished Aluminum Drip Rails Above All Doors, Entry and Compartment.</p>	1	
	<p align="center">WHEEL WELL LINERS</p> <p>RR, Wheel well liners Aluminum Wheel well Liners Extending to Bottom of Skirt.</p>	1	
	<p align="center">CAB TO MODULE ACCESS</p> <p>RR, Cab to Module, Walk Through Door The cab to module walk/crawl through to include a clear fixed window and a self latching hinged door in the open or closed position with the actuator latch being on the cab side. Overall door height to accommodate a fluid dam.</p>	1	
	<p>RR, Cab to Module, Fluid Dam Cab to Module Fluid Dam - A formed fluid dam, 4" tall to be installed below the cab to module walk through door to prevent fluids from contaminating the cab. The floor and fluid dam to be fully sealed.</p>	1	
	<p align="center">LICENSE PLATE HOLDER</p> <p>RR, Rear License Holder Location, C/S Above Rear Kick plate The license plate frame shall be installed on the curbside rear module body above the diamond plate.</p>	1	
	<p align="center">EXTERIOR COMPARTMENT CONSTRUCTION</p>		

	DESCRIPTION	QTY
	RR, Exterior Compartment Construction, Heavy Duty	1
	RR, Door Sill Protection, Stainless Steel, All Compartments.	1
	Door Sill Protection Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage.	
	EXTERIOR COMPARTMENT DOORS	
	RR, Compartment Door, Hidden Hinge, Seal on Door (UM)	1
	COMPARTMENT PADDLE HANDLES	
	RR, Compartment Handles, Exterior, TriMark Logo Chrome/Black (UM)	1
	TriMark Two-Point Cast w/Polished Chrome Paddle Handle and Housing, Locking and Non-Locking, with floating cam - Mounted in CNC Cut Opening in Each Compartment Door Skin w/OEM Clamp Assembly.	
	RR, Compartment Handle, TriMark Logo Chrome/Black, Paddle, Street side, locking	3
	For single doors or Leading doors on Compartment #1 Compartment #2 Compartment #4	
	RR, Compartment Handle, TriMark Logo Chrome/Black, Paddle, Street side, Non-Lock	1
	For Trailing doors on the street side. Compartment #2	
	RR, Compartment Handle, TriMark Logo Chrome/Black, Paddle, Curbside, locking	2
	For single doors or Leading doors on the curbside. . Compartment #6 Compartment #8	
	RR, Compartment Handle, TriMark Logo Chrome/Black ,Drop Door or Drawer, Locking	1
	For Drop down doors or drawers on either side of unit. Compartment #8.5	
	RR, Compartment Door Locks, 2015 TriMark	1
	Compartment Door Handle Manual Locks. All doors shall incorporate double cut, non-directional tumbler assemblies that are keyed alike.	
	RR, Compartment Rotary Latches	1
	RR, Compartment Door Nader Pin	1
	RR, Compartment Door Lubrication, Door Handles and Latches	1
	RR, Compartment Door Switches, Magnetic	1
	RR, Compartment Door Panel, Inner, Polyurethane coated	1
	The interior door panels of the exterior compartment doors are to be flat aluminum with the same color Scorpion Rubberized polyurethane coating applied as the exterior compartments.	
	RR, Compartment Door, Panel Mounting Screws	1
	RR, Power Door Locks, Exterior Compartments	1
	RR, Exterior Compartment #'s 1, 2, 4, 6 & 8, Only	1
	RR, Compartment Door, Gas Struts	1
	The struts will be installed on each exterior compartment door. Exterior compartment doors to open to 90+ degrees.	

	DESCRIPTION	QTY
	RR, All Standard Compartment Lights, LED, Flexible Strip Two (2) Vertical strips in each exterior compartment installed, one (1) on each side of the opening. The compartment #1 lights will be also wired to Oxygen light switch in action area. #1 Compartment #2 Compartment #4 Compartment #6 Compartment #8 Compartment	1
	<p style="text-align: center;">EXTERIOR COMPARTMENT INTERIOR</p> RR, Exterior Compartment, Interior Finish, Polyurethane Coated Exterior Compartment Interior Polyurethane Rubberized Liner Color Choice. Rubberized polyurethane coating applied to the surfaces of ALL exterior compartment walls and dividers. Does not include slide out battery tray or mounting angles. Battery Tray to be raw aluminum.	1
	RR, Color, Light Gray <p style="text-align: center;">EXTERIOR COMPARTMENT SHELVING</p> RR, Exterior Compartment Shelving and Unistrut All exterior shelving Unistrut shall be welded to the walls prior to any compartment wall finish. Where specified, exterior adjustable shelves shall be box pan formed of a minimum .125 inch Aluminum Diamond Plate and corners shall be welded. Shelves shall be infinitely adjustable, and securely mounted to heavy gauge aluminum Unistrut track.	1
	RR, Compartment Shelving, Diamond Plate Diamond Plate Exterior Compartment Shelving.	1
	<p style="text-align: center;">COMPARTMENT #1 - STREETSIDE FWD</p> RR, Compartment #1, EXTERIOR RR, Compartment #1, Electrical Storage #1 Compartment Electrical Storage - Recessed into the bulkhead side of compartment #1 shall be an enclosed area for the installation of miscellaneous electrical components. The aluminum cover for this area to be installed with 'J' molding The 'J' molding to be full length of panel on bottom and inboard side. Outboard side of panel to be secured with mechanical fasteners.	1
	RR, Compartment #1, Full Height, Standard Configuration (UM) The forward most compartment on the street side of the module. It shall be externally vented with stamped louvers, to prevent compression of the air inside the compartment to allow you to shut the door.	1
	RR, Compartment #1, Shelf, Fixed There shall be a fixed shelf above the oxygen area for miscellaneous storage.	1
	RR, Compartment #1, Divider, Fixed fixed divider(s) shall be installed in compartment #1 providing backboard storage on the forward side.	1
	<p style="text-align: center;">COMPARTMENT #2 - STREETSIDE FWD WHEELWELL</p> RR, Compartment #2, EXTERIOR	1

	DESCRIPTION	QTY
	RR, Compartment #2, Standard Configuration, (UM) #2 Compartment to be directly behind the #1 compartment and below the interior action area shelf on the street side of the module.	1
	RR, Compartment #2, Shelf Adjustable, First Shelf	1
	COMPARTMENT #4 - STREETSIDE AFT	
	RR, Compartment #4, EXTERIOR	1
	RR, Compartment #4, 3/4 Height, Standard Configuration #4 Compartment street side rear of module with Interior Upper left #4 Cabinet - #4 Compartment to be to the bottom of upper left #4 cabinet.	1
	RR, Compartment #4, Shelf Adjustable, First Shelf This compartment shall have one (1) adjustable shelf installed at the base of the INT / EXT access.	1
	RR, Compartment #4, Shelf Adjustable, Additional, Each Install (1) Adjustable shelf below the bottom INT / EXT access	1
	COMPARTMENT #6 - CURBSIDE AFT	
	RR, Compartment #6, EXTERIOR	1
	RR, Compartment #6, Standard Configuration (UM)	1
	RR, Compartment #6, Divider, Fixed (UM) Compartment #6 shall include a fixed vertical divider centered in compartment.	1
	RR, Compartment #6, Shelf Adjustable, First shelf There shall be an adjustable shelf mounted in compartment #6. The addition of this shelf will include an additional compartment light for this exterior compartment. The shelf will be installed forward of the compartment's vertical divider at the bottom of INT / EXT access.	1
	RR, Compartment #6, Shelf Adjustable, Additional, Each (2) shelves evenly spaced between INT / EXT opening.	2
	RR, Compartment #6, Equipment Strap, Seat Belt Style, Metal Buckle, Each (1) Seatbelt style strap with metal buckle. (Push button) Approximate mid height from wall #1 to fix divider.	1
	RR, Compartment #8, EXTERIOR	
	RR, Compartment #8, Reduced Height Door Exterior compartment #8 shall be the forward most compartment on the curbside of the module allowing interior / exterior access to the interior ALS cabinet. This compartment shall be per the size and configuration shown in the attached prints.	1
	COMPARTMENT #8.5 - CURBSIDE LOWER FORWARD	
	RR, Compartment #8.5, EXTERIOR	
	RR, Compartment #8.5, Drawer Style Battery Box Configuration Battery access door mounted slide out battery tray. The interior of the battery compartment to be made of POLYURETHANE COATED ALUMINUM. Battery Tray to be raw aluminum.	1

	DESCRIPTION	QTY	
	INTERIOR TRIM AND FEATURES		
	INTERIOR ADJUSTABLE SHELVES		
	INTERIOR TRIM		
	RR, Interior Trim, Standard	1	
	All cabinet and wall panel aluminum trim including shall be Gray anodized. All protective corner trim shall be Opaque and will include a matching domed end cap. (No Black trim to be used)		
	HEADLINER		
	RR-Ceiling Medical Device Rail (UM & UM-150)	1	
	The medical device rail allows for previsions for standard:		
	(1) IV Hanger		
	(1) Oxygen outlets		
	(2) AM/FM speakers.		
	(1) Dome Light over the walkway		
	(3) Patient Lights focused at head, torso and legs		
	(2) antenna accesses under cot lights.		
	RR, Headliner, Vinyl Ceiling, No Seams (UM & UM-150)	1	
	RR, Ceiling Medical Device Rail. White LED Strip Lights,(UM & UM-150)	1	
	RR, Ceiling Medical Device Rail, Red/Amber LED Turn/Brake Strip Lights (UM & UM-	1	
	Red/Amber LED strip lights shall be installed in the Ceiling Medical Device Rail on both sides at the rear. Total length on each side to be 12"		
	FLOORING		
	RR, Flooring, Aluminum Floor/Wall Cove Molding	1	
	RR, Flooring, Stainless Steel Rear Threshold, 45 Degree Chamfered	1	
	RR, Flooring - Lonplate II Choice	1	
	RR, Color- 424 TX Gunpowder	1	
	RR, Floor, Curbside Stainless Steel Threshold, 4"wide,Safety Walk Anti-Skid Tap	1	
	Rear Entry Door Grab Handles		
	RR, Rear Entry Door Grab Handles, "L" Bars, 16" Anti-Microbial	2	
	"L" Bars - 16" Anti-Microbial. 1.25" Diameter stainless steel "L" Bars mounted to each rear door. Approximately 16" wide by 26" high. Clear Anti-Microbial finish.		
	Side Entry Door Grab Handle		
	RR, Side Entry Door Grab Handle, "L" Bar - 19" Anti-Microbial	1	
	"L" Bar - 19" Anti-Microbial. 1.25" Diameter stainless steel "L" Bars mounted to side entry door. Approximately 19" wide by 24" high. Clear Anti-Microbial finish.		
	Ceiling Grab Rail - Center		
	RR, Ceiling Grab Rail, Center 108" Anti-Microbial	1	
	Ceiling Grab Rail - Street side		
	RR, Ceiling Grab Rail, Street side 72" Anti-Microbial	1	
	IV FLUID HANGERS		
	RR, IV Hangers, CPI #IV2008	1	
	RR, IV Hangers, Quantity (2)	1	

	DESCRIPTION	QTY	
	LEFT STACK AND BULKHEAD AREA #1		
	RR, Interior Street side #1 - Left Stack and Bulkhead	1	
	RR, Upper Bulkhead Cabinet, Double Doors	1	
	Upper Bulkhead Electrical Cabinet, Double Doors		
	Install double hinged Kydex Thermoplastic or multi-spec (picked in the proper section of work order) doors with locking latch on the right hand door and center mullion on the left hand door on the standard upper bulkhead electrical cabinet.		
	RR, Left Stack, Storage Area #1, 45 Deg Angled, CN 10 Certified	1	
	A two section vertical cabinet shall be provided behind the attendant seat on the street side forward corner on a 45 degree bevel that includes the access doors to the cabinet. The lower cabinet door shall be aluminum with plastic laminate and the upper cabinet shall be a hinged Poly carbonate door with full perimeter extruded aluminum frame and integral latching handles.		
	RR, Shelf Adjustable, Left Stack, First Shelf	1	
	There shall be an adjustable shelf located in the left stack cabinet. C1		
	ACTION WALL AREA #2		
	RR - INTERIOR STREETSIDE #2 - ACTION AREA	1	
	RR, Action Wall Area #2, Medical Device Rail	1	
	The medical device rail allows for provisions for the standard		
	(2) Oxygen Outlets		
	(1) Oxygen Solenoid Valve		
	(1) Suction Regulator		
	(2) 12V Outlet		
	(1) 110V Outlet		
	(1) SSCOR regulator.		
	RR, Cabinet, UL2 & UL2.5 Comb, Single Restock Cabinet w/Split Interior, CN 10 Cer	1	
	The UL2 and UL2.5 cabinets shall share a single door with sliding poly carbonate doors with spring actuated latching handles and have restocking feature with integral exterior spring actuated latch. The interior of the cabinet shall be split into (2) sections with (1) adjustable shelf in each. The attendant switch panel and environmental controls shall be built into a separate 6" high section below the restocking door.		
	RR, Cabinet, Upper Left U2.75, Angled Close out w/ cushion	1	
	The rearward end of the UL2 or 2.5 cabinet shall be angled forward at approximately 45 degrees to provide a safety zone for the CPR seat occupant in the event of a forward vehicular impact. The angled face of this cabinet shall be covered with a minimum 1" thick cushion.		
	RR, Action Wall Area #2, Stainless Steel Panel, Entire Street Side Wall	1	
	The street side wall shall be finished with full height, one piece stainless steel installed from the front of the forward action area to the rear of the rear action shelf aft of the CPR seat. The stainless steel is to be one single piece with no exposed fasteners.		

	DESCRIPTION	QTY
	RR Countertop, Forward and Rear Monitor Area.	1
	RR, HI-MACS, Sanremo Black	1
	RR-Interior Street side #3 - CPR Seat	
	RR, CPR Seat, Street side, Standard Configuration The CPR seat shall include a flip up seat equipped with a gas strut hold open device and positive latch for securing the lid when closed. The CPR seat shall include a 2" foam seat and backrest, the upper and lower sections will be padded on both sides for added protection.	1
	RR, CPR Seat Lid Hold-Down CPR Seat Lid Hold-down - Install a Black Tri Mark recessed paddle latch, Include a tri-mark retention mounting bracket (1) under CPR seat lid.	1
	RR, Cabinet, Upper Left U3, 9"H x 27"W, 72" Headroom ONLY - Upper left #3 Cabinet with 3/8" Lexan lift up door with restocking feature and two 2" round locking stainless steel latches. Does not include shelf. Cabinet to be approximately 9'H x 10-3/4" D x 27"W. Reduce the height of the CPR seat to 15" from floor and the bottom of seat cushion. The cushion on the under side of #3 cabinet to utilize 1/2" foam. The distance between top of the CPR seat and bottom of the cabinet cushion to be a minimum of 43" in compliance with KKK-A-1822F. NOTE: Requires 72" headroom.	1
	RR, CPR Seat, Seat Belt, 4 Point (Per4Max) Black, Change Notice 8- Compliant Above Lid mounted..	1
	RR, CPR Seat, "U" Barrier Bar, Padded, 1.5" SS, Gunmetal Mounted Approximate 12" from the center of the seat to the side of the barrier bar.	1
	RR, CPR Seat, RR Backrest and Head Cushion, RR Logo, (1) Set, Gunmetal	1
	RR, INTERIOR STREETSIDE #4 - REAR AREA	
	RR, Cabinet, Upper Left U4, Standard Configuration- CN 10 Certified Upper left U4 cabinet with sliding poly carbonate doors with spring loaded latching handles, restocking feature with spring loaded exterior integral latch and (1) adjustable shelf.	1
	RR, Countertop, 24" Aft of CPR Seat Counter aft of CPR seat to be 24" wide. Requires notching the #4 compartment. The door frame notch close out at the rear of the counter to be 24" wide.	1
U	RR, Interior Access, Sliding Doors, to Exterior Comp #4-CN 10 Certified SR #2025271F There shall be an access opening from the patient compartment into exterior compartment #4. The opening shall include sliding poly carbonate doors with spring loaded latching handles. The exterior compartment shelf shall be aligned with the lower edge of the opening.	1

	DESCRIPTION	QTY
	<p>There shall be (2) Interior access Areas to Compartment #4 with sliding Acrylic doors. There will be (1) in the upper portion of the exterior compartment and (1) below with access into the mid portion of the exterior compartment. See drawings.</p>	
	<p align="center">SQUAD BENCH AREA</p>	
	RR, INTERIOR CABINETS - SQUAD BENCH AREA	1
	RR, Squad Bench, Curbside, Two Piece Hinged Lid	1
	RR, Squad Bench, Restraint Belts	1
	RR, Squad Bench, Medical Device Rail	1
	The medical device rail allows for provisions for the standard	
	(1) Load / Scene cut out	
	(1) Oxygen Outlet	
	(1) Ceiling Light Timer.	
	RR, Squad Bench, Latches, Lids, Tri Mark, Include a tri-mark retention mounting brackets	1
	RR, Squad Bench, Seat Belts, Two 4-Point belts (Per4Max) Black, CN-8 Above the Lid Mounted.	1
	RR, Squad Bench, RR Backrest and Head Cushion, RR Logo, (1) Set, Gunmetal	2
	SEAT BELTS/ SAFETY NETS	
	RR, Safety Net, Head of Squad Bench (BLACK NET)	1
	The module shall include a utility net located at the head of the squad bench. The net shall be secured to the ceiling and curbside wall with aircraft style hardware to allow the net to be removed if necessary. The aircraft style hardware shall be securely mounted to structural tubing in the side wall at the side entry door and to a 1/4" plate welded between the frame member in the ceiling. Hardware at the wall and ceiling attachment points must be fastened with 1/4-20 stainless steel 100 degree flat head machine screws into threaded inserts.	
	RR, Head of Squad Bench, Storage, Recessed (2) O2 Brackets, Single Door	1
	There shall be a recessed cabinet for (2) QR-D-2 portable oxygen bottle brackets at the forward end of squad bench. The cabinet shall be located to the left of the side entry door step well and below the squad bench lid. Cabinet to have a single aluminum with Kydex Thermoplastic or multi-spec door. Door will be held closed with (2) latches.	
	RR, Upper Squad Bench, Cabinet, 9"H, 72" Headroom ONLY	1
	There shall be a cabinet located above the squad bench. The cabinet will be approximately 9"H x 8-1/2"D and will be the same length as the squad bench. The cabinet shall be divided into two (2) separate sections by a fixed center divider. Each section will have 3/8" Lexan lift up doors with restocking feature and locking latches. Does not include shelves. The distance between the top of the squad bench cushion to the bottom of the cabinet cushion shall be a minimum of 43" in compliance with KKK-A-1822F requirements for head clearance.	
	KKK Compliancy Regarding Overhead Cabinetry	1
	The inclusion of a cabinet over the squad bench or CPR seat on a unit with less than 72" headroom will result in the unit not meeting KKK specification requirements. The end user has	

	DESCRIPTION	QTY
	<p>been informed of the KKK requirements and this cabinet has been added at the request of, and according to the specifications of, the end user.</p>	
	<p align="center">BIOHAZARD- RR, INTERIOR - BIOHAZARD</p>	
	RR, Glove Butler(s)	1
	RR, Glove Butler (3) Total, Over Curbside Entry, Drop down Door	1
	<p>(3) Glove Butler II glove boxes installed above the side module entrance door inside a cabinet with drop down door and (2) locking latches. Door to be Kydex Thermoplastic or multi-spec covered and bottom hinged to tip out for restocking. Access holes to be cut in door for glove removal.</p>	
S	RR, Drawer, Sharps Only, Slide-out, Aft of CPR Seat	1
	<p>The Lower left cabinet shall include a pull out drawer Aft of the CPR Seat. This will include a slide out with Sharps storage drawer. Supplied with a 4.7 quart Sharps container .(290184) Face of slide out drawer to be stainless steel and will include a locking latch. Standard cutout of 7.875"w x 9.75"h x 12.25"d (inside).</p> <p>NOTE: Depth of drawer to 12" to allow 12" slides to give full access to the sharps container.</p>	
	RR, Access, Waste, Recessed in Lower Left Wall	1
	<p>Waste storage area recessed in lower left wall below action counter with interior access only. Supplied with 8 quart waste container. Access door to be stainless steel with opening above for disposal.</p>	
	<p align="center">CURBSIDE RIGHT STACK STORAGE #8</p>	
	RR, INTERIOR CURBSIDE - RIGHT STACK STORAGE #8	1
	RR, RF ALS, Upper Heater, A/C Unit, Standard Configuration (UM & UM-150)	1
	RR, RF ALS, Hidden Air Intake	1
	RR, RF ALS, "N2" Style, 2 OHO Polycarbonate, 2 Alum, 1 Drawer, 22", CN 10	1
	<p>Right Stack ALS, with Locking Middle Drug Drawer. 22"deep for applications with STANDARD or NO CAB RECESS.</p> <p>A 6 Inch high locking drug drawer with gas strut assist shall be installed in the middle portion of the right stack. The drawer shall have 22" slides. The remainder of the right stack shall be split into (2) sections. The lower section shall have framed Gen II OHO poly carbonate double doors with spring loaded latching handles with interior and exterior access. The upper section shall have aluminum double doors with interior access only. Both sections shall have (1) shelf in each.</p>	
	<p align="center">ATTENDANT SEAT</p>	
	RR, Attendant's Seat, EVS 1880, Child safety, Comfort, Per4Max Belt-Black	1
	RR, Color - Gunmetal	1
	RR, Attendant's Seat Base, EVS Swivel 2 Pos	1
	<p align="center">RR-INTERIOR COLORS</p>	
	RR, Thermoplastic, Anti-microbial, Interior Finish	1
	RR, Thermoplastic, Anti-microbial, Cardiac Cadet, Cabinet finish	1
	Part Number #KD18805	

	DESCRIPTION	QTY
	RR, Upper Band Vinyl Color, Cabinets and Stitched Cushions Upper Band Vinyl Color Choice for cabinets and stitched cushions.	1
	RR, Color, Weathered Gray ALG-7052	1
	RR, Lower Band Vinyl Color, Vacuum Formed Cushions	1
	RR, Color, Gunmetal	1
	RR, Poly carbonate Color Choice	1
	RR, Poly carbonate, Clear 1/4" poly carbonate	1
	RR-MISC. INTERIOR OPTIONS	
	RR, Interior Cabinet Lights, LED Strip, White	1
	RR, Upper Left Cabinets, 2, 2.5, 3, 4, 7 & 7.5	1
	CABINET KICK PANELS	
	RR, Squad Bench & Lower Left, 11 Inch Brushed Stainless Kick panels The kick panel shall be approximately 11 inches high and shall run the full length of the squad bench and lower left wall.	1
	RR, Interior Access, #6 Compartment, w/ Hinged Poly carbonate Door, CN 10 Certif The patient compartment shall include a inside/outside access to the #6 compartment. The access opening will be fully framed and will include an aluminum framed, single hinged, 1/4" Poly carbonate door with an integral latch. The access will be installed at the forward portion of the #6 compartment, and facing the aisle. The door will extend from the highest possible/practical point of the compartment down to the level of the squad bench lids and will be full width from compartment wall to divider. Exterior shelf retaining lip to be aligned with door opening.	1
	CABINET LATCHES- INTERIOR	
	RR, Cabinet Latch, Southco 2" Round, Stainless Locking, CN 10-Rated 10lb	18
	GENERAL WIRING	
	RR, General Wiring, General Harness	1
	CAMERAS	
	RR, Camera System, Ext Back-Up, Over Rear Doors, Includes LCD Monitor, Ign Hot Install one (1) Audiovox, ASA Voyager VCMS-24 color camera.	1
	RR, Mirror Mount for Monitor. For chassis without OEM Rearview Mirror Includes installation of OEM style button mount on windshield glass. The monitor will mount to the windshield ILO a rear view mirror.	1
	RR-COMMUNICATION	
	RR, Two Way Radio Routing Path Cab to Module	1
	RR, Two Way Radio Pre wire, 12VDC Power & Ground #8 gauge Red power and Black ground wiring will be labeled appropriately for future installation by a radio technician. The Black ground wire to be connected to a main ground point, the Red power wire to be left unconnected near a direct to battery connection point inside the power distribution cabinet. Both wires to route to the lower section of the Left Stack/Radio	1

	DESCRIPTION	QTY
	Cabinet and be of sufficient length to allow routing to the Cab Console as an alternate radio installation location. Wires to be labeled at both ends.	
	RR, Antenna UHF/VHF, (2) Pre wire, two RG58AU low loss cables installed from the two-way radio cabinet to the ceiling of the module. Accessible be removing an interior light in the patient compartment ceiling. The interior light shall include an etched plastic label identifying the plate as the antenna access point. The cables shall route from the module roof to the lower section of the left stack/radio cabinet and be of sufficient length to allow routing to the cab console as an alternate radio installation location.	1
	RADIO AND CLOCKS	
	RR, Clock, Analog, Trintec 12/24 Hour, Over Rear Doors Trintec 12/24 Hour Clock, Battery Powered, Over Rear Doors - Trintec 6" inch, dry cell battery operated electric 12/24 hour analog clock with sweep second hand, recessed in cushion over rear doors.	1
	RR, Speakers, Mounted in Ceiling w/Volume Control in Action Wall The speakers shall be recessed in the ceiling. There will be a volume control located in the action area.	1
	07 - ELECTRICAL 12 VOLT DC	
	RR, Electrical System 12V, Multiplex System, Type 3 (UM,UM-150)	1
	RR, Crct Pwr Accs.,Ign/Shrline,1-20 amp 12VDC to 2 locs,W/O,PD9330 chrgr (1) 10 amp lead shall be coiled up behind the A/A panel for future use. (1) 10 amp lead shall be coiled up behind the drivers seat in the cab, for future use. Note: This code will be used when and additional battery charger has already been installed, the PD9130 will not be used with this option.	1
	VOLTMETER	
	RR, Voltmeter - Standard	1
	RR, Alarm,Low Voltage,With Buzzer and Indicator,in cab console	1
	AMMETER	
	RR, Ammeter - for multiplex system	1
	BATTERY SYSTEM	
	RR, Ignition Battery Shut off Timer, 5 minute (Multiplex)	1
XS	RR, Battery Additional, Group 31T, Interstate	2
	RR, Module Disconnect, Multiplex System	1
	RR-Battery Ground	1
	RR, Battery Charger, Iota, 45Amp, Charger/Converter DLS-45	1
	12VDC OUTLETS	
	RR, Power Outlets 12V, (2) Power Point Style, On with Ignition (1) outlet shall be mounted in the action area medical rail. (1) outlet shall be mounted above the shelf in cabinet L8 On with ignition.	1
	RR, (2) Additional 12V Outlets, Direct to Battery (1) Forward action wall next to standard (1) aft of CPR seat over rear monitor shelf.	1

	DESCRIPTION	QTY
	RR, Power Outlet, Kussmaul, USB Dual Port, 5VDC, 4.8 Amp, 091-219-5 Located in the cab switch panel per Electrical Engineering ignition hot standard.	1
	FRONT CONSOLE	
	RR, Console, Drivers Switch & Radio, Multiplex, E-Series, CN11 Aluminum console finished with black polyurea,(ECN-2071)	1
	RR, Clipboard/Map box, w/3 Dividers	1
	RR, Driver's Control Panel, Smart Display 5.0, 7" Touch Screen Smart Display 5.0 Multiplex Electrical System. IP67 - 7.0" Touch Screen Display. Includes a (5) button multiplex switch panel on the center console, just under the display. These switches shall operate the following: <ul style="list-style-type: none"> * Outside Left Switch: Emergency Master * Inside Left Switch: Park Over Ride * Center Switch: Siren/Horn * Inside Right Switch: Dome Light * Outside Right Switch: Module Power 	1
	RR, Door Open Indicators (Multiplex) Door Open Indicators, - Magnetic Proximity Switches located at the top of the door between the jamb and the door frame will activate a door open indicator on the driver's control panel. The Multiplex display screen will include a digital layout with door open indicators for each module door and activate the corresponding Interior compartment light. NOTE- OPEN CAB DOOR WILL NOT BE SHOWN ON DISPLAY.	1
	ATTENDANT CONTROL PANEL	
	RR, Attendant Control Panel, Smart Display 5.0, 7" Touch Screen Smart Display 5.0 Multiplex Electrical System. IP67 - 7.0" Touch Screen Display. Include a (5) button multiplex switch panel on the attendant rear control panel, just under the display. These switches shall operate the following: <ul style="list-style-type: none"> * Outside Left Switch: Suction * Inside Left Switch: O2 Valve * Center Switch: Bench Lights * Inside Right Switch: Cot Lights * Outside Right Switch: Dome Lights 	1
	POWER DISTRIBUTION	
	RR, Power Distribution, SMART DISPLAY 5.0, Video Inputs (UM) Includes (2) High Content I/O S-Node and (1) 8x16 S-Nodes. Includes an O2 Regulator/Transducer Mounted in #1 Compartment. INCLUDES S-CORE VIDEO INPUTS MODULE FOR BACK-UP/INTERIOR CAMERAS and up to 3 additional video inputs to be viewed in the front cab display. (4) Inputs total. (CURRENTLY NOT ABLE TO HAVE A BACK UP/INTERIOR CAMERAS VIEWED IN THE FRONT CAB DISPLAY. MUST ORDER SEPARATE MONITOR. CHECK WITH OUR SALES	1

	DESCRIPTION	QTY	
	<p>DEPARTMENT FOR AVAILABILITY.)</p> <p>NOTE: The battery shut-off circuit to remain on for 5 minutes after the ignition has been shut off. Shutting off the ignition will activate a timer that will leave the batteries on for five minutes so that the module dome lights can be left on for patient unloading/vehicle restocking.</p> <p>Clock - Digital, Rear Control Panel, Smart Display 5.0 display Voltmeter - Standard for Multiplex System.</p> <p>Alarm, Low Voltage. Console, Multiplex System Ammeter - for MULTIPLEX ELECTRIC SYSTEM. Multiplex Module Disconnect - Smart Display 5.0 Multiplex Electrical System</p>		
	<p>RR, Warning Audible - Siren Speakers, Air Horns-E-series</p> <p>SIREN ELECTRONIC - CONTROL HEADS / AMPS</p> <p>RR, Siren Electronic, Whelen 295SLSA1, California Title 13 Compliant</p>	1	
	<p>SIREN SPEAKERS</p> <p>RM, Speakers, (2) CPI "Though-The-Bumper" for E-Series</p>	1	
	RR, Backup Alarm, No Cutoff	1	
	RR, Emergency Sequencer/Load Manager	1	
	<p>TRAFFIC MANAGEMENT LIGHTS</p> <p>RR, Traffic Advisor, Whelen TAL85, 47" (8) 5MM LED,W red ICC lights, Mod Pwr</p> <p>TAL85 Traffic Advisor. Whelen Low Profile #TAL85 with (8) 5mm LED Traffic Advisor mounted above rear doors with control head in radio console. NOTE: The Traffic Advisor shall be wired directly to the batteries.</p> <p>For use without a rear Lightbar.</p>	1	
	<p>WARNING LIGHT LOCATIONS</p> <p>FRONT WARNING LIGHT CONFIGURATION</p> <p>RR, Visual Warning Front Upper - (7) Seven Light "W" Pattern Configuration</p>	1	
	<p>AUXILLARY EMERGENCY LIGHTS</p> <p>RR, Emergency Flashers Set to, "X" Flash Pattern</p> <p>The vehicles emergency flashers shall flash in an "X" flash pattern.</p> <p>Flash pattern as follows:</p> <ul style="list-style-type: none"> - Street side front corner - A - Curbside rear corner - A - Street side rear corner - B - Curbside front corner - B <p>Grill lights, Intersection lights and lights showing through rear door windows to be in an 'X' pattern with upper module lights</p>	1	
	<p>WARNING LIGHTS</p> <p>LED Series - 900 (Flange Separate)</p> <p>RR, Light, Whelen 900 LED, w/Chrome Flange, Red w/Clear Lens (Internal Flasher)</p>	10	
	<p>FRONT UPPER BODY LIGHTING</p> <ul style="list-style-type: none"> - Front Body - Upper Curbside Corner - Front Body - Upper Street side Corner - Front Body - Upper Curbside Inner - Front Body - Upper Streetside Inner 		
	<p>MODULE SIDES LIGHTING</p> <ul style="list-style-type: none"> - Street side Body - Upper Forward - Street side Body - Upper Rear 		

	DESCRIPTION	QTY	
	- Curbside Body - Upper Forward - Curbside Body - Upper Rear		
	MODULE REAR LIGHTING - Rear Body - Lower Street side through window - Rear Body - Upper Curbside through window		
	Double Flash 150, via the multiplex Primary / Secondary		
	RR, Light, Whelen 900 LED, w/Chrome Flange, Amber w/Clear Lens (Internal Flasher)	2	
	MODULE REAR LIGHTING - Rear Body - Lower Curbside Window - Rear Body - upper streetside window		
	Double Flash 150, via the multiplex Primary / Secondary		
	RR, Light, Whelen 900 LED, w/Chrome Flange, White (Internal Flasher)	3	
	FRONT UPPER BODY LIGHTING - Front Body - Upper Center - Front Body - Upper Street side Outer - Front Body - Upper Curbside Outer		
	Double Flash 150, via the multiplex Primary Only		
	LED Series - 700 (Flange Separate)		
	RR, Light, Whelen 700 LED, Red w/Clear Lens (Internal Flasher)	2	
	FRONT FENDER INTERSECTION LIGHTING - Front Fender Warning - Intersectors - LH Side - Front Fender Warning - Intersectors - RH Side		
	Double Flash 150, via the multiplex Primary / Secondary		
	LED Series - 600 (Flange Separate)		
	RR, Light, Whelen 600 LED, w/Chrome Flange, Red, Clear Lens (Internal Flasher)	2	
	MODULE REAR LIGHTING - Rear Body - Upper Street side Outer Corner - Rear Body - Upper Curbside Outer Corner		
	Double Flash 150, via the multiplex Primary / Secondary		
	RR, Light, Whelen 600 LED, w/Chrome Flange, Amber, Clear Lens (Internal Flasher)	3	
	MODULE REAR LIGHTING - Rear Body - Upper Curbside Inner Corner - Rear Body - Upper streetside Inner Corner - Rear Body - Upper Center		
	Double Flash 150, via the multiplex Primary / Secondary		
	WHELEN ION WARNING LIGHTS (Flange Included)		

	DESCRIPTION	QTY
	RR, Light, Whelen, ION, WIONSMCR, Red,Clear lens, w/chrome flange FRONT GRILL LIGHTING - Grille - LH Upper Corner - Grille - RH Upper Corner Double Flash 150, via the multiplex Primary Only	2
	Whelen 700 Light head Flanges / Options RR, Housings, Cast, 15 degree angled, 7x3, Intersection, E-series, Pair There shall be a pair of Cast Products housings for the 7x3 intersection lights mounted on the front fender of the chassis. These housings shall incorporate a 15 degree forward angle so the lights shall shine into the intersection prior to the vehicle entering the intersection	1
	EXTERIOR AUTOMOTIVE LIGHTING RR, Tail Lights, Brake/Turn, Whelen 600-Series, Pair To be mounted vertically above the rear diamond plate area.	1
	RR, Back-up Lights, Whelen 600, LED Rear (Max-Intensity), Pair To be mounted above the rear diamond plate area in line with the brake/tail lights and turn signals.	1
	ICC/MARKER LIGHTS RR, Marker/Clearance Lights, Front, Trucklite Model 33 LED, Amber The front of the module shall have (5) amber clearance lights.	1
	RR, Marker/Clearance Lights, Side and Rear, TruckLite Model 33 LED, Red/Amber The side body marker lights and rear clearance lights shall be TruckLite Model 33 3/4" grommet mounted LED type. There shall be (2) Amber mounted at the forward end of each side module roof extrusion, (2) Red mounted at the rearward end of each side module roof extrusion and (5) Red mounted in the rear module roof extrusion. In addition there shall be (2) Red marker lights on each side in the midline of the body at the rear. (1) On each side shall function as a marker light and (1) will function as a turn signal.	1
	RR, Chrome Flange, (1) Whelen 600 RR, Taillight Chrome Flanges, (6) Whelen 600 RR, Outboard Rear Flashers, Wired to OEM Brake Lights The outboard rear emergency flashers shall be wired to the OEM brake lights. These lights shall NOT function as brake lights when Emergency Flashers are on.	1 1 1
	RR, Marker/Clearance Lights, Side, Crash Rail TruckLite Model 33 LED, Red/Amber (3) Amber at Streetside side towards the front. (3) Amber at Curbside side towards the front. (3) Red at Streetside side towards the rear. (3) Red at Curbside side towards the rear. (12 lights total)	1
	NOTE : ALL LIGHTS IN CRASH RAIL TO HAVE 12" SERVICE LOOP AT EACH FIXTURE.	

DESCRIPTION		QTY
FLOOD AND LOAD SYSTEMS		
	RR, Scene Lighting, (4) Whelen 900 Series Halogen, 8-32ø, Steady Burn MODULE SIDES LIGHTING -Street side Body - Upper Forward -Street side Body - Upper Rear -Curbside Body - Upper Forward -Curbside Body - Upper Rear	1
U	RR, Rear load Lights Whelen 600 Series LED Scene Lights (2) SR #2026172F Install (2) Rear Load Lights Model #6SC0ENZR	1
	RR, Lighting Operation, Side Scene, Rear Load & Back-Up Lights The electrical system shall be wired so that the rear module load lights and the lower back-up lights will operate when the rear doors are open, the switch on the front panel is activated, or when the vehicle is placed in reverse. With the module power switch "off", both the lower back-up lights and the upper load lights will operate when the vehicle is placed in reverse. The curbside scene lights will operate when the curbside door is opened.	1
	RR, Lighting Operation, Feature, Scene & Load Light, Auto-Reset Cutout Switch (1) Momentary cutout switch located on curbside wall over head of squad bench and (1) momentary cutout switch on curbside rear door panel. Closing the doors will reset the circuits.	1
	RR, Fog Lights, (2) PIAA LP530 Round Amber LED Ion The manufacturer shall install a set of PIAA LP530 Series Amber LED Ion wide spread fog lights with switch located in the front switch panel.	1
11 - INTERIOR LIGHTING		
	RR, Dome Lights - (11) Kinequip 8" Round LED The interior lighting system shall consist of (11) Kinequip 8" Round LED Dome Lights fixtures in the following configuration: (3) Cot lights In the medical device rail over the primary cot (2) Bench lights over the squad bench (3) Dome lights Street side (1) Dome light Curbside over head of squad bench (1) Dome light Curbside rear (1) Dome Light over the walkway The four outside corner lights and the (1) light over the CPR seat area and the (1) over the walkway shall be designated module dome lights and be activated when the side or rear module entrance doors are opened or by a three-way circuit allowing these lights to be turned on and off from cab or module. The lights over the primary cot and squad bench shall have switches in the module that will allow independent high/low/off control.	1
	RR, Timer -15 minute- Restocking The vehicle shall be equipped with a momentary switch that will activate a fifteen minute timer, wired direct to battery, to allow operation of the module dome lights while the vehicle is off. This	1

	DESCRIPTION	QTY
	feature will enable personnel to clean and restock the vehicle, but eliminates the risk of leaving the lights on and draining the batteries. The momentary switch shall be located on the curbside wall near the side entrance door.	
	SPOTLIGHTS / HANDHELD LIGHTS	
	RR, Handheld Spotlight - Sho-Me 200,000 CP, Mod Power The cab shall be equipped with a spotlight with a coiled cord that is hardwired "On" with Ignition. The handle shall include a momentary switch. The bulb shall be a 12V - 200,000 candle power sealed beam non-glare bulb.	1
	ATTENDANT LIGHT	
	RR, Attendant Light - LED Strip Under UL2-2.5 Cabinets, Action Wall There shall be LED strip lighting under the upper left #2 and #2.5 Cabinets. The LED light strip shall be mounted in an anodized aluminum channel on the bottom surface of the cabinets close to the action wall and shall run the full length of the Upper Left #2 and #2.5 cabinets to illuminate the action counter area. This light will be controlled with an On/Off switch on the rear switch panel.	1
	SHORELINE INLET	
	RR, Shoreline Inlet, Kussmaul Super Auto-Eject, 20A Shore Inlet, 20 AMP, Auto Eject. 20 AMP/125VAC shoreline inlet in lieu of standard 15 amp. Includes mating female connector body for inlet and 20 amp GFI circuit breaker combo in lieu of standard 15 amp. Install the breaker box installed behind the driver's seat.	1
	RR, Kussmaul, Eject,Cover,15 or 20A,White	1
	RR, GFI Box Location- Behind Driver's Seat	1
	OUTLETS - 125VAC	
	RR, Outlets, Interior, 125V-15A (1) Action Wall, (1) Right Stack (1) outlet shall be mounted on the action area medical rail (1) outlet shall be mounted above the shelf in cabinet L8.	1
	RR, Outlets, Interior, Each, Additional, 125V-15A, Aft CPR Seat Counter There shall be one 125VAC 2-wire plus ground illuminated 15 amp duplex outlet on the street side device rail aft of the CPR seat.	1
	BLOCKHEATERS	
	RR-Block Heater, Engine, W/Switch, Wired to Shoreline The chassis shall include a 110VAC powered engine block heater. The block heater shall be wired to the module shoreline system and will include an OEM disconnect located in the engine compartment. In the driver seat area, there shall be an On/Off switch with pilot light for the engine block heater, powered from shore.	1
	INVERTER - 125VAC	
	RR, Inverter Charger - Pre wire, Under 2000W Wiring only for 1200 watt maximum 'UL' listed inverter with internal transfer relay and battery charger. Wiring setup is for installation in bottom section of Left Stack/Radio Cabinet. Includes remote on/off switch in the rear switch panel.	1

	DESCRIPTION	QTY	
	13 - ENVIRONMENTAL SYSTEMS		
	ENVIRONMENTAL CLIMATE CONTROL SYSTEM		
	RR, HVAC - Central Air Flow Discharge (UM & UM-150)	1	
	RR, Climate Control - (UM & UM-150)	1	
	RR, Exhaust Fan - 100 CFM Standard Location	1	
	The patient compartment shall include a 100CFM, high output exhaust fan and exhaust cowl vent installed on the rear of the module on the street side rear panel. The exhaust fan shall include an On/Off switch in the rear control panel.		
	HVAC BASE SYSTEM - HOSELINE BRUSHED		
	RR, Heat/AC Base System, Hoseline, Ford E-series, BRUSHLESS Motor	1	
	RR, Thermostat, In Multiplex Display, Temperature Sensor in Air Return	1	
	RR, Return Air System	1	
	RR, Return Air Central Plenum	1	
	RR, Heat/AC Cabinet	1	
	14 - MEDICAL SYSTEMS		
	COT MOUNTING PROVISIONS		
	RR, Cot Mounting, Hardware	1	
	RR, Post & Wheel Cups, None	1	
	RR, Safety Hook, Ship Loose	1	
	RR, Safety Hook, Stryker with bolts, Shipped Loose	1	
	RR, Stryker Performance/Power Load, Add Floor Structure Plates & Wiring for Futu	1	
	Additional floor structure for future installation of a Stryker Power Load or Performance Load w/ inductive charging System.		
	RR, Cut Floor and Install Cot Mount Floor plate, 6390-700-001A, for Performance	1	
	For Performance Load Cot mounts. Note: Stryker Deutsch connection to be coiled up on the interior of the module.		
	Center Mount	1	
	OXYGEN AND AIR SYSTEMS		
	RR, O2 System, Multiplex (Senson), Mod Pwr	1	
	RR, O2 Cylinder Wrench	1	
	RR, O2 Cylinder Bracket - Zico #QR-MV	1	
	RR, O2 Control - Electric with Manual Bypass on Action Wall.	1	
	The vehicle shall be equipped with an electric O2 solenoid valve to turn the 50 PSI supply to the oxygen outlets on and off. The valve shall be controlled by an "On/Off" switch located on the rear switch panel. The valve shall also provide a manual by-pass feature for emergency use in the event that power to the solenoid is interrupted.		
	RR, O2 Outlets, Ohio Style, (2) Action Wall, (1) Squad Bench	1	
	(2) O2 outlets in Action area medical device rail (1) O2 outlet CS Wall head of squad bench in medical device rail		
	*** NOTE *** O2 outlets MUST be at least 12" from any 125V AC outlet.		
	RR, O2 Outlet, Ohio Style, Additional in Ceiling	1	
	There shall be one (1) Ohmeda/Ohio style O2 outlet located in the ceiling above the primary cot location		
	PORTABLE O2 HOLDERS		

	DESCRIPTION	QTY
	RR, O2 Cylinder Holder, Zico QR-D-2 Strapless "D" Bracket, CN 10 Certified, Each Oxygen bottle brackets at the forward end of squad bench.	2
	SUCTION SYSTEM	
	RR, Suction System, SSCOR On-Board To be install on the Medical Device Rail at the action wall #2	1
	MISC MEDICAL	
	RR, Fire Extinguisher, 5# ABC w/ Mounting Bracket HD Amerex Bracket #861H with Amerex 5LB fire extinguisher. SHIPPED LOOSE	1
	15 - PAINT / DECALS AND NOMENCLATURE	
	PAINT AND FINISH	
	RR, Road Rescue Paint Process	1
	Module Paint, Single Color, OEM White Ford white: FA91:YZ	1
	Cab Paint - Single Color, OEM White	1
	RR, Pinstripe, None, Fine Line Paint Edge	1
	GRAPHICS AND LETTERING	
	RR, Badge Logos	1
	RR, Logos and Model Name	1
	RR, Ultramedic - Black Logos	1
	RR, Nomenclature Plaques. UNLEADED.	1
	RR, Owner's Manual	1
	Indemnification Statement	1
	The purchaser agrees to defend, indemnify and hold Rev Ambulance Group harmless from any claims, costs (including actual attorneys' fees), damages and liabilities caused in whole or in part by any alteration or modification of, or changes or additions to the purchased products OR use of product for purposes it was not designed or intended for.	