

Specification Summary

Name	Specifications
Type I - MXP150	Overall Length 285" - 291" (724 cm - 739 cm) Overall Width 95" (241 cm) Overall Height 110" (279 cm)** Headroom 72" (183 cm) Wheelbase 165" - 168" (411 cm - 427 cm)* Payload Capacity Up to 4500 lbs (2041 kg) *Depending on chassis selection **Total height of vehicle may differ according to chassis and suspension



Sales Options by Category

0-Change Order (CO)

Name/Description	Quantity
change order - digital clock	1.00
change order - Apr.20th,2026(AM)rev.4; analog clock is no longer offered. Digital clock selected in cpq config. Credit for the price difference.	
change order - upgrade to 4 pts and SAEJ3026	1.00
upgrade safety belts to 4pts 1 click and upgrade to meet SAEJ3026 requirements.	

10-Base (BAS)

Item Number	Name/Description	Quantity
	TYPE I - MXP150	1.00
	TYPE I - MXP150	



Type I - Pick up	1.00
Type I - Pick up	

11-Chassis (CH*)

<i>Name/Description</i>	<i>Quantity</i>
Conversion Ford F350/F450 Chassis Cab	1.00
Conversion Ford F350/F450 Chassis Cab	
Ford F350XLT Super Duty Diesel Chassis Cab 4X4 169	1.00
Ford F350XLT Super Duty Diesel Chassis Cab 4X4 1696,7L POWER STROKE V8 Diesel EngineWheelbase 169" (4293 mm)GVWR (Gross vehicle weight rating) 13,300 Lbs / 6,033 Kg	

13-Module (MOD)

<i>Name/Description</i>	<i>Quantity</i>
MXP150 Ambulance Module	1.00
All Aluminum ambulance module structure, doors structure and accessories. (Included)	

14-Module Configuration (MCF)

<i>Name/Description</i>	<i>Quantity</i>
C1 Door, ALS Access and Battery Location	1.00
First door on curbside (C1) for ALS compartment access and battery slide out sealed compartment. (Included)	
C2, Curbside Entry Door	1.00
Side entry door on curbside (C2) for patient compartment access, with flush-mounted, automotive-style window.	
C3 Door, Storage Exterior Compartment	1.00
Third door on curbside (C3) for backboard or other storage.	
Premium Backboard Dividers, Two (2), with Belts	1.00
Two (2) adjustable Premium backboard dividers, with belts, in C3 compartment.	
4"-Diameter Compartment Lights, LED	1.00
4"-diameter LED Compartment lights. With Side entry Door Steps.	
A1 and A2, Rear Entry Doors, Indiv. Door Handles	1.00
Two (2) rear entry doors for patient compartment access, each with its individual exterior door handle.	
S1 Door, Main Oxygen Exterior Compartment	1.00
First door on streetside (S1) for main vertical oxygen cylinder.	
S2 Door, Storage Exterior Compartment, Electrical	1.00
Second door on streetside (S2) for equipment storage. Upper enclosed electrical compartment. MX164/MXP150	
Spare Tire Storage	1.00
Reinforcement for spare tire storage.	
S3 Compartment, Equipment Storage, Short	1.00
Third door on streetside (S3) short for equipment storage.	

15-Lighting (LGT)

<i>Name/Description</i>	<i>Quantity</i>
Turn Signal Lights, Amber (2), LED	1.00
Two (2) amber turn-signal lights, intermediate side mount. Whelen 700 series (7 x 3) LED lights.	
Third Upper Brake Light, LED	1.00
Third upper brake light at rear of module. Whelen 600 series (6 x 4) LED light.	
Rear Step Plate: Turn Signal Light, Brake, Reverse	1.00

Two (2) red brake/tail lights, two (2) amber turn lights, and two (2) reverse lights installed in rear step plate. Round LED lights.

Marker Lights, Amber (7) and Red (7), LED 1.00

Seven (7) front upper center and corner amber LED marker lights. Seven (7) rear upper center and corner red LED marker lights.

16-Emergency and Working Lights (EWL)

<i>Name/Description</i>	<i>Quantity</i>
Chrome bezels	26.00
Chrome bezels	
No Emergency Lights on Inside of Doors	1.00
No emergency lights on the compartment and entry door inside panels.	
Emergency Lights, (5) LED (900)	1.00
Five (5) emergency lights installed on the front of the module. Whelen 900 series (7 x 9) LED lights. (Standard setup includes two (2) red, one (1) white, and two (2) red)	
Lights in Front Grille, (2) LED (500)	1.00
Two (2) lights in front grille. Whelen 500 series (5 x 1) LED lights. (Standard setup includes red lighting)	
Intersection Lights, (2) LED (700)	1.00
Two (2) intersection lights. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red lighting)	
Emergency Lights, (2) LED, Inter. Side Mount (700)	1.00
Two (2) emergency lights, intermediate side mount. Whelen 700 series (7 x 3) LED lights. (Standard setup contains red lighting)	
Scene Lights, Four (4), Clear LED, (900)	1.00
Four (4) lateral scene lights (two (2) on each side). Whelen 900 series (7 X 9) LED scene lights.	
Four (4) LED lateral emergency lights (900)	1.00
Four (4) lateral emergency lights (two (2) on each side). Whelen 900 series (7 x 9) LED lights. (Standard setup contains red lighting)	
Loading Lights, Two (2), LED (600)	1.00
Two (2) rear loading lights. Whelen 600 series (6 x 4) LED lights.	
Emergency Lights, (2) LED, Rear Corners (900)	1.00
Two (2) rear emergency lights at upper rear corners. Whelen 900 series (7 x 9) LED lights. (Standard setup contains red lighting)	
Emergency Lights, (2) LED (600)	1.00
Two (2) rear upper lights. Whelen 600 series (6 x 4) LED lights. (Standard setup contains amber lighting)	
Emergency Lights, (2) LED, Addt'l, Window Hgt (900)	1.00
Two (2) additionnal lights at window height. Whelen 900 series (7 x 9) LED lights. (Standard setup contains red lighting)	

17-Audible Warning System (WRN)

<i>Name/Description</i>	<i>Quantity</i>
Back-Up Alarm	1.00
Back up alarm (97dB) with override switch.	
Whelen 295SLS Hands-Free Siren	1.00
Whelen model 295HFSA1 siren amplifier with 17 Scan-Lock™ siren tones.	
Whelen SA315 Series Speakers	1.00
Whelen SA315 series speakers is a compact speaker meeting SAE Class A requirements when paired with Whelen 100 watt siren amplifier.	

18-Exterior Vehicle features (VFT)

<i>Name/Description</i>	<i>Quantity</i>
OEM exterior mirrors Keep OEM exterior mirrors	1.00
Module Rub Rails, Aluminum Aluminium rub rails on module sides.	1.00
Module Corner Protectors, Stainless-Steel Stainless-steel protectors on module corners.	1.00
Module Wheel Trims, Fiberglass Formed fiberglass wheel trimming on module.	1.00
Undercoating Protection Undercoating protection for module and chassis.	1.00
Rear Wheel Mud Guards Mud guards on module for rear wheels.	1.00
License Plate with Light Surface mounted license plate location with LED light.	1.00
Cab Steps, Anti-Skid Material with Mud Guards Anti-skid lateral steps. Includes mud guards for front wheels.	1.00
Rear Step Bumper, Retractable Center Section Anti-skid rear retractable step. Diamond plate corner bumper. Rubber bumperette. (Included)	1.00

19-Convenience (CNV)

<i>Name/Description</i>	<i>Quantity</i>
Valet Switch in Front Grille The door unlock valet switch is located on the back of the front grille, on the driver's side half portion of the grille. It allows to unlock all doors of the vehicle, but cannot lock the doors.	1.00
Demers Fast Idle Demers fast idle is generated by the multiplex module, it allows fast charging of the batteries by the engine when specific conditions are met. (Included)	1.00
Black Back-Up Camera RearView Safety standard back-up camera with build-in audio support and infra-red night vision.	1.00
Anti-Theft System The anti-theft allows leaving the vehicle without keys and the engine running to keep the vehicle at the ideal operating temperature. It protects against theft by turning off the engine if the vehicle moves. (Included)	1.00
ECOSMART Anti-Idling System The ECOSMART Anti-Idling System automatically stops and restarts the engine of the vehicle in idling conditions. The ECOSMART Anti-Idling System is managed by the Demers Electronic MultiplexSystem (DEMS).	1.00

21-Paint and Decals (DEC)

<i>Name/Description</i>	<i>Quantity</i>
Urethane Paint Two (2) coats of primer with two (2) coats of urethane. All four (4) sides and roof. No sanding. No buffing.	1.00

22-Drivers Compartment (CAB)

<i>Name/Description</i>	<i>Quantity</i>
-------------------------	-----------------

Spotlight in Front Cab, Hand-Held, with Bracket	1.00
Hand-held spotlight, 2000 lumens, with trigger-type switch and bracket.	
Floor-Mounted Console with control	1.00
Floor-mounted console in front cab.	
Armrests, Driver and Passenger, Individual	1.00
Individual driver- and passenger-side armrests on sides of floor-mounted console.	
Cup Holders, Dual, in Floor-Mounted Console	1.00
Dual cup holders in floor-mounted console.	
Control Center with Switches and Touch Pad	1.00
Control center with switches and LED backlit pictograms in the floor mounted console.	
Cab headliner with Reading Lights, Red/Clear (2)	1.00
Two (2) clear and red overhead LED reading lights.	

23-Curbside Configuration (CRB)

<i>Name/Description</i>	<i>Quantity</i>
Safety Net	1.00
Safety net at the head of the curbside configuration, by the side entry door (C2).	
Full-Length Seat Cushion	1.00
Full-length, thermoformed, molded seat cushion.	
Seat Backrest	2.00
Individual, thermoformed, molded backrests.	
Seating, Two (2) Passengers, 6Pts Safety Belts	1.00
Seating for two (2) passengers with 6-point safety belts.	

24-Streetside Configuration (STR)

<i>Name/Description</i>	<i>Quantity</i>
Polycarbonate Tinted Sliding Windows	3.00
Polycarbonate tinted sliding windows.	
Medical Cabinet, CPR Bench Seat	1.00
Medical cabinet with CPR bench seat.	
CPR Seat , 6-Pt Safety Belt	1.00
Seating for one EMT with 6-point safety belt.	

25-Forward Bulkhead (FWB)

<i>Name/Description</i>	<i>Quantity</i>
Sliding Window Pass-Through	1.00
Pass-through sliding window on front division for communication with cab.	
Locking Radio Communication Compartment	1.00
Lockable compartment for radio communication	
ALS Cabinet, without Drawer	1.00
ALS cabinet on curbside of front wall. Includes four (4) aluminum extruded doors with see-through windows, adjustable shelf(s), one (1) fixed shelf at mid-height, LED strip lighting, and inside/outside access via curbside door.	
Compartment above ALS Cabinet, Lockable	1.00
Lockable compartment located above the front wall ALS cabinet.	
See-Through Door, Two Handles	1.00
Four (4) extruded doors with see through windows and handles	

26-Attendant Seat (AST)

<i>Name/Description</i>	<i>Quantity</i>
EVS Swivel Seat Base, Two (2) Positions	1.00
EVS swivel 360 degrees seat base, locking in two (2) positions, forward and rearward positions	
EVS 1880 3Pts Vac-Formed Seamless Child Seat	1.00



The EVS 1880 is a vac-form, seamless ambulance attendant's seat. Integrated child restraint system that allows uninjured children weighing between 20-65 lbs to be transported in a five point safety harness. When it is not needed, the child-insert can be folded into the seat and allow an adult to use the seat as a standard attendant's seat

27-Cot Configuration (COT)

<i>Name/Description</i>	<i>Quantity</i>
Floor Plate & Pre-wire Power-LOAD - GEN 2 (NEW) Stryker Power-Load floor plate. No cot fastener included. Include pre-wiring for charging feature. Default option for new Power-LOAD system from the field.	1.00
Center Floor-Mount Cot Configuration Center floor mount cot configuration	1.00

28-Rear Control Panel (CAR)

<i>Name/Description</i>	<i>Quantity</i>
Rocker Switch Controls with LED Backlit Pictograms Rocker switch controls with LED backlit pictograms.	1.00

29-Oxygen (OXY)

<i>Name/Description</i>	<i>Quantity</i>
Oxygen Outlets, Two (2) Two (2) oxygen outlets. Two (2) in left wall ECC.	1.00
Oxygen Outlet, Quick-Connect Quick-connect style oxygen outlet.	2.00
Universal Vertical Holder for Main Oxygen Cylinder Universal vertical holder for types "K" or "M" main oxygen cylinder in S1 streetside exterior compartment.	1.00

31-Suction (SUC)

<i>Name/Description</i>	<i>Quantity</i>
Suction System location in ECC Main suction system is located in front streetside action area.	1.00
Thomas high flow vacuum pump Thomas high flow vacuum pump	1.00
Vacuum outlet QD in action area Vacuum outlet QD Puritan with yellow 5/16" hose 4 ft long	1.00
Vacuum regulator with disposable canister Vacuum regulator with disposable canister	1.00

32-Electrical System (ELE)

<i>Name/Description</i>	<i>Quantity</i>
Power Inverter, Xantrex Freedom, True Sine, 1000W The inverter/charger provides AC power using the DC power from the conversion battery bank. Recharge all battery banks and power all 120 volts AC outlets when the external shoreline is connected.	1.00
Super Auto Eject Power Inlet, 20 Amps, Yellow Kusmaull 120 Volts AC, 20 Amps - Automatically disconnects shoreline - Completely sealed - Yellow cover - Indicator light.	1.00
Electrical Outlet, 120V AC with Indicator 120V AC hospital-grade electrical outlets with indicator. (Included)	1.00
Add 120V AC Duplex outlet with indicator	1.00



Additional 120V AC Duplex outlet with indicator. Details and location are as follows:
One Hospital-grade 120 VAC dual outlet with indicator
light in lower ALS area

ACDelco Conversion Batteries(Included) 1.00

Electrical Outlet, 12V DC 20 amp with Indicator 1.00

12V DC, 20 amp Duplex electrical outlets.

Add 12V DC outlet with indicator 1.00

Additional 12V DC outlet with indicator. Details and location are as follows: e 12 VDC
outlet in lower ALS area

Demers Multiplex Electronic Management System 1.00

Demers Electronic Management System (DEMS) – Multiplex system.

33-Communication System (COM)

<i>Name/Description</i>	<i>Quantity</i>
Pre-Wiring for 2-Way Radio, Two (2) Antenna Cables	1.00
Wiring preparation for two-way radio, with two (2) antenna cables.(routed from front cab to radio communication compartment)	
Radio Communications Compartment	1.00
Radio communications compartment universal board, Bussmann blade-type fuse panels, and harness to power the radio communication devices.(12V battery feed, ground, ignition).	
Radio Communications Front Console	1.00
Radio communications front console universal board, Bussmann blade-type fuse panels, and harness.	
Data Recorder Available Signals	1.00
Data recorder available signals through a universal connector in the electrical compartment.	

34-HVAC (CVC)

<i>Name/Description</i>	<i>Quantity</i>
OEM Tie-In Air Conditioning Unit System	1.00
The evaporator is tied-in to the OEM air conditioning system, cooling the air of the patient compartment through the ducted outlets.	
Air Conditioning Outlets, Round	1.00
Round outlets for ducted air conditioning unit.	
OEM Tie-In Heating Unit	1.00
The heating system is an extension of the OEM heating system, heating the patient compartment area through invisible opening underneath the medical cabinet at floor level. (Included)	
Exhaust Fans (2)	1.00
Two (2) exhaust fans for contaminated air. Activated by front control interface or rear console switch.	

35-Interior Lights (ILG)

<i>Name/Description</i>	<i>Quantity</i>
LED Dome Lights, Adjustable, Dig. Timer	8.00
The ceiling lights have four (4) different intensities. Each time the ceiling lights button is pushed, the intensity increases, until maximum intensity is reached.	

36-Grab Handles (GBR)

<i>Name/Description</i>	<i>Quantity</i>
Grab Bars Color, Yellow	1.00
Color of selected grab bars is Yellow.	

Rear Door-Mounted Grab Bars, 16" x 16"	1.00
Two (2) door-mounted grab bars, 16" x 16", inside of rear doors (A1 and A2).	
Curbside Door-Mounted Grab Bar, 12"	1.00
One (1) door-mounted grab bar, 12" each, on the inside of the side entry door (C2). (included)	
Embarking Grab Bars, 12"	1.00
Two (2) entry grab bars, 12" each, mounted inside the patient compartment. One (1) near the curbside entry door, and one (1) near the R2 rear entry door.	
Ceiling Grab Rails, 90", Two (2)	1.00
Two (2) ceiling-mounted grab rails, 90".	

37-Finish and Trim (FNS)

<i>Name/Description</i>	<i>Quantity</i>
Lonseal, Lonplate II, Gun metal	1.00
Lonseal, Lonplate II, Gun Metal floor covering.	
Cobalt Blue Upholstery	1.00
Colbalt blue vinyl upholstery for seat and padding covering.	
Safety Yellow Upholstery	1.00
Yellow vinyl upholstery for safety exit padding covering.	
Wood Flooring	1.00
Exterior grade plywood, 0,75 inches thick.	
Fiberglass Ceiling	1.00
Fiberglass ceiling in Patient Compartment.	
General Vehicle Identification	1.00
Vehicle general labels identification.	

38-Functionality (FCT)

<i>Name/Description</i>	<i>Quantity</i>
Radio Speakers, Recessed, Two (2)	1.00
Two (2) recessed radio speakers.	
Two (2) recessed/flexible IV hooks in ceiling	1.00
Two (2) recessed/flexible IV hooks in ceiling	
Trash Container, Flip-Down, Hands-Free	1.00
Trash container bracket in curbside flip-down container.	
Digital Clock, Driver and Step Indicator Lights	1.00
Digital clock, rear step indicator light, driver intention indicator lights (direction, braker) located in padding above the rear doors.	