MEDIX SPECIALTY VEHICLES, INC.

Unit #:
24-TWGK1549-
24-TWGK1558

DEALER:	**NERV**
CUSTOMER:	**NERV Stock**
Street or P.O. Box	
City, State, Zip	
Customer Contact:	
Customer Email:	
Customer Phone #:	
Sales Associate:	
Sales Engineer:	
VIN#:	

Chassis Model Yr	**2024**
MEDIX Model	**SRH-148WD, Type II - TWGK**
CHASSIS	**Ford 250 MR, AWD Van, 3.5L ECOBOOST V6 Gas, 148"WB, 9070 GVWR, 10 Spd Trans**
BODY	**OEM Van Body w/Mid-Roof**

QTY	STD/OPT	Description
1	**15-2000-TG**	**Chassis & Conversion**
		Chassis Model Year Adjustment
		-
	01-	**Flooring & Interior Colors**
1	STD	**Cabinets:** Laminated Wood **Laminate Color**: **Titanium**
1	STD	**Upholstery:** (Specify Color)
1	STD	**Color**: **Black** Brand: **EVS**
1	STD	**Flooring:** Altro - Transfloor Meta Black
		-
	02-	**Body & Chassis**
1	STD	This chassis is equipped with a Gasoline Exhaust System to meet the EPA standards for Gasoline exhaust emissions
1	**STD**	**Anti-Theft Device: IdleLock Ignition Security System, for Ford Transit Chassis Only. Locate activation button to the right side of the steering wheel.**
1	STD	**Pass-Thru** w/Sliding, latching window that slides behind driver's seat. Window to have full length extruded handle for access.
1	STD	**Bumper:** Transit rear step to have aluminum diamond plate with "Star Punch" surface installed on rear OEM step.
2	STD	**IV Hangers:** (2) Cast black rubber fold-down over chest area of stretcher and Squad Bench.
3	STD	**Mirrors, OEM:** (1) each cab door, (1) on interior windshield
1	STD	Wheel Covers, OEM.
1	STD	OEM fuel fill behind panel by driver's door.
1	STD	**Undercoating:** Per OEM Guidelines
		-
	03-	**Brake, Turn & Back-Up Lights**

1	STD	OEM Standard Stop, Tail and Turn Lights.□
		-
	04-	**Electrical, Power Distribution, Control Center & Interior Lighting**
1	STD	**Battery Switch, Automatic:** TST CDR-400 with mounting plate.
1	STD	**Front Console:** CNC Cut, Formed, Welded and Powder Coated Black housing between OEM seats. Console to include Whelen 295SLSA1 Siren and one removable blank radio plate. Switch panel mounted on OEM engine cowl for visibility.
2	STD	**Antenna, Radio Coax Cables:** Terminated behind driver's seat w/Power & Ground for each
8	STD	**Lights: Dome, LED, w/flange, switched separately with Hi/Lo functions.**
1	STD	**Action Area Light:** 12 VDC LED light, with On/Off switch on rear control panel
1	STD	**USB Port:** Vanner VSS-USB dual port 2Amp mounted on A/A wall
1	STD	**Shoreline:** 125 VAC, 20-amp, 60 HZ, straight blade inlet w/hinged, weatherproof cover. Located on SS behind driver's door.
1	STD	**Timer:** 5-minute check-out, wired to CS High mode dome lights
1	**400160**	**Inverter: Vanner LSC12-1100- 1100watt with 3-Stage 55Amp battery charger, 20Amp power supply and built in GFI. Remote controlled with switch in the rear switch panel. (This option deletes the GFI in the A/A wall). ILOS** **Location: Standard Transit Location behind lower main wall**
1	**400150**	**Electrical: Battery Charger, DELETE STANDARD (when adding Inverter with integral charger)**
1	STD	**Breaker Box**: 125 VAC w/20-Amp Breaker located behind the lower main access panel. GFI receptacle located on the Action Area wall.
3	STD	**12 VDC Outlets:** (2) located in Action Area and (1) located on bulkhead wall above ALS cabinet.
3	STD	**125 VAC Outlet**- (1) on Action Area wall, (1) Curbside wall at the head of the squad bench and (1) located on bulkhead wall above ALS cabinet.
1	STD	**Electrical Cabinet:** Located in upper streetside wall with vented, hinged door powder coated black with (2) flip latches.
		-
	05-	**Warning Lights & Sirens**
1	STD	**Forward Lighting:** (5) Whelen 700 Series Super LEDs: (4)-70R02FCR Red, (1)-70C02FCR White mounted on custom engineered front facing fairing mounted on the OEM roof above the front windshield. R/R/W/R/R.
1	STD	**EMERGENCY/SCENE LIGHTS:** (4)- M9RCZ LED combination Emergency and Scene lights mounted at each upper corner of the OEM chassis w/Whelen angled chrome mounting bezel.

1	STD	**Lights Warning:** (2) Whelen 700 Series Super LEDs Red 70R02FCR, (1) mounted on each outer corner of the rear facing fairing mounted on the OEM roof above rear doors.
1	STD	**Lights Warning:** (1) Whelen 700 Series Amber Super LED 70A02FCR center mounted on the rear facing fairing mounted on OEM roof above rear doors.
1	STD	**Lights Warning:** (2) ION Mini-T series Red LED mounted (1) each side on the OEM front fenders w/chrome bezels.
2	STD	**Lights, Warning, Grille:** ION Mini-T series Red LED w/clear lenses & chrome flanges on center grille bar
2	STD	**Lights, Load:** (2) Whelen 700 Series white LED 7SC0ENZR load lights mounted (1) on each side of the center amber LED on the rear facing fairing mounted on OEM roof above rear doors
1	STD	**Flasher:** Dual mode flasher for Warning Light system, **Vanner 9860GCPE**
2	STD	**Siren Speakers:** Dual 100 watt Speakers mounted behind the OEM front bumper.
1	STD	**Siren:** Whelen 295SLSA1, 200 Watt
		-
	06-	**Oxygen, Vacuum & Miscellaneous Items**
3	STD	**Oxygen Outlets:** Quick-connect style, (2) in Action Area, (1) over Squad Bench
1	STD	**Electric Oxygen with manual bypass** and switch on A/A panel
1	STD	**Suction Aspirator System:** Rico disposable container mounted in Action Area w/gauge and quick-connect; SSCOR vacuum pump mounted in rear air return.
1	STD	**Oxygen Cylinder Retention:** For "M" cylinder, black steel w/3-spring buckle straps and top collar on slide-out, tilt-down tray w/lift strap; Located transverse at bulkhead. Side entry door access. Head of O2 cylinder accessible through sliding window under tech seat
1	STD	**O2 Regulator:** Amvex, 50psi, pre-set
		-
	07-	**AC / Heat**
1	STD	**HVAC System:** High Capacity, Up-Draft Heat/AC System ducted thru angled panel between main and upper cabinets. Multi-speed fan with digital thermostatic control on the action area wall; HVAC unit located behind vented access in lower main cabinet wall.
		-
	08-	**Cabinets, Hardware & Miscellaneous Items**
1	STD	**Main Streetside Cabinet Wall:** Stair chair storage Vertical Slide-in w/single seat belt style restraint strap at left rear entry door, w/(4) cabinets, HVAC access, inverter access and and action area panel designed into the forward wall area. (5) HVAC vents, (2) upper wall cabinet storage and the electrical cabinet designed into the upper/forward section. Cabinets are CNC cut and assembled.
1	STD	Open Floor width 40" from face of street side cabinet to face of squad bench.

1	STD	ALS Cabinet: Storage for 747 with locking flip-down door and LifeDefender latch. Open upper shelf. Lower waste tip-out
1	STD	SO/TD O2 Bracket w/latch and pull strap, accessible through curb side entry door, hinged access door. Head of O2 cylinder accessible through sliding window below tech seat.
1	STD	**Glove Box Holder**: Three-sized cabinet w/hinged, powder coated door recessed into upper bulkhead wall above pass through.
1	STD	Cargo Net @ head of squad bench.
1	STD	**Squad Bench-**Laminated 3/4" plywood.
	1	Full length hinged lid w/TriMark latch for access to interior storage; Full length upholstered seat cushion except over Sharps/Waste Area.
	2	(2) EVS V-4 Belted seating positions w/progressive foam back and head pads and (3) short bottom straps for 2nd Patient restraint
	3	Squad Bench-stainless steel riser on face of bench.
	4	**Sharps**: Drop-in style sharps w/Red powder coated aluminum, hinged lid through head of squad bench.
	5	**Backboard Storage:** Slanted, vertical slot access at curb side rear door built into the aisle side of the squad bench with space for 16"/18" boards.
1	STD	**Technician's Seat:** EVS 1760 seat w/V-4 seat belt system mounted on structure around O2 cylinder; front access to O2 cylinder valve.
1	STD	**Assist Rail:** overhead in center of unit w/radius ends
1	STD	**Grab Handle:** (1) 12" on ALS cabinet to use at side entry door.
1	STD	**Grab Handles:** one on each rear entry door.
4	STD	**Reflective Striping, Door Open Protection**: .50" Red reflective striping around interior door pan of all body doors.
		-
	09-	**Cots & Miscellaneous Items**
1	**99-2011**	**Cot Mount: Stryker, Power/Performance Load Systems, install floor plate assembly "Only" in standard position ILOS 175-5. NOTE: Transit Type II Only.**
		-
	10-	**Paint & Lettering**
1	STD	**Paint:** Body all OEM White
		-
1	**1000100**	**Roof Star ONLY, INSTALLED**

		SHIP LOOSE
2	STD	**Fire Extinguisher:** (2) 5 lb- Ship Loose is Standard